



BE SURE. BUILD SURE.

Page 1/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.03.2023

Version number 23 (replaces version 22)

Revision: 24.03.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name **MC-DUR TopSpeed - Komponente B**

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

· Sector of Use SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

· Product category PC9a Coatings and paints, thinners, paint removers

· Process category PROC10 Roller application or brushing

· Environmental release category

ERC8f Widespread use leading to inclusion into/onto article (outdoor)

ERC11a Widespread use of articles with low release (indoor)

· Article category AC13 Plastic articles

· Application of the substance / the mixture

Polyurethane lacquer

Hardening agent/ Curing agent

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier: MC-Bauchemie Müller GmbH & Co. KG
Am Kruppwald 1-8
D-46238 Bottrop
Tel.: +49(0)2041-101-0
Fax.: +49(0)2041-101-400
E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG
Hagackerstr. 10
CH-8953 Dietikon
Tel.: +44-7400510
Fax : +44-7400533

· Informing department: msds@mc-bauchemie.de

· 1.4 Emergency telephone number:

Tel.: +49 / (0)700 24112112 (MCR)

Tel.: +48612864565

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour.

Acute Tox. 4 H332 Harmful if inhaled.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

(Contd. on page 2)

GB



BE SURE. BUILD SURE.

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.03.2023




Version number 23 (replaces version 22)

Revision: 24.03.2023

Trade name MC-DUR TopSpeed - Komponente B

(Contd. of page 1)

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008** The product is classified and labelled according to the GB CLP regulation.
- **Hazard pictograms**

GHS02 GHS07 GHS08
- **Signal word** Danger
- **Hazard-determining components of labelling:** Aliphatisches Polyisocyanat
Solvent naphtha
- **Hazard statements** H226 Flammable liquid and vapour.
H332 Harmful if inhaled.
H317 May cause an allergic skin reaction.
H335 May cause respiratory irritation.
H304 May be fatal if swallowed and enters airways.
H412 Harmful to aquatic life with long lasting effects.
- **Precautionary statements** P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P321 Specific treatment (see on this label).
P331 Do NOT induce vomiting.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P362+P364 Take off contaminated clothing and wash it before reuse.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- **Additional information:** To avoid risks to human health and the environment, comply with the instructions for use.
Contains isocyanates. May produce an allergic reaction.
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**
- **Description:** Mixture consisting of the following components.

· **Dangerous components:**

CAS: 28182-81-2	Aliphatisches Polyisocyanat Acute Tox. 4, H332; Skin Sens. 1, H317; STOT SE 3, H335, EUH204	60-80%
-----------------	--	--------

(Contd. on page 3)



BE SURE. BUILD SURE.

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.03.2023

Version number 23 (replaces version 22)

Revision: 24.03.2023

Trade name MC-DUR TopSpeed - Komponente B

(Contd. of page 2)

EC number: 918-668-5 Reg.nr.: 01-2119455851-35	Solvent naphtha Flam. Liq. 3, H226; Asp. Tox. 1, H304; STOT SE 3, H335-H336, EUH066	≥10-<20%
CAS: 108-32-7 EINECS: 203-572-1	propylene carbonate Eye Irrit. 2, H319	<2.5%

· **Additional information** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· **4.1 Description of first aid measures**

- **General information** Instantly remove any clothing soiled by the product.
Take affected persons into the open air.
Seek medical treatment.
- **After inhalation** Supply fresh air.
Call a doctor immediately.
- **After skin contact** Instantly wash with water and soap and rinse thoroughly.
- **After eye contact** Rinse opened eye for several minutes under running water.
Seek medical treatment.
- **After swallowing** Call a doctor immediately.

· **4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

· **4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

SECTION 5: Firefighting measures

· **5.1 Extinguishing media**

· **Suitable extinguishing agents** Use fire fighting measures that suit the environment.

· **5.2 Special hazards arising from the substance or mixture**

Can be released in case of fire
Carbon monoxide (CO)
Nitrogen oxides (NOx)
Under certain fire conditions, traces of other toxic gases cannot be excluded, e.g.:
Hydrogen cyanide (HCN)

· **5.3 Advice for firefighters**

· **Protective equipment:** Wear self-contained breathing apparatus.

GB

(Contd. on page 4)



BE SURE. BUILD SURE.

Page 4/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.03.2023

Version number 23 (replaces version 22)

Revision: 24.03.2023

Trade name **MC-DUR TopSpeed - Komponente B**

(Contd. of page 3)

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
*Ensure adequate ventilation
Use breathing protection against the effects of fumes/dust/aerosol.*
- **6.2 Environmental precautions:**
Prevent material from reaching sewage system, holes and cellars.
- **6.3 Methods and material for containment and cleaning up:**
*Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose of contaminated material as waste according to item 13.
Ensure adequate ventilation.*
- **6.4 Reference to other sections**
*See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.
See Section 13 for information on disposal.*

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
*Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.*
- **Information about protection against explosions and fires:** *No special measures required.*
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and containers:** *Store only in the original container.*
- **Information about storage in one common storage facility:** *Store away from foodstuffs.*
- **Further information about storage conditions:** *Keep container tightly sealed.*
- **Storage class** 3
- **7.3 Specific end use(s)** *No further relevant information available.*

SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**
- **Components with critical values that require monitoring at the workplace:** *The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.*

(Contd. on page 5)

GB



BE SURE. BUILD SURE.

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.03.2023

Version number 23 (replaces version 22)

Revision: 24.03.2023

Trade name MC-DUR TopSpeed - Komponente B

(Contd. of page 4)

· **DNELs**

28182-81-2 Aliphatisches Polyisocyanat

Inhalative	DNEL	0.5 mg/m ³ (Workers) (long term local)
		1 mg/m ³ (kei) (acute local eff)

· **PNECs**

28182-81-2 Aliphatisches Polyisocyanat

PNEC	12.7 µg/l (Daphnia magna) (marine)
PNEC	38.28 mg/l (kei) (STP)

· **Additional information:** The lists that were valid during the compilation were used as basis.

· **8.2 Exposure controls**

· **Appropriate engineering controls**

No further data; see section 7.

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures**

Keep away from foodstuffs, beverages and food.
Instantly remove any soiled and impregnated garments.
Wash hands during breaks and at the end of the work.
Avoid contact with the eyes and skin.
Do not eat, drink or smoke while working.

· **Hand protection**

· **Material of gloves**

Protective gloves.
Nitrile rubber, NBR

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye/face protection**

Safety glasses
Tightly sealed safety glasses.

· **Body protection:**

Protective work clothing.

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Colour:**

Dark brown

· **Smell:**

Characteristic

· **Melting point/freezing point:**

Not determined

· **Boiling point or initial boiling point and boiling range**

36 °C (Solvent naphtha)

· **Flash point:**

47 °C (DIN 51755)

· **Auto-ignition temperature:**

400 °C

· **pH**

Not applicable.
Not determined.

· **Viscosity:**

· **Kinematic viscosity**

Not determined.

· **dynamic:**

Not determined.

(Contd. on page 6)



BE SURE. BUILD SURE.

Page 6/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.03.2023

Version number 23 (replaces version 22)

Revision: 24.03.2023

Trade name MC-DUR TopSpeed - Komponente B

(Contd. of page 5)

- **Solubility**
- **Water:** Hydrolized
- **Steam pressure:** Not determined.
- **Vapour pressure:**
- **Density and/or relative density**
- **Density at 20 °C** 1.11 g/cm³

- **9.2 Other information**
- **Appearance:**
- **Form:** Fluid
- **Important information on protection of health and environment, and on safety.**
- **Self-inflammability:** Product is not selfigniting.
- **Explosive properties:** Product is not explosive.

- **Information with regard to physical hazard classes**
- **Explosives** Void
- **Flammable gases** Void
- **Aerosols** Void
- **Oxidising gases** Void
- **Gases under pressure** Void
- **Flammable liquids** Flammable liquid and vapour.
- **Flammable solids** Void
- **Self-reactive substances and mixtures** Void
- **Pyrophoric liquids** Void
- **Pyrophoric solids** Void
- **Self-heating substances and mixtures** Void
- **Substances and mixtures, which emit flammable gases in contact with water** Void
- **Oxidising liquids** Void
- **Oxidising solids** Void
- **Organic peroxides** Void
- **Corrosive to metals** Void
- **Desensitised explosives** Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** Reacts with amines
- **10.4 Conditions to avoid** No further relevant information available.

(Contd. on page 7)

GB



BE SURE. BUILD SURE.

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 24.03.2023

Version number 23 (replaces version 22)

Revision: 24.03.2023

Trade name MC-DUR TopSpeed - Komponente B

(Contd. of page 6)

- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Harmful if inhaled.

· **LD/LC50 values that are relevant for classification:**

28182-81-2 Aliphatisches Polyisocyanat

Oral LD50 >2500 mg/kg (rat) (OECD 423)

Dermal LD50 >2000 mg/kg (rat) (OECD 402)

108-32-7 propylene carbonate

Oral LD50 >5000 mg/kg (rat)

Dermal LD50 >2000 mg/kg (rbt)

- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** May cause respiratory irritation.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** May be fatal if swallowed and enters airways.
- **11.2 Information on other hazards**

· **Endocrine disrupting properties**

None of the ingredients is listed.

SECTION 12: Ecological information

· **12.1 Toxicity**

· **Aquatic toxicity:**

28182-81-2 Aliphatisches Polyisocyanat

ErC10/72h 370 mg/l (Desmodesmus subspicatus) (EU C.3)

ErC50/72h >1000 mg/l (Desmodesmus subspicatus) (EU C.3)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

(Contd. on page 8)



BE SURE. BUILD SURE.

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.03.2023

Version number 23 (replaces version 22)

Revision: 24.03.2023

Trade name MC-DUR TopSpeed - Komponente B

(Contd. of page 7)

· **12.6 Endocrine disrupting properties**

The product does not contain substances with endocrine disrupting properties.

· **12.7 Other adverse effects**

· **Additional ecological information:**

· **General notes:**

Do not allow product to reach ground water, water bodies or sewage system.
Danger to drinking water if even small quantities leak into soil.

SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**

· **Recommendation**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packagings:**

· **Recommendation:**

Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.

SECTION 14: Transport information

· **14.1 UN number or ID number**

· **ADR, IMDG, IATA**

Void

· **14.2 UN proper shipping name**

· **ADR, IMDG, IATA**

Void

· **14.3 Transport hazard class(es)**

· **ADR, ADN, IMDG, IATA**

· **Class**

Void

· **14.4 Packing group**

· **ADR, IMDG, IATA**

Void

· **14.5 Environmental hazards:**

· **Marine pollutant:**

No

· **14.6 Special precautions for user**

Not applicable.

· **14.7 Maritime transport in bulk according to IMO instruments**

Not applicable.

· **UN "Model Regulation":**

Void

GB

(Contd. on page 9)



BE SURE. BUILD SURE.

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.03.2023

Version number 23 (replaces version 22)

Revision: 24.03.2023

Trade name MC-DUR TopSpeed - Komponente B

(Contd. of page 8)

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- Directive 2012/18/EU
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5.000 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50.000 t
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
 - H226 Flammable liquid and vapour.
 - H304 May be fatal if swallowed and enters airways.
 - H317 May cause an allergic skin reaction.
 - H319 Causes serious eye irritation.
 - H332 Harmful if inhaled.
 - H335 May cause respiratory irritation.
 - H336 May cause drowsiness or dizziness.
 - EUH066 Repeated exposure may cause skin dryness or cracking.
 - EUH204 Contains isocyanates. May produce an allergic reaction.
- **Department issuing data specification sheet:** Environment protection department.
- **Abbreviations and acronyms:**
 - RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
 - ICAO: International Civil Aviation Organisation
 - ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
 - IMDG: International Maritime Code for Dangerous Goods
 - IATA: International Air Transport Association
 - GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 - EINECS: European Inventory of Existing Commercial Chemical Substances
 - ELINCS: European List of Notified Chemical Substances
 - CAS: Chemical Abstracts Service (division of the American Chemical Society)
 - DNEL: Derived No-Effect Level (UK REACH)
 - PNEC: Predicted No-Effect Concentration (UK REACH)
 - LC50: Lethal concentration, 50 percent
 - LD50: Lethal dose, 50 percent
 - PBT: Persistent, Bioaccumulative and Toxic
 - vPvB: very Persistent and very Bioaccumulative
 - Flam. Liq. 3: Flammable liquids – Category 3
 - Acute Tox. 4: Acute toxicity – Category 4
 - Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

(Contd. on page 10)



BE SURE. BUILD SURE.

Page 10/10

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 24.03.2023

Version number 23 (replaces version 22)

Revision: 24.03.2023

Trade name MC-DUR TopSpeed - Komponente B

(Contd. of page 9)

Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

*** Data compared to the
previous version altered.**

GB