

Page 1/14

# Safety data sheet according to UK REACH

Printing date 07.09.2024

Version number 42 (replaces version 41)

Revision: 31.08.2024

## SECTION 1: Identification of the substance/mixture and of the company/ undertaking

Trade name       MC-DUR rapid - Komponente A         · Article number:       950         · 1.2 Relevant identified uses of the substance or mixture and uses advised against · Application of the substance / the mixture       No further relevant information available.
• 1.2 Relevant identified uses of the substance or mixture and uses advised against • Application of the substance
· Application of the substance
/ the mixture Epoxy coating
<ul> <li>1.3 Details of the supplier of the safety data sheet</li> <li>Manufacturer/Supplier: MC-Bauchemie Müller GmbH &amp; Co. KG Am Kruppwald 1-8 D-46238 Bottrop Tel.: +49(0)2041-101-0 Fax.: +49(0)2041-101-400 E-Mail: info@mc-bauchemie.de</li> <li>MC-Bauchemie AG Hagackerstr. 10 CH-8953 Dietikon Tel.: +44-7400510 Fax : +44-7400533</li> </ul>
<ul> <li>Informing department: msds@mc-bauchemie.de</li> <li>1.4 Emergency telephone</li> </ul>
number:         Tel.: +49 / (0)700 24112112 (MCR)           Tel.: +1 872 5888271 (MCR)

### **SECTION 2: Hazards identification**

#### · 2.1 Classification of the substance or mixture · Classification according to Regulation (EC) No 1272/2008 Skin Irrit. 2 H315 Causes skin irritation. Eye Irrit. 2 H319 Causes serious eye irritation. Skin Sens. 1 H317 May cause an allergic skin reaction. Repr. 1B H360F May damage fertility. STOT RE 1 H372 Causes damage to the lung through prolonged or repeated exposure. Route of exposure: Inhalation. Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects. · 2.2 Label elements · Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation. (Contd. on page 2) GB



Page 2/14

# Safety data sheet according to UK REACH

Printing date 07.09.2024

Version number 42 (replaces version 41)

Revision: 31.08.2024

### Trade name MC-DUR rapid - Komponente A

Hazard pictograms	(Contd. of page
	GHS07 GHS08 GHS09
Signal word	Danger
•	5
<i>Hazard-determining components of labelling:</i>	Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene dioxirane and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}meth oxirane and 2,2'-[methylenebis(2,1-phenyleneoxymethylene dioxirane crystalline silica Alkyl Glycidyl Ether epoxide derivates maleic anhydride Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxiral
	(1:2)
	Fatty acids, C14-18 and C16-18 unsaturated, treated with male
	acid
Hazard statements	H315 Causes skin irritation.
	H319 Causes serious eye irritation.
	H317 May cause an allergic skin reaction. H360F May damage fertility.
	H372 Causes damage to the lung through prolonged or repeat
	exposure. Route of exposure: Inhalation.
	H411 Toxic to aquatic life with long lasting effects.
Precautionary statements	P260 Do not breathe dust/fume/gas/mist/vapou spray.
	P273 Avoid release to the environment.
	P280 Wear protective gloves/protective clothing/e protection/face protection/hearing protection.
	P305+P351+P338 IF IN EYES: Rinse cautiously with water t several minutes. Remove contact lenses, present and easy to do. Continue rinsing.
	P308+P313 IF exposed or concerned: Get medical advic attention.
	P405 Store locked up.
Additional information:	EUH205 Contains epoxy constituents. May produce an allerg
2.3 Other hazards	
Results of PBT and vPvB as	sessment
PBT:	Not applicable.
	Not applicable.

(Contd. on page 3)



Safety data sheet according to UK REACH

Printing date 07.09.2024

Version number 42 (replaces version 41)

Revision: 31.08.2024

Trade name MC-DUR rapid - Komponente A

(Contd. of page 2)

Page 3/14

3.2 Mixtures Description:	Mixture consisting of the following components.	
Dangerous componer	nts:	
CAS: 9003-36-5 EC number: 701-263-0	Reaction mass of 2,2'-[methylenebis(4,1- phenyleneoxymethylene)]dioxirane and 2-({2-[4-(oxiran-2- ylmethoxy)benzyl]phenoxy}methyl)oxirane and 2,2'- [methylenebis(2,1-phenyleneoxymethylene)]dioxirane Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Skin Sens. 1, H317	<i>≥</i> 25- <i>≤</i> 30%
CAS: 14808-60-7	crystalline silica STOT RE 1, H372	10-30%
CAS: 1675-54-3 EINECS: 216-823-5	epoxide derivates Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317, EUH205 Specific concentration limits: Skin Irrit. 2; H315: C ≥ 5 % Eye Irrit. 2; H319: C ≥ 5 %	<i>≥</i> 5-<10%
CAS: 933999-84-9	Reaction products of hexane-1,6-diol with 2- (chloromethyl)oxirane (1:2) Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; Aquatic Chronic 3, H412	<i>≥</i> 1-<2.5%
CAS: 100-51-6	Benzyl alcohol Acute Tox. 4, H302; Acute Tox. 4, H332; Eye Irrit. 2, H319	<1.5%
CAS: 68609-97-2	Alkyl Glycidyl Ether Repr. 1B, H360F; Skin Irrit. 2, H315; Skin Sens. 1, H317	<i>≥</i> 0.3-<0.5%
CAS: 85711-46-2	Fatty acids, C14-18 and C16-18 unsaturated, treated with maleic acid Skin Irrit. 2, H315; Skin Sens. 1, H317	<i>≥</i> 0.1-<0.5%
CAS: 222417-26-7	Polyacrylate Eye Dam. 1, H318; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Irrit. 2, H315	<i>≥</i> 0.025-<0.259
CAS: 108-31-6 EINECS: 203-571-6	maleic anhydride Resp. Sens. 1, H334; STOT RE 1, H372; Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Sens. 1A, H317, EUH071 Specific concentration limit: Skin Sens. 1A; H317: C ≥ 0.001 %	<i>≥</i> 0.001-<0.1%

(Contd. on page 4)



Page 4/14

# Safety data sheet according to UK REACH

Printing date 07.09.2024

Version number 42 (replaces version 41)

Revision: 31.08.2024

Trade name MC-DUR rapid - Komponente A

(Contd. of page 3)

### SECTION 4: First aid measures

· 4.1 Description of first aid measures

General information	Remove contaminated clothing immediately. Consult a doctor if symptoms occur. Move affected person to fresh air.
· After inhalation	Supply fresh air; seek medical advice if symptoms occur. If unconscious, place in recovery position and seek medical advice.
· After skin contact	In case of contact with skin, wash carefully with plenty of soap and water. Consult a doctor in case of skin reactions.
· After eye contact	Rinse opened eye for several minutes under running water. Call a doctor immediately
· After swallowing	Rinse mouth with water. Never give anything by mouth to an unconscious person. DO NOT induce vomiting. If symptoms persist, consult a doctor.
4.2 Most important symptom and effects, both acute and	S
delayed	Advice for the doctor: Elementary aid, decontamination,

### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents Use fire fighting measures that suit the environment.

symptomatic treatment.

- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
   5.3 Advice for firefighters
- · Protective equipment:

No special measures required.

#### **SECTION 6: Accidental release measures**

<ul> <li>6.1 Personal precautions, protective equipment and</li> </ul>	
emergency procedures 6.2 Environmental	Not required.
precautions:	Prevent material from reaching sewage system, holes and cellars.
<ul> <li>6.3 Methods and material for containment and cleaning up:</li> </ul>	Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
· 6.4 Reference to other	
sections	See Section 7 for information on safe handling
	See Section 8 for information on personal protection equipment. See Section 13 for information on disposal.

(Contd. on page 5)



Page 5/14

# Safety data sheet according to UK REACH

Printing date 07.09.2024

Version number 42 (replaces version 41)

Revision: 31.08.2024

Trade name MC-DUR rapid - Komponente A

(Contd. of page 4)

handling	Open and handle containers with care.
	Ventilation measures are required in rooms without sufficient exchange (e.g. closed rooms),
	because the occupational exposure limit values (see chapte
	could be exceeded. This must be avoided.
	Wear suitable personal protective equipment (see section 8). A
	contact with eyes, skin and clothing. Change contaminated
	damaged gloves and contaminated clothing immediately and w skin immediately. Mix slowly, partially covering the mix
	container. Pour carefully and slowly when repotting. Observe
	BGBau technical data sheet and practical guide for handling ep resins.
Information about protection	
	Ensure sufficient air exchange and/or extraction in the work areas. Take precautionary measures to avoid electrosta discharges.
-	ge, including any incompatibilities
Storage	
Requirements to be met by storerooms and containers:	No special requirements.
Further information about	no special requirements.
	None.
storage conditions:	NONE.

CAS: 108	-31-6 m	naleic anhydride	
	g-term	value: 3 mg/m³ value: 1 mg/m³	
DNELs			
CAS: 100	-51-6 B	Benzyl alcohol	
Oral	DNEL	4 mg/kg bw/Tag (ArL)	
		20 mg/kg bw/Tag (Ark)	
Dermal	DNEL	8 mg/kg bw/day (ArL)	
		40 mg/kg bw/day (Ark)	
Inhalative	DNEL	22 mg/m <sup>3</sup> (ArL)	
		110 mg/m <sup>3</sup> (Ark)	
		(Cont	d. on page



Page 6/14

# Safety data sheet according to UK REACH

Printing date 07.09.2024

Version number 42 (replaces version 41)

Revision: 31.08.2024

Trade name MC-DUR rapid - Komponente A

C49.4	58609-97-2 Alkyl Glyd	Cidul Ether (Contd. of page
Derma		•
Innalat	ive DNEL 0.49 mg/m	<sup>(ArL)</sup>
PNEC		
CAS: 1	100-51-6 Benzyl alco	hol
PNEC	0.527 mg/l (Marine w	ater sediment)
	0.1 mg/l (Mew)	
	1 mg/l (Fresh water s	sediment)
PNEC	0.456 mg/kg dwt (Bo	d)
	5.27 mg/kg dwt (Fres	,
CAS: 6	58609-97-2 Alkyl Glyd	
	0.00072 mg/l (Mew)	··· <b>/</b> · · ·
	0.0072 mg/l (Freshwa	ater)
PNEC	80.12 mg/kg dwt (Bo	
	6.677 mg/kg dwt (Se	
A	66.77 mg/kg dwt (Fre onal information:	The lists that were valid during the compilation were used as bas
	al protective and nic measures	Keep away from food, drink and animal feed.
Genera	al protective and	sures, such as personal protective equipment
nygien	nc measures	Reep away from food, drink and animal feed. Remove soiled, soaked clothing immediately.
		Wash hands before breaks and at the end of work.
		Avoid contact with eyes and skin.
Breath	ing equipment:	If workplace limit values cannot be complied with by ventilation measures or if rooms cannot be technically ventilated, respirate protection must be worn: Use combination filter A1-P2 (brow white) in rooms that cannot be ventilated. If oxygen deficiency expected, use self-contained breathing apparatus. Obser wearing time limits according to §9 (3) GefStoffV in conjunction with BGR 190.
Hand J	protection	Selection of the glove material on consideration of the penetrati times, rates of diffusion and the degradation
· Material of gloves		You can find help with choosing gloves on the website https www.bgbau.de/fileadmin/Gisbau/Projekte.pdf For example, we recommend the Sol-vex 37-900 protective glov from Ansell GmbH. The breakthrough time of the protective glov
		can be found under point 8 "Penetration time of the glove materia The selection of a suitable glove depends not only on the materi but also on other quality features and varies from manufacturer manufacturer. As the product is a preparation of several substances, the resistance of glo
		materials cannot be calculated in advance and must therefore be (Contd. on page



Page 7/14

GB

# Safety data sheet according to UK REACH

Printing date 07.09.2024

Version number 42 (replaces version 41)

Revision: 31.08.2024

### Trade name MC-DUR rapid - Komponente A

	(Contd. of page 6)
	checked before use.
	Nitrile rubber
	Recommended material thickness:> 0.4 mm
<ul> <li>Penetration time of glove</li> </ul>	
material	The breakthrough times of the Sol-vex 37-900 protective gloves
material	are around 8 hours.
	The following applies to all other gloves:
	The exact breakthrough time must be obtained from the protective
	glove manufacturer and adhered to.
	Nitrile rubber
	Material thickness: ≥ 0.40 mm
	Penetration time: $\geq$ 480 min
	Butyl rubber:
	Material thickness: $\geq$ 0.5 mm
	Penetration time: > 480 min
· Eye/face protection	Tight-fitting safety goggles.
	Safety goggles.
· Body protection:	Protective clothing
Body protection.	
	Suitable protective clothing should be worn when working with
	epoxy resins. In addition to normal work clothing (long trousers,
	long-sleeved shirt or T-shirt), disposable overalls, aprons,
	overshoes, sleeve protectors etc. may be necessary depending on
	the activity. Uncovered areas of skin should be avoided as far as
	possible, even in hot weather. If the work involves kneeling, the
	lower leg area should be protected by protective trousers.

SECTION 9: Physical and chemical properties

General Information	Assorting to product aposition
Colour:	According to product specification
Smell:	Characteristic
Melting point/freezing point:	Not determined
Boiling point or initial boiling point and	
boiling range	>200 °C (CAS: 9003-36-5 2,2'-[methylenebis(p phenyleneoxymethylene)]bisoxirane polymer and homologues, molecular weight < 700)
Flash point:	151 °C
Auto-ignition temperature:	460 °C
pH .	Not determined.
, Viscosity:	
Kinematic viscosity	Not determined.
dynamic:	Not determined.
Solubility	
Water:	Not miscible or difficult to mix
Steam pressure at 1732 °C:	13.5 hPa (CAS: 14808-60-7 Quartz (SiO2))



Page 8/14

# Safety data sheet according to UK REACH

Printing date 07.09.2024

Version number 42 (replaces version 41)

Revision: 31.08.2024

### Trade name MC-DUR rapid - Komponente A

	(Contd. of pa	g
Density and/or relative density		
Density at 20 °C	2.23 g/cm³	
9.2 Other information		
Appearance:		
Form:	Fluid	
Important information on protection of hea	alth	
and environment, and on safety.		
Self-inflammability:	Product is not selfigniting.	
Explosive properties:	Product is not explosive.	
Information with regard to physical haz	ard	
classes		
Explosives	Void	
Flammable gases	Void	
Aerosols	Void	
Oxidising gases	Void	
Gases under pressure	Void	
Flammable liquids	Void	
Flammable solids	Void	
Self-reactive substances and mixtures	Void	
Pyrophoric liquids	Void	
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit		
flammable gases in contact with water	Void	
Oxidising liquids	Void	
Oxidising solids	Void	
Organic peroxides	Void	
Corrosive to metals	Void	
Desensitised explosives	Void	

## SECTION 10: Stability and reactivity

<ul> <li>10.1 Reactivity</li> <li>10.2 Chemical stability</li> <li>Thermal decomposition /</li> </ul>	No further relevant information available.
conditions to be avoided: 10.3 Possibility of hazardous	No decomposition if used according to specifications.
reactions	No dangerous reactions known
<ul> <li>10.4 Conditions to avoid</li> </ul>	No further relevant information available.
<ul> <li>10.5 Incompatible materials:</li> <li>10.6 Hazardous</li> </ul>	No further relevant information available.
decomposition products:	No dangerous decomposition products known

(Contd. on page 9)

GB



Safety data sheet according to UK REACH

Printing date 07.09.2024

Version number 42 (replaces version 41)

Revision: 31.08.2024

Trade name MC-DUR rapid - Komponente A

(Contd. of page 8)

Page 9/14

11.1 Infor	mation on hazard clas	sses as defined in Regulation (EC) No 1272/2008	
Acute tox	cicity l	Based on available data, the classification criteria are not r	net.
LD/LC50	values that are releva	nt for classification:	
CAS: 900	and 2-({2-[4-(o)	of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]di xiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane al 2,1-phenyleneoxymethylene)]dioxirane	
Oral	LD50	>2000 mg/kg (rat)	
Dermal	LD50	>2000 mg/kg (rabbit)	
CAS: 167	5-54-3 epoxide derivat	tes	
Dermal	LD50	23000 mg/kg (rabbit)	
CAS: 100	-51-6 Benzyl alcohol		
Oral	LD50	1230 mg/kg (rat)	
	NOAEL 2nd year study	y 200 mg/kg (mouse)	
		200 mg/kg (rat)	
Dermal	LD50	2000 mg/kg (rabbit)	
Inhalative	LC50/4 h	>4178 mg/l (rat)	
CAS: 686	09-97-2 Alkyl Glycidyl	Ether	
Oral	LD50	17100 mg/kg (rat)	
CAS: 108	-31-6 maleic anhydrid	e	
Oral	LD50	1090 mg/kg (rat)	
Dermal	LD50	2620 mg/kg (rat)	
Skin corr	osion/irritation	Causes skin irritation.	
		Causes serious eye irritation.	
	ory or skin	May aquad an allerric akin reaction	
		lay cause an allergic skin reaction. ased on available data, the classification criteria are not met.	
		ased on available data, the classification criteria are not met.	
Reproductive toxicity M		May damage fertility.	
		ased on available data, the classification criteria are not met.	
	eated exposure (	Causes damage to the lung through prolonged or r	epeate
STOT-rep	eated exposure	Causes damage to the lung through prolonged or r exposure. Route of exposure: Inhalation.	
STOT-rep	eated exposure	Causes damage to the lung through prolonged or r exposure. Route of exposure: Inhalation. Based on available data, the classification criteria are not r	
STOT-rep Aspiration 11.2 Infor	n hazard exposure	Causes damage to the lung through prolonged or r exposure. Route of exposure: Inhalation. Based on available data, the classification criteria are not r <b>rds</b>	
STOT-rep Aspiration 11.2 Infor Endocrine	n hazard	Causes damage to the lung through prolonged or r exposure. Route of exposure: Inhalation. Based on available data, the classification criteria are not r <b>rds</b> s	
STOT-rep Aspiration 11.2 Infor Endocrin CAS: 128	eated exposure ( n hazard mation on other hazar e disrupting propertie	Causes damage to the lung through prolonged or r exposure. Route of exposure: Inhalation. Based on available data, the classification criteria are not r rds p-cresol	net.

(Contd. on page 10)

GB



Page 10/14

# Safety data sheet according to UK REACH

Printing date 07.09.2024

Version number 42 (replaces version 41)

Revision: 31.08.2024

Trade name MC-DUR rapid - Komponente A

(Contd. of page 9)

12.1 Toxici	ty			
Aquatic to	-			
CAS: 9003-	and 2-({2-[	nass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane 4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane and 2,2' bis(2,1-phenyleneoxymethylene)]dioxirane		
LC50/96h	>100 mg/l (Dapl	nnia magna)		
EC50/96h	>100 mg/l (Leuc	idus idus)		
CAS: 1675-	54-3 epoxide de	rivates		
IC50	>42.6 mg/l (Bak			
LC50/96h	2 mg/l (Oncorhy	nchus mykiss)		
EC50/48h	1.8 mg/l (Daphnia magna)			
ErC50/72h	11 mg/l (Selenastrum capricornutum)			
CAS: 100-5	1-6 Benzyl alcol	hol		
IC50/72h	700 mg/l (algae)			
LC50/96h	460 mg/l (Pimephales promelas)			
	10 mg/l (Lepomi	's macrochirus)		
CAS: 68609	97-2 Alkyl Glyd	cidyl Ether		
EbC50/72h	843 mg/l (Pseud	lokirchneriella subcapitata)		
LC50/96h	>5000 mg/l (Ond	corhynchus mykiss)		
	1800 mg/l (Lepo	mis macrochirus)		
EC50	>100 mg/l (BEL)			
NOEC	500 mg/l (Pseud	lokirchneriella subcapitata)		
12.2 Persis				
degradabil		No further relevant information available.		
12.3 Bioaco potential	cumulative	No further relevant information available.		
12.4 Mobility in soil		No further relevant information available.		
12.5 Result	s of PBT and vF	PvB assessment		
PBT:		Not applicable.		
vPvB:	rina diamentina -	Not applicable.		
12.6 Endoc properties	rine disrupting	For information on endocrine disrupting properties see section 11.		
	adverse effects			
Additional	ecological infor			
General no	tes:	Do not allow product to reach ground water, water bodies of sewage system.		
		Danger to drinking water if even small quantities leak into soil.		

(Contd. on page 11)



Page 11/14

## Safety data sheet according to UK REACH

Printing date 07.09.2024

Version number 42 (replaces version 41)

Revision: 31.08.2024

Trade name MC-DUR rapid - Komponente A

(Contd. of page 10)

### **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation:

Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.

14.1 UN number or ID number	
ADR, IMDG, IATA	UN3082
14.2 UN proper shipping name	
ADR, IATA	ENVIRONMENTALLY HAZARDOUS
	SUBSTANCE, LIQUID, N.O.S. (epoxide derivates)
IMDG	ENVIRONMENTALLY HAZARDOU
	SUBSTANCE, LIQUID, N.O.S. (epoxide derivates MARINE POLLUTANT
14.3 Transport hazard class(es)	
ADR	
Class	9 (M6) Miscellaneous dangerous substances an
	articles.
Label	9
IMDG, IATA	
Class	9 Miscellaneous dangerous substances an
	articles.
Label	9
14.4 Packing group	
ADR, IMDG, IATA	III
14.5 Environmental hazards:	
Marine pollutant:	Yes
	Symbol (fish and tree)
Special marking (ADR):	Symbol (fish and tree)
Special marking (IATA):	Symbol (fish and tree)
14.6 Special precautions for user	Warning: Miscellaneous dangerous substances an
	articles.
Kemler Number:	90
EMS Number:	F-A,S-F
Stowage Category	A
14.7 Maritime transport in bulk accordi	
IMO instruments	Not applicable.

GB



Page 12/14

# Safety data sheet according to UK REACH

Printing date 07.09.2024

Version number 42 (replaces version 41)

Revision: 31.08.2024

#### Trade name MC-DUR rapid - Komponente A

	(Contd. of page 1
<ul> <li>Transport/Additional information:</li> </ul>	
· ADR	
· Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· Transport category	3
Tunnel restriction code	(-)
·IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 100 ml
· UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXIDI DERIVATES), 9, III

### **SECTION 15: Regulatory information**

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Poisons Act

Regulated explosives precurs	ors	
None of the ingredients is listed.		
· Regulated poisons		
None of the ingredients is listed.		
· Reportable explosives precurs	sors	
None of the ingredients is listed.		
· Reportable poisons		
None of the ingredients is listed.		
<ul> <li>Directive 2012/18/EU</li> <li>Qualifying quantity (tonnes) for the application of lower- tier requirements</li> <li>Qualifying quantity (tonnes) for the application of upper-</li> </ul>	200 t	
tier requirements	500 t	(Contd. on page 13) GB



Page 13/14

### Safety data sheet according to UK REACH

Printing date 07.09.2024

Version number 42 (replaces version 41)

Revision: 31.08.2024

(Contd. of page 12)

#### Trade name MC-DUR rapid - Komponente A

 15.2 Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

### **SECTION 16: Other information**

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H314 Causes severe skin burns and eye damage. H315 Causes skin irritation.

Harmful if swallowed.

- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.

H302

- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H360F May damage fertility.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- Toxic to aquatic life with long lasting effects. H411
- Harmful to aquatic life with long lasting effects. H412
- EUH071 Corrosive to the respiratory tract.
- EUH205 Contains epoxy constituents. May produce an allergic reaction.

 Department issuing data specification sheet:

Environment protection department. RID: Règlement international concernant le transport des marchandises

· Abbreviations and acronyms: dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) DNEL: Derived No-Effect Level (UK REACH) PNEC: Predicted No-Effect Concentration (UK REACH) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Acute Tox. 4: Acute toxicity - Category 4 Skin Corr. 1B: Skin corrosion/irritation - Category 1B Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 (Contd. on page 14)



Safety data sheet according to UK REACH

Printing date 07.09.2024

Version number 42 (replaces version 41)

Revision: 31.08.2024

Page 14/14

### Trade name MC-DUR rapid - Komponente A

	(Contd. of page 1
	Resp. Sens. 1: Respiratory sensitisation – Category 1
	Skin Sens. 1: Skin sensitisation – Category 1
	Skin Sens. 1A: Skin sensitisation – Category 1A
	Repr. 1B: Reproductive toxicity – Category 1B
	STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1
	Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard
	Category 1
	Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aqua hazard – Category 1
	Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aqua hazard – Category 2
	Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aqua hazard – Category 3
• * Data compared to the	
previous version altered.	

GB