



BE SURE. BUILD SURE.

Page 1/13

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.02.2023

Version number 18 (replaces version 17)

Revision: 25.02.2023

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name **MC-DUR rapid - Komponente B**

Article number: 970

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

#### Application of the substance / the mixture

Epoxy coating  
Hardening agent/ Curing agent

#### 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: MC-Bauchemie Müller GmbH & Co. KG  
Am Kruppwald 1-8  
D-46238 Bottrop  
Tel.: +49(0)2041-101-0  
Fax.: +49(0)2041-101-400  
E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG  
Hagackerstr. 10  
CH-8953 Dietikon  
Tel.: +44-7400510  
Fax : +44-7400533

Informing department: msds@mc-bauchemie.de

#### 1.4 Emergency telephone number:

Tel.: +49 / (0)700 24112112 (MCR)  
Tel.: +48612864565

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification according to Regulation (EC) No 1272/2008

Acute Tox. 4 H302 Harmful if swallowed.

Skin Corr. 1A H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

#### 2.2 Label elements

##### Labelling according to

Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation.

##### Hazard pictograms



GHS05 GHS07

(Contd. on page 2)

GB



BE SURE. BUILD SURE.

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 25.02.2023

Version number 18 (replaces version 17)

Revision: 25.02.2023

**Trade name MC-DUR rapid - Komponente B**

(Contd. of page 1)

- **Signal word** Danger
- **Hazard-determining components of labelling:** *Benzyl alcohol  
1,3-Cyclohexanedimethanamine  
polymer amine terminated  
Formaldehyde, oligomeric reaction products with 3,3'-iminodi(propylamine)  
2,4,6-Tris-(1-Phenyl-Ethyl) carbolic acid  
m-phenylenebis(methylamine)  
3-aminomethyl-3,5,5-trimethylcyclohexylamine*
- **Hazard statements** *H302 Harmful if swallowed.  
H314 Causes severe skin burns and eye damage.  
H317 May cause an allergic skin reaction.  
H412 Harmful to aquatic life with long lasting effects.*
- **Precautionary statements** *P260 Do not breathe dusts or mists.  
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P310 Immediately call a POISON CENTER/doctor.  
P321 Specific treatment (see on this label).  
P362+P364 Take off contaminated clothing and wash it before reuse.*
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** *Not applicable.*
- **vPvB:** *Not applicable.*

**SECTION 3: Composition/information on ingredients**

- **3.2 Mixtures**
- **Description:** *Mixture consisting of the following components.*

· **Dangerous components:**

CAS: 100-51-6 EINECS: 202-859-9 Reg.nr.: 01-2119492630-38	<i>Benzyl alcohol Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332</i>	10-30%
	<i>polymer amine terminated Eye Dam. 1, H318; Skin Irrit. 2, H315; Skin Sens. 1B, H317</i>	10-30%
CAS: 2579-20-6 EINECS: 219-941-5 Reg.nr.: 01-2119543741-41-XXXX	<i>1,3-Cyclohexanedimethanamine Skin Corr. 1B, H314; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317</i>	10-30%

(Contd. on page 3)



BE SURE. BUILD SURE.

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 25.02.2023

Version number 18 (replaces version 17)

Revision: 25.02.2023

**Trade name MC-DUR rapid - Komponente B**

(Contd. of page 2)

CAS: 61788-44-1 EINECS: 262-975-0	2,4,6-Tris-(1-Phenyl-Ethyl) carbolic acid Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Skin Sens. 1, H317	≥10-<25%
CAS: 161278-35-9	Formaldehyde, oligomeric reaction products with 3,3'-iminodi(propylamine) Skin Corr. 1A, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Sens. 1, H317	10-30%
CAS: 1477-55-0 EINECS: 216-032-5 Reg.nr.: 01-2119480150-50	m-phenylenebis(methylamine) Skin Corr. 1B, H314; Acute Tox. 4, H302; Skin Sens. 1, H317; Aquatic Chronic 3, H412	≥1-<2.5%
CAS: 90-72-2 EINECS: 202-013-9 Reg.nr.: 2119560597-27	2,4,6-tris(dimethylaminomethyl)phenol Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319	<2.5%
CAS: 64-17-5 EINECS: 200-578-6	ethyl alcohol Flam. Liq. 2, H225	<2.5%
CAS: 2855-13-2 EINECS: 220-666-8 Reg.nr.: 01-2119514687-32	3-aminomethyl-3,5,5-trimethylcyclohexylamine Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1A, H317 ATE: LD50 oral: 1030 mg/kg Specific concentration limit: Skin Sens. 1A; H317: C≥ 0.001 %	≥0.1-<0.5%

· **Additional information**

For the wording of the listed hazard phrases refer to section 16.

**SECTION 4: First aid measures**

· **4.1 Description of first aid measures**

· **General information**

Instantly remove any clothing soiled by the product.  
Take affected persons into the open air.

· **After inhalation**

Supply fresh air and call for doctor for safety reasons.

· **After skin contact**

Instantly wash with water and soap and rinse thoroughly.

· **After eye contact**

Rinse opened eye for several minutes under running water.  
Call a doctor immediately.

· **After swallowing**

Drink copious amounts of water and provide fresh air. Instantly call for doctor.

· **4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

· **4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

GB

(Contd. on page 4)



BE SURE. BUILD SURE.

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.02.2023

Version number 18 (replaces version 17)

Revision: 25.02.2023

Trade name MC-DUR rapid - Komponente B

(Contd. of page 3)

### SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents** Use fire fighting measures that suit the environment.
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** Put on breathing apparatus.

### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Prevent material from reaching sewage system, holes and cellars.
- **6.3 Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose of contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling  
See Section 8 for information on personal protection equipment.  
See Section 13 for information on disposal.

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Store in cool, dry place in tightly closed containers.  
Open and handle container with care.
- **Information about protection against explosions and fires:** No special measures required.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and containers:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Storage class** 8A
- **7.3 Specific end use(s)** No further relevant information available.

GB

(Contd. on page 5)



BE SURE. BUILD SURE.

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 25.02.2023

Version number 18 (replaces version 17)

Revision: 25.02.2023

**Trade name MC-DUR rapid - Komponente B**

(Contd. of page 4)

**SECTION 8: Exposure controls/personal protection**

· **8.1 Control parameters**

· **Components with critical values that require monitoring at the workplace:**

**64-17-5 ethyl alcohol**

WEL Long-term value: 1920 mg/m<sup>3</sup>, 1000 ppm

· **DNELs**

**100-51-6 Benzyl alcohol**

Oral	DNEL	4 mg/kg bw/Tag (ArL) 20 mg/kg bw/Tag (Ark)
Dermal	DNEL	8 mg/kg bw/day (ArL) 40 mg/kg bw/day (Ark)
Inhalative	DNEL	22 mg/m <sup>3</sup> (ArL) 110 mg/m <sup>3</sup> (Ark)

**2579-20-6 1,3-Cyclohexanedimethanamine**

Inhalative DNEL 0.00947 mg/m<sup>3</sup> (Workers)

**1477-55-0 m-phenylenebis(methylamine)**

Dermal	DNEL	0.33 mg/kg bw/day (Workers)
Inhalative	DNEL	1.2 mg/m <sup>3</sup> (Workers)

**90-72-2 2,4,6-tris(dimethylaminomethyl)phenol**

Inhalative DNEL 0.31 mg/m<sup>3</sup> (ArL)

**2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine**

Oral	DNEL	0.526 mg/kg bw/Tag (ArL)
Inhalative	DNEL	20.1 mg/m <sup>3</sup> (ArL)

· **PNECs**

**100-51-6 Benzyl alcohol**

PNEC	0.527 mg/l (Marine water sediment) 0.1 mg/l (Mew) 1 mg/l (Fresh water sediment)
PNEC	0.456 mg/kg dwt (Bod) 5.27 mg/kg dwt (Fresh water sediment)

**2579-20-6 1,3-Cyclohexanedimethanamine**

PNEC	0.003 mg/l (Mew)
PNEC	0.033 mg/l (Fresh water)

**1477-55-0 m-phenylenebis(methylamine)**

PNEC	10 mg/l (Kla) 0.009 mg/l (Mew) 0.094 mg/l (Suw)
PNEC	0.045 mg/kg dwt (Bod)

(Contd. on page 6)



BE SURE. BUILD SURE.

### Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.02.2023

Version number 18 (replaces version 17)

Revision: 25.02.2023

**Trade name MC-DUR rapid - Komponente B**

(Contd. of page 5)

	0.43 mg/kg dwt (Marine water sediment)
	0.43 mg/kg dwt (Fresh water sediment)
<b>90-72-2 2,4,6-tris(dimethylaminomethyl)phenol</b>	
PNEC	0.2 mg/l (Sewage Treatment Plant)
	0.0084 mg/l (Mew)
	0.084 mg/l (Suw)
<b>2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine</b>	
PNEC	0.006 mg/l (Mew)
	0.06 mg/l (Suw)
PNEC	0.578 mg/kg dwt (Sediment)
	5.784 mg/kg dwt (Fresh water sediment)

- **Additional information:** The lists that were valid during the compilation were used as basis.
- **8.2 Exposure controls**
- **Appropriate engineering controls** No further data; see item 7.
- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures**
  - Keep away from foodstuffs, beverages and food.
  - Instantly remove any soiled and impregnated garments.
  - Wash hands during breaks and at the end of the work.
  - Avoid contact with the eyes and skin.
- **Hand protection**
  - Protective gloves.
  - Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
  - After use of gloves apply skin-cleaning agents and skin cosmetics.
- **Material of gloves**
  - The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
  - The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye/face protection**
  - Safety glasses
  - Tightly sealed safety glasses.
- **Body protection:**
  - Protective work clothing.

## SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**
- **General Information**
- **Colour:** Yellow
- **Smell:** Amine-like

(Contd. on page 7)



BE SURE. BUILD SURE.

Page 7/13

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.02.2023

Version number 18 (replaces version 17)

Revision: 25.02.2023

Trade name MC-DUR rapid - Komponente B

(Contd. of page 6)

· <b>Melting point/freezing point:</b>	Not determined
· <b>Boiling point or initial boiling point and boiling range</b>	205.4 °C (100-51-6 Benzyl alcohol)
· <b>Lower and upper explosion limit</b>	
· <b>Lower:</b>	1.3 Vol % (100-51-6 Benzyl alcohol)
· <b>Upper:</b>	13 Vol % (100-51-6 Benzyl alcohol)
· <b>Flash point:</b>	98 °C
· <b>pH</b>	Not determined.
· <b>Viscosity:</b>	
· <b>Kinematic viscosity</b>	Not determined.
· <b>dynamic:</b>	Not determined.
· <b>Solubility</b>	
· <b>Water:</b>	Not miscible or difficult to mix
· <b>Steam pressure at 20 °C:</b>	0.1 hPa
· <b>Density and/or relative density</b>	
· <b>Density at 20 °C</b>	1.08 g/cm <sup>3</sup>

### · 9.2 Other information

· <b>Appearance:</b>	
· <b>Form:</b>	Fluid
· <b>Important information on protection of health and environment, and on safety.</b>	
· <b>Self-inflammability:</b>	Product is not selfigniting.
· <b>Explosive properties:</b>	Product is not explosive.

### · Information with regard to physical hazard classes

· <b>Explosives</b>	Void
· <b>Flammable gases</b>	Void
· <b>Aerosols</b>	Void
· <b>Oxidising gases</b>	Void
· <b>Gases under pressure</b>	Void
· <b>Flammable liquids</b>	Void
· <b>Flammable solids</b>	Void
· <b>Self-reactive substances and mixtures</b>	Void
· <b>Pyrophoric liquids</b>	Void
· <b>Pyrophoric solids</b>	Void
· <b>Self-heating substances and mixtures</b>	Void
· <b>Substances and mixtures, which emit flammable gases in contact with water</b>	Void
· <b>Oxidising liquids</b>	Void
· <b>Oxidising solids</b>	Void
· <b>Organic peroxides</b>	Void
· <b>Corrosive to metals</b>	Void

(Contd. on page 8)

GB



BE SURE. BUILD SURE.

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 25.02.2023

Version number 18 (replaces version 17)

Revision: 25.02.2023

**Trade name MC-DUR rapid - Komponente B**

(Contd. of page 7)

· **Desensitised explosives**      Void

**SECTION 10: Stability and reactivity**

- **10.1 Reactivity**      No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**      No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions**      No dangerous reactions known
- **10.4 Conditions to avoid**      No further relevant information available.
- **10.5 Incompatible materials:**      No further relevant information available.
- **10.6 Hazardous decomposition products:**      No dangerous decomposition products known

**SECTION 11: Toxicological information**

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity**      Harmful if swallowed.

· **LD/LC50 values that are relevant for classification:**

**100-51-6 Benzyl alcohol**

Oral	LD50	1230 mg/kg (rat)
	NOAEL 2nd year study	200 mg/kg (mouse)
Dermal	LD50	200 mg/kg (rat)
	LC50/4 h	2000 mg/kg (rabbit)
Inhalative	LC50/4 h	>4178 mg/l (rat)

**2579-20-6 1,3-Cyclohexanedimethanamine**

Oral	LD50	700 mg/kg (rat)
Dermal	LD50	1700 mg/kg (rat)

**1477-55-0 m-phenylenebis(methylamine)**

Oral	LD50	1180 mg/kg (mouse)
		930 mg/kg (rat)
Dermal	LD50	>3100 mg/kg (rabbit)

**90-72-2 2,4,6-tris(dimethylaminomethyl)phenol**

Oral	LD50	2169 mg/kg (rat)
	NOAEL	15 mg/kg (rat)

**64-17-5 ethyl alcohol**

Oral	LD50	7060 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rabbit)
Inhalative	LC50/4 h	>20 mg/l (rat)

(Contd. on page 9)





BE SURE. BUILD SURE.

Page 9/13

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.02.2023

Version number 18 (replaces version 17)

Revision: 25.02.2023

Trade name **MC-DUR rapid - Komponente B**

(Contd. of page 8)

**2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine**

Oral	LD50	1030 mg/kg (ATE) 1030 mg/kg (rat)
	NOAEL	250 mg/kg (rat)
Dermal	LD50	1840 mg/kg (rabbit) >2000 mg/kg (rat)

- **Skin corrosion/irritation** Causes severe skin burns and eye damage.
- **Serious eye damage/irritation** Causes serious eye damage.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **11.2 Information on other hazards**

· **Endocrine disrupting properties**

61788-44-1	2,4,6-Tris-(1-Phenyl-Ethyl) carboic acid	List II
78-93-3	butanone	List II

**SECTION 12: Ecological information**· **12.1 Toxicity**· **Aquatic toxicity:****100-51-6 Benzyl alcohol**

IC50/72h	700 mg/l (algae)
LC50/96h	460 mg/l ( <i>Pimephales promelas</i> ) 10 mg/l ( <i>Lepomis macrochirus</i> )

**2579-20-6 1,3-Cyclohexanedimethanamine**

EC50/24h	90 mg/l ( <i>Pseudokirchneriella subcapitata</i> )
EC50	90 mg/l ( <i>Pseudomonas putida</i> )
LC50/48h	130 mg/l ( <i>Leucidus idus</i> )

**1477-55-0 m-phenylenebis(methylamine)**

IC50/72h	12 mg/l (algae)
EC50/72h	12 mg/l ( <i>Scenedesmus subspicatus</i> )
LC50/96h	>100 mg/l ( <i>Oncorhynchus mykiss</i> ) 87.6 mg/l ( <i>Ory</i> )
EC50/48h	15.2 mg/l ( <i>Daphnia magna</i> )

**90-72-2 2,4,6-tris(dimethylaminomethyl)phenol**

EC50/72h	84 mg/l ( <i>Desmodesmus subspicatus</i> )
----------	--

(Contd. on page 10)

GB



BE SURE. BUILD SURE.

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 25.02.2023

Version number 18 (replaces version 17)

Revision: 25.02.2023

**Trade name MC-DUR rapid - Komponente B**

(Contd. of page 9)

LC50/96h	175 mg/l (Cyp)
NOEC	2 mg/l (BEL) 6.25 mg/l (Desmodemus subspicatus)
<b>64-17-5 ethyl alcohol</b>	
EC50/24h	858 mg/l (Artemia salina)
LC50/24h	11200 mg/l (Salmo gairdneri)
LC50/96h	15300 mg/l (Pimephales promelas)
EC50/4h	5800 mg/l (Paramecium caudatum)
LC50/48h	5012 mg/l (Ceriodaphnia dubia)
EC50/48h	>10000 mg/l (Daphnia magna)
EC50/3d	275 mg/l (Chlorella vulgaris)
EC10/3d	11.5 mg/l (Chlorella vulgaris)
<b>2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine</b>	
LC50/96h	110 mg/l (Leucidus idus)
EC50	1120 mg/l (Pseudomonas putida)
EC50/48h	23 mg/l (Daphnia magna)
NOEC	1.5 mg/l (Desmodemus subspicatus) 3 mg/l (Daphnia magna)
ErC50/72h	>50 mg/l (Desmodemus subspicatus)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties** For information on endocrine disrupting properties see section 11.
- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:** Do not allow product to reach ground water, water bodies or sewage system.  
Danger to drinking water if even small quantities leak into soil.

**SECTION 13: Disposal considerations**

- **13.1 Waste treatment methods**
- **Recommendation** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 11)



BE SURE. BUILD SURE.

### Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.02.2023

Version number 18 (replaces version 17)

Revision: 25.02.2023

Trade name MC-DUR rapid - Komponente B

(Contd. of page 10)

- **Uncleaned packagings:**
- **Recommendation:** Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.

#### SECTION 14: Transport information

· 14.1 UN number or ID number · ADR, IMDG, IATA	UN2735
· 14.2 UN proper shipping name · ADR, IMDG, IATA	AMINES, LIQUID, CORROSIVE, N.O.S. (1,3-Cyclohexanedimethanamine, Formaldehyde, oligomeric reaction products with 3,3'-iminodi(propylamine))
· 14.3 Transport hazard class(es) · ADR · Class · Label	8 (C7) Corrosive substances. 8
· IMDG, IATA · Class · Label	8 Corrosive substances. 8
· 14.4 Packing group · ADR, IMDG, IATA	II
· 14.5 Environmental hazards: · Marine pollutant:	No
· 14.6 Special precautions for user · Kemler Number: · EMS Number: · Segregation groups · Stowage Category · Segregation Code	Warning: Corrosive substances. 80 F-A, S-B (SGG18) Alkalis A SG35 Stow "separated from" SGG1-acids
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
· Transport/Additional information: · ADR · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· Transport category · Tunnel restriction code	2 E

(Contd. on page 12)



BE SURE. BUILD SURE.

Page 12/13

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.02.2023

Version number 18 (replaces version 17)

Revision: 25.02.2023

Trade name **MC-DUR rapid - Komponente B**

(Contd. of page 11)

· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	1L
· <b>Excepted quantities (EQ)</b>	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· <b>UN "Model Regulation":</b>	UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S. (1,3-CYCLOHEXANEDIMETHANAMINE, FORMALDEHYDE, OLIGOMERIC REACTION PRODUCTS WITH 3,3'- IMINODI(PROPYLAMINE)), 8, II

### SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**  
No further relevant information available.
- **15.2 Chemical safety assessment:**  
A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**  
H225 Highly flammable liquid and vapour.  
H302 Harmful if swallowed.  
H312 Harmful in contact with skin.  
H314 Causes severe skin burns and eye damage.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H318 Causes serious eye damage.  
H319 Causes serious eye irritation.  
H332 Harmful if inhaled.  
H411 Toxic to aquatic life with long lasting effects.  
H412 Harmful to aquatic life with long lasting effects.
- **Department issuing data specification sheet:** Environment protection department.
- **Abbreviations and acronyms:** RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)  
ICAO: International Civil Aviation Organisation  
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
GHS: Globally Harmonised System of Classification and Labelling of Chemicals

(Contd. on page 13)



BE SURE. BUILD SURE.

Page 13/13

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.02.2023

Version number 18 (replaces version 17)

Revision: 25.02.2023

**Trade name MC-DUR rapid - Komponente B**

(Contd. of page 12)

*EINECS: European Inventory of Existing Commercial Chemical Substances*

*ELINCS: European List of Notified Chemical Substances*

*CAS: Chemical Abstracts Service (division of the American Chemical Society)*

*DNEL: Derived No-Effect Level (UK REACH)*

*PNEC: Predicted No-Effect Concentration (UK REACH)*

*LC50: Lethal concentration, 50 percent*

*LD50: Lethal dose, 50 percent*

*PBT: Persistent, Bioaccumulative and Toxic*

*vPvB: very Persistent and very Bioaccumulative*

*Flam. Liq. 2: Flammable liquids – Category 2*

*Acute Tox. 4: Acute toxicity – Category 4*

*Skin Corr. 1A: Skin corrosion/irritation – Category 1A*

*Skin Corr. 1B: Skin corrosion/irritation – Category 1B*

*Skin Irrit. 2: Skin corrosion/irritation – Category 2*

*Eye Dam. 1: Serious eye damage/eye irritation – Category 1*

*Eye Irrit. 2: Serious eye damage/eye irritation – Category 2*

*Skin Sens. 1: Skin sensitisation – Category 1*

*Skin Sens. 1A: Skin sensitisation – Category 1A*

*Skin Sens. 1B: Skin sensitisation – Category 1B*

*Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2*

*Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3*

**\* Data compared to the  
previous version altered.**

GB