

Page 1/11

Safety data sheet according to UK REACH

Printing date 09.12.2024 Version number 36 (replaces version 35) Revision: 09.12.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name MC-Fastpack PR solid - Komponente A

1.2 Relevant identified uses of the substance or mixture and uses advised against

· Sector of Use SU22 Professional uses: Public domain (administration,

education, entertainment, services, craftsmen)

• Product category PC9a Coatings and paints, thinners, paint removers

Process category PROC10 Roller application or brushing

· Environmental release

category ERC8f Widespread use leading to inclusion into/onto article

(outdoor)

ERC11a Widespread use of articles with low release (indoor)

· Article category AC13 Plastic articles

Application of the substance

/ the mixture Knife filler/ Surfacer

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier: MC-Bauchemie Müller GmbH & Co. KG

Am Kruppwald 1-8 D-46238 Bottrop Tel.: +49(0)2041-101-0 Fax.: +49(0)2041-101-400 E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG Hagackerstr. 10 CH-8953 Dietikon Tel.: +44-7400510 Fax: +44-7400533

Informing department:

msds@mc-bauchemie.de

· 1.4 Emergency telephone

number: Tel.: +49 / (0)700 24112112 (MCR)

Tel.: +1 872 5888271 (MCR)

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT RE 1 H372 Causes damage to the lung through prolonged or repeated exposure.

Route of exposure: Inhalation.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

· 2.2 Label elements

Labelling according to

Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP

regulation.

(Contd. on page 2)



Page 2/11

(Contd. of page 1)

Safety data sheet according to UK REACH

Printing date 09.12.2024 Version number 36 (replaces version 35) Revision: 09.12.2024

Trade name MC-Fastpack PR solid - Komponente A

· Hazard pictograms

SHS07 GHS08

· Signal word Danger

· Hazard-determining

components of labelling: tetraethyl-N,N'-(methylenedicyclohexane-4,1-diyl)bis-DL-aspartate

crystalline silica

· **Hazard statements** H317 May cause an allergic skin reaction.

H372 Causes damage to the lung through prolonged or repeated

exposure. Route of exposure: Inhalation.

H412 Harmful to aquatic life with long lasting effects.

• **Precautionary statements** P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P273 Avoid release to the environment.

P280 Wear protective gloves.

P333+P313 If skin irritation or rash occurs: Get medical advice/

attention.

P501 Dispose of contents/container in accordance with

local/regional/national/international regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· **Description:** Resin mixture.

Mixture consisting of the following components.

· Dangerous components:		
CAS: 136210-30-5 ELINCS: 429-270-1	tetraethyl-N,N'-(methylenedicyclohexane-4,1-diyl)bis-DL-aspartate	30-60%
Reg.nr.: 01-0000017556-64- xxxx	Skin Sens. 1, H317; Aquatic Chronic 3, H412	
CAS: 1317-65-3	Calcium carbonate substance with a Community workplace exposure limit	10-30%
CAS: 14808-60-7	crystalline silica STOT RE 1, H372	10-30%
A alalitia as a l insta assautia as	Towards and the listed because where the costs	10

• Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· **General information** Remove soiled, soaked clothing immediately.

(Contd. on page 3)



Page 3/11

Safety data sheet according to UK REACH

Printing date 09.12.2024 Version number 36 (replaces version 35) Revision: 09.12.2024

Trade name MC-Fastpack PR solid - Komponente A

(Contd. of page 2)

· After inhalation Remove person to fresh air, keep warm, allow to rest; if breathing

is difficult, seek medical attention.

· After skin contact In case of contact with skin, wash carefully with plenty of soap and

water. Consult a doctor in case of skin reactions.

• After eye contact Rinse the eyes with open eyelids for a sufficiently long time (at

least 10 minutes) with water that is as lukewarm as possible.

Consult an ophthalmologist.

· After swallowing Do NOT induce vomiting. Rinse mouth with water. Medical

attention required.

· 4.2 Most important symptoms and effects, both acute and

delayed Advice for the doctor: Elementary aid, decontamination,

symptomatic treatment.

4.3 Indication of any immediate medical attention

and special treatment needed Therapeutic measures: No information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

• Suitable extinguishing agents Use fire fighting measures that suit the environment.

 5.2 Special hazards arising from the substance or

mixture No further relevant information available.

· 5.3 Advice for firefighters

• **Protective equipment:** No special measures required.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and

emergency procedures Not required.

6.2 Environmental precautions:

Inform respective authorities in case product reaches water or

sewage system.

Dilute with much water.

· 6.3 Methods and material for

containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders,

universal binders, sawdust).

Ensure adequate ventilation.

6.4 Reference to other

sections No dangerous materials are released.

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

GB



Page 4/11

Safety data sheet according to UK REACH

Printing date 09.12.2024 Version number 36 (replaces version 35) Revision: 09.12.2024

Trade name MC-Fastpack PR solid - Komponente A

(Contd. of page 3)

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure sufficient air exchange and/or extraction in the work areas.

Air extraction is required for spray application.

For solid products: Avoid dust formation and dust deposits. Air limit values mentioned in section 8 must be monitored.

At workplaces where isocyanate aerosols and/or vapours can occur in higher concentrations, targeted air extraction must be used to prevent the occupational hygiene limit value from being

exceeded. The air must be moved away from people.

For products containing solvents: Explosion protection required. The personal protective measures described in section 8 must be observed. The protective measures required when handling isocyanates must be observed. Avoid contact with skin and eyes and inhalation of vapours.

Keep away from food and beverages. Wash hands before breaks and at the end of work and apply skin protection ointment. Store work clothes separately. Remove soiled, soaked clothing

immediately.

· Information about protection

against explosions and fires: Keep ignition sources away - do not smoke.

Protect from heat.

Do not store near heat sources.

· 7.2 Conditions for safe storage, including any incompatibilities

Keep container dry and tightly closed. Further information on the

storage conditions that must be observed for quality assurance reasons can be found in our technical data sheet.

· Storage

Requirements to be met by storerooms and containers:

Keep tightly closed in original packaging. Ventilate storage rooms

well. Carefully close opened containers and store upright to

prevent any leakage.

Storage temperature >5°C and <30°C

· Information about storage in

one common storage facility: May be stored together with hazardous substances of other

classes up to 200 kg.

· Further information about

storage conditions:

Keep container tightly closed in a well-ventilated place.

· Storage class

6.1C

· 7.3 Specific end use(s)

No further relevant information available.

- GE



Page 5/11

Safety data sheet according to UK REACH

Printing date 09.12.2024 Version number 36 (replaces version 35) Revision: 09.12.2024

Trade name MC-Fastpack PR solid - Komponente A

(Contd. of page 4)

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Components with critical values that require monitoring at the workplace:

CAS: 1317-65-3 Calcium carbonate

WEL Long-term value: 10* 4** mg/m3 *inhalable dust; **respirable

· DNELs

CAS: 136210-30-5 tetraethyl-N,N'-(methylenedicyclohexane-4,1-diyl)bis-DL-aspartate

DNEL 4 mg/kg bw/day (ArL) Inhalative DNEL 28 mg/m³ (ArL) 112 mg/m³ (Ark)

CAS: 1317-65-3 Calcium carbonate

Oral DNEL 6.1 mg/kg bw/Tag (ArL) Inhalative DNEL 10 mg/m³ (ArL)

PNECs

CAS: 136210-30-5 tetraethyl-N,N'-(methylenedicyclohexane-4,1-diyl)bis-DL-aspartate

PNEC 31.1 mg/l (Kla) 0.000013 mg/l (Mew)

0.00013 mg/l (Freshwater)

PNEC 0.1 mg/kg dwt (Bod)

0.02 mg/kg dwt (Marine water sediment) 0.21 mg/kg dwt (Fresh water sediment)

CAS: 1317-65-3 Calcium carbonate

PNEC 100 mg/l (Sewage Treatment Plant)

· Additional information: The lists that were valid during the compilation were used as basis.

· 8.2 Exposure controls · Appropriate engineering

No further data; see section 7. controls

· Individual protection measures, such as personal protective equipment

· General protective and

Do not smoke, eat or drink while working. Have eye wash hygienic measures

equipment ready.

Do not inhale gases/vapours/aerosols. Avoid contact with eyes and

Do not store food in the work area. Wash hands before breaks and

at the end of work.

Breathing equipment: Respiratory protection required at insufficiently ventilated

workplaces and when working with splashes. Fresh air masks or combination filters A2-P2 (EN529) are recommended for short-

term work.

If applicable, further recommendations for respiratory protection

can be found in the appendix.

In case of hypersensitivity of the respiratory tract (asthma, chronic

(Contd. on page 6)



Page 6/11

Safety data sheet according to UK REACH

Printing date 09.12.2024 Version number 36 (replaces version 35) Revision: 09.12.2024

Trade name MC-Fastpack PR solid - Komponente A

(Contd. of page 5)

bronchitis), handling of the product is not recommended.

An nicht ausreichend entlüfteten Arbeitsplätzen und bei Spritzverarbeitung Atemschutz erforderlich. Empfohlen werden Frischluftmaske oder für kurzzeitige Arbeiten Kombinationsfilter

A2-P2.

Bei Überempfindlichkeit der Atemwege und der Haut (Asthma, chronische Bronchitis, chronische Hautleiden) wird der Umgang

mit dem Produkt abgeraten.

• Hand protection Suitable materials for protective gloves; EN 374:

Butyl rubber - IIR: thickness \geq 0.5mm; breakthrough time \geq 480min. Fluororubber - FKM: thickness \geq 0.4mm; breakthrough time

≥480min.

Multi-layer glove - PE/EVAL/PE; Breakthrough time ≥480 min.

Recommendation: Dispose of contaminated gloves.

• Material of gloves The selection of the suitable gloves does not only depend on the

material, but also on further marks of quality and varies from

manufacturer to manufacturer.

· Penetration time of glove

material

Butyl rubber - IIR: thickness \geq 0.5mm; breakthrough time \geq 480min. Fluoro rubber - FKM: thickness \geq 0.4mm; breakthrough time

≥480min.

Multi-layer glove - PE/EVAL/PE; Breakthrough time ≥480 min.

· Eye/face protection

otection Wear safety goggles/face protection.

• **Body protection:** Wear suitable protective clothing when working.

In case of hypersensitivity of the skin, handling of the product is not

recommended.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

Physical stateColour:FluidGrey

Smell: Characteristic
 Odour threshold: Not determined.
 Melting point/freezing point: Not determined

· Boiling point or initial boiling point and

boiling range

185 °C (CAS: 136210-30-5 tetraethyl-N,N'-

(methylenedicyclohexane-4,1-diyl)bis-DL-

aspartate)

Flammability Not applicable.

· Lower and upper explosion limit

Lower: Not determined.Upper: Not determined.

· Flash point: 100 °C

(Contd. on page 7)



Page 7/11

Safety data sheet according to UK REACH

Printing date 09.12.2024 Version number 36 (replaces version 35) Revision: 09.12.2024

Trade name MC-Fastpack PR solid - Komponente A

(Contd. of page 6)

· Auto-ignition temperature: 350 °C (CAS: 152637-10-0 poly(oxy(methyl-1,2-

ethanediyl)))

· Decomposition temperature: Not determined.

• pH Mixture reacts violently with water.

Not determined.

· Viscosity:

Kinematic viscositydynamic:Not determined.

· Solubility

· Water: · Partition coefficient n-octanol/water (log

value) Not determined.

Steam pressure at 20 °C: 2 hPa (CAS: 152637-10-0 poly(oxy(methyl-1,2-

Void

Void

Void

ethanediyl)))

Fully miscible

· Vapour pressure at 50 °C: 8 hPa

Density and/or relative density

Density at 20 °C
 Relative density
 Vapour density
 Not determined.
 Not determined.

· 9.2 Other information

· Appearance:

· Form: Viscous

· Important information on protection of health

and environment, and on safety.

• Self-inflammability: Product is not selfigniting. • Explosive properties: Product is not explosive.

· Change in condition

Oxidising solids

· Organic peroxides

· Corrosive to metals

· Evaporation rate Not determined.

· Information with regard to physical hazard

classes · Explosives Void Flammable gases Void · Aerosols Void · Oxidising gases Void · Gases under pressure Void Flammable liquids Void Flammable solids Void Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids · Self-heating substances and mixtures Void Substances and mixtures, which emit flammable gases in contact with water Void · Oxidising liquids Void

(Contd. on page 8)



Page 8/11

Safety data sheet according to UK REACH

Printing date 09.12.2024 Version number 36 (replaces version 35) Revision: 09.12.2024

Trade name MC-Fastpack PR solid - Komponente A

(Contd. of page 7)

Desensitised explosives

Void

SECTION 10: Stability and reactivity

• 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability stable

· Thermal decomposition /

conditions to be avoided: No decomposition if used according to specifications.

· 10.3 Possibility of hazardous

reactions No dangerous reactions known

• 10.4 Conditions to avoid No further relevant information available. • 10.5 Incompatible materials: No further relevant information available.

· 10.6 Hazardous

decomposition products: No dangerous decomposition products known

SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

· Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values that are relevant for classification:

CAS: 136210-30-5 tetraethyl-N,N'-(methylenedicyclohexane-4,1-diyl)bis-DL-aspartate

Oral LD50 >2000 mg/kg (rat) (67/548/EWG, Annex V, B.1)
Dermal LD50 >2000 mg/kg (rat) (67/548/EWG, Annex V, B.3)

CAS: 1317-65-3 Calcium carbonate

Oral LD50 >2000 mg/kg (rat)
Dermal LD50 >2000 mg/kg (rat)

· Respiratory or skin

sensitisation May cause an allergic skin reaction.

· STOT-repeated exposure Causes damage to the lung through prolonged or repeated

exposure. Route of exposure: Inhalation.

· 11.2 Information on other hazards

· Endocrine disrupting properties

CAS: 128-37-0 | 2,6-Di-tert-butyl-p-cresol | List II

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

CAS: 136210-30-5 tetraethyl-N,N'-(methylenedicyclohexane-4,1-diyl)bis-DL-aspartate

LC50/96h 66 mg/l (Danio rerio) (OECD 203)

EC50 3110 mg/l (BEL)

(Contd. on page 9)



Page 9/11

Safety data sheet according to UK REACH

Printing date 09.12.2024 Version number 36 (replaces version 35) Revision: 09.12.2024

Trade name MC-Fastpack PR solid - Komponente A

EC50/48h 88.6 mg/l (Daphnia magna)

(Contd. of page 8)

NOEC	0.01 mg/l (Daphnia magna)
ErC50/72h	113 mg/l (Scenedesmus subspicatus)
CAS: 1317	-65-3 Calcium carbonate
EC50/72h	>14 mg/l (Desmodesmus subspicatus)
LC50/96h	>10000 mg/l (Oncorhynchus mykiss)
LC50/48h	>1000 mg/l (Daphnia magna)
EC50/48h	>1000 mg/l (Daphnia magna)

12.2 Persistence and

degradability No further relevant information available.

· 12.3 Bioaccumulative

potential
No further relevant information available.

12.4 Mobility in soil
No further relevant information available.

· 12.5 Results of PBT and vPvB assessment · PBT: Not applicable. · vPvB: Not applicable.

· 12.6 Endocrine disrupting

properties For information on endocrine disrupting properties see section 11.

12.7 Other adverse effects

· Remark: Harmful to fish

· Additional ecological information:

· General notes: Harmful to aquatic organisms

Do not allow product to reach ground water, water bodies or

sewage system.

Danger to drinking water if even small quantities leak into soil.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

• Recommendation Must not be disposed of together with household garbage. Do not

allow product to reach sewage system.

· Uncleaned packagings:

Recommendation: Empty contaminated packagings thoroughly. They can be recycled

after thorough and proper cleaning.

· Recommended cleaning

agent: Water, if necessary with cleaning agent.

SECTION 14: Transport information

· 14.1 UN number or ID number

· ADR, IMDG, IATA Void

(Contd. on page 10)



Page 10/11

Safety data sheet according to UK REACH

Printing date 09.12.2024 Version number 36 (replaces version 35) Revision: 09.12.2024

Trade name MC-Fastpack PR solid - Komponente A

(Contd. of page 9)

	(Conta.	oi page
· 14.2 UN proper shipping name · ADR, IMDG, IATA	Void	
· 14.3 Transport hazard class(es)		
· ADR, ADN, IMDG, IATA · Class	Void	
· 14.4 Packing group · ADR, IMDG, IATA	Void	
· 14.5 Environmental hazards: · Marine pollutant:	No	
· 14.6 Special precautions for user	Not applicable.	
· 14.7 Maritime transport in bulk accord IMO instruments	ling to Not applicable.	
· UN "Model Regulation":	Void	

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Poisons Act
- Regulated explosives precursors

None of the ingredients is listed.

Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

· Directive 2012/18/EU

· Named dangerous

substances - ANNEX I None of the ingredients is listed.

· 15.2 Chemical safety

assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

• Relevant phrases H317 May cause an allergic skin reaction.

H372 Causes damage to organs through prolonged or repeated

exposure.

H412 Harmful to aquatic life with long lasting effects.

(Contd. on page 11)



Page 11/11

Safety data sheet according to UK REACH

Printing date 09.12.2024

Version number 36 (replaces version 35)

Trade name MC-Fastpack PR solid - Komponente A

(Contd. of page 10)

Revision: 09.12.2024

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Skin Sens. 1: Skin sensitisation – Category 1

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

* * Data compared to the previous version altered.