



BE SURE. BUILD SURE.

Page 1/13

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.12.2022

Version number 18 (replaces version 17)

Revision: 25.12.2022

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name **MC-Flex 2099 - Komponente B**

Article number: 1004

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

#### Application of the substance / the mixture

Polyurethane resin  
Hardening agent/ Curing agent

#### 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: MC-Bauchemie Müller GmbH & Co. KG  
Am Kruppwald 1-8  
D-46238 Bottrop  
Tel.: +49(0)2041-101-0  
Fax.: +49(0)2041-101-400  
E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG  
Hagackerstr. 10  
CH-8953 Dietikon  
Tel.: +44-7400510  
Fax : +44-7400533

Informing department: msds@mc-bauchemie.de

#### 1.4 Emergency telephone number:

Tel.: +49 / (0)700 24112112 (MCR)  
Tel.: +48612864565

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification according to Regulation (EC) No 1272/2008

Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Carc. 2 H351 Suspected of causing cancer.

STOT SE 3 H335 May cause respiratory irritation.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

#### 2.2 Label elements

##### Labelling according to

Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)

GB



BE SURE. BUILD SURE.

### Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.12.2022

Version number 18 (replaces version 17)

Revision: 25.12.2022

**Trade name MC-Flex 2099 - Komponente B**

(Contd. of page 1)

· **Hazard pictograms**



GHS07 GHS08

· **Signal word**

**Danger**

· **Hazard-determining components of labelling:**

diphenylmethanediisocyanate, isomeres and homologues  
diphenylmethane-4,4'-di-isocyanate  
diphenylmethane-2,4'-diisocyanate  
MDI-basiertes Polyisocyanat-Prepolymer  
diphenylmethane-2,2'-diisocyanate

· **Hazard statements**

H332 Harmful if inhaled.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
H317 May cause an allergic skin reaction.  
H351 Suspected of causing cancer.  
H335 May cause respiratory irritation.  
H373 May cause damage to organs through prolonged or repeated exposure.

· **Precautionary statements**

P260 Do not breathe dust/fume/gas/mist/vapours/spray.  
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.  
P284 [In case of inadequate ventilation] wear respiratory protection.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.  
P403+P233 Store in a well-ventilated place. Keep container tightly closed.

· **Additional information:**

To avoid risks to human health and the environment, comply with the instructions for use.  
Contains isocyanates. May produce an allergic reaction.

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

## SECTION 3: Composition/information on ingredients

· **3.2 Mixtures**

· **Description:** Active substance with propellant.

(Contd. on page 3)



BE SURE. BUILD SURE.

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 25.12.2022

Version number 18 (replaces version 17)

Revision: 25.12.2022

**Trade name MC-Flex 2099 - Komponente B**

(Contd. of page 2)

Mixture consisting of the following components.

**Dangerous components:**

CAS: 9016-87-9	diphenylmethanediisocyanate, isomeres and homologues Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335, EUH204 Specific concentration limits: Eye Irrit. 2; H319: C ≥ 5 % Skin Irrit. 2; H315: C ≥ 5 % Resp. Sens. 1; H334: C ≥ 0.1 % STOT SE 3; H335: C ≥ 5 %	25-50%
CAS: 101-68-8 EINECS: 202-966-0 Reg.nr.: 01-2119457014-47	diphenylmethane-4,4'-di-isocyanate Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335, EUH204 Specific concentration limits: Eye Irrit. 2; H319: C ≥ 5 % Skin Irrit. 2; H315: C ≥ 5 % Resp. Sens. 1; H334: C ≥ 0.1 % STOT SE 3; H335: C ≥ 5 %	≥10-<25%
CAS: 5873-54-1 EINECS: 227-534-9	diphenylmethane-2,4'-diisocyanate Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335, EUH204 Specific concentration limits: Eye Irrit. 2; H319: C ≥ 5 % Skin Irrit. 2; H315: C ≥ 5 % Resp. Sens. 1; H334: C ≥ 0.1 % STOT SE 3; H335: C ≥ 5 %	≥10-<25%
CAS: 67815-87-6	MDI-basieres Polyisocyanat-Prepolymer Resp. Sens. 1, H334; STOT RE 2, H373; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	≥10-<20%

(Contd. on page 4)



BE SURE. BUILD SURE.

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 25.12.2022

Version number 18 (replaces version 17)

Revision: 25.12.2022

**Trade name MC-Flex 2099 - Komponente B**

(Contd. of page 3)

CAS: 2536-05-2 EINECS: 219-799-4	diphenylmethane-2,2'-diisocyanate Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335, EUH204 Specific concentration limits: Eye Irrit. 2; H319: C ≥ 5 % Skin Irrit. 2; H315: C ≥ 5 % Resp. Sens. 1; H334: C ≥ 0.1 % STOT SE 3; H335: C ≥ 5 %	≥1-<2.5%
CAS: 9016-87-9	diphenylmethanediisocyanate, isomeres and homologues Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335, EUH204 Specific concentration limits: Eye Irrit. 2; H319: C ≥ 5 % Skin Irrit. 2; H315: C ≥ 5 % Resp. Sens. 1; H334: C ≥ 0.1 % STOT SE 3; H335: C ≥ 5 %	≥1-<2.5%

· **Additional information** For the wording of the listed hazard phrases refer to section 16.

**SECTION 4: First aid measures**

· **4.1 Description of first aid measures**

- **General information** Instantly remove any clothing soiled by the product.  
Take affected persons into the open air.  
Seek medical treatment.
- **After inhalation** Supply fresh air.  
Call a doctor immediately.
- **After skin contact** Instantly wash with water and soap and rinse thoroughly.
- **After eye contact** Rinse opened eye for several minutes under running water.  
Seek medical treatment.
- **After swallowing** Call a doctor immediately.

· **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

· **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

**SECTION 5: Firefighting measures**

- **5.1 Extinguishing media**
- **Suitable extinguishing agents** Use fire fighting measures that suit the environment.
- **5.2 Special hazards arising from the substance or mixture** Can be released in case of fire

(Contd. on page 5)



BE SURE. BUILD SURE.

Page 5/13

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.12.2022

Version number 18 (replaces version 17)

Revision: 25.12.2022

Trade name **MC-Flex 2099 - Komponente B**

(Contd. of page 4)

Carbon monoxide (CO)

Nitrogen oxides (NO<sub>x</sub>)

Under certain fire conditions, traces of other toxic gases cannot be excluded, e.g.:

Hydrogen cyanide (HCN)

· **5.3 Advice for firefighters**

· **Protective equipment:**

Wear self-contained breathing apparatus.

### SECTION 6: Accidental release measures

· **6.1 Personal precautions, protective equipment and emergency procedures**

Ensure adequate ventilation

Use breathing protection against the effects of fumes/dust/aerosol.

· **6.2 Environmental precautions:**

Prevent material from reaching sewage system, holes and cellars.

· **6.3 Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

· **6.4 Reference to other sections**

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

### SECTION 7: Handling and storage

· **7.1 Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· **Information about protection against explosions and fires:**

No special measures required.

· **7.2 Conditions for safe storage, including any incompatibilities**

· **Storage**

· **Requirements to be met by storerooms and containers:**

Store only in the original container.

· **Information about storage in one common storage facility:**

Store away from foodstuffs.

· **Further information about storage conditions:**

Keep container tightly sealed.

· **7.3 Specific end use(s)**

No further relevant information available.

GB

(Contd. on page 6)



BE SURE. BUILD SURE.

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 25.12.2022

Version number 18 (replaces version 17)

Revision: 25.12.2022

**Trade name MC-Flex 2099 - Komponente B**

(Contd. of page 5)

**SECTION 8: Exposure controls/personal protection**

· **8.1 Control parameters**

· **Components with critical values that require monitoring at the workplace:**

**9016-87-9 diphenylmethanediisocyanate, isomeres and homologues**

WEL Short-term value: 0.07 mg/m<sup>3</sup>  
Long-term value: 0.02 mg/m<sup>3</sup>  
Sen; as -NCO

**101-68-8 diphenylmethane-4,4'-di-isocyanate**

WEL Short-term value: 0.07 mg/m<sup>3</sup>  
Long-term value: 0.02 mg/m<sup>3</sup>  
Sen; as -NCO

**5873-54-1 diphenylmethane-2,4'-diisocyanate**

WEL Short-term value: 0.07 mg/m<sup>3</sup>  
Long-term value: 0.02 mg/m<sup>3</sup>  
Sen; as -NCO

**2536-05-2 diphenylmethane-2,2'-diisocyanate**

WEL Short-term value: 0.07 mg/m<sup>3</sup>  
Long-term value: 0.02 mg/m<sup>3</sup>  
Sen; as -NCO

**9016-87-9 diphenylmethanediisocyanate, isomeres and homologues**

WEL Short-term value: 0.07 mg/m<sup>3</sup>  
Long-term value: 0.02 mg/m<sup>3</sup>  
Sen; as -NCO

· **DNELs**

**9016-87-9 diphenylmethanediisocyanate, isomeres and homologues**

Inhalative DNEL 0.05 mg/m<sup>3</sup> (ArL)

**101-68-8 diphenylmethane-4,4'-di-isocyanate**

Dermal DNEL 50 mg/kg bw/day (Ark)  
Inhalative DNEL 0.05 mg/m<sup>3</sup> (ArL)

**5873-54-1 diphenylmethane-2,4'-diisocyanate**

Inhalative DNEL 0.05 mg/m<sup>3</sup> (ArL)

**9016-87-9 diphenylmethanediisocyanate, isomeres and homologues**

Inhalative DNEL 0.05 mg/m<sup>3</sup> (ArL)

· **PNECs**

**9016-87-9 diphenylmethanediisocyanate, isomeres and homologues**

PNEC 1 mg/l (Sewage Treatment Plant)  
0.1 mg/l (Mew)  
1 mg/l (Suw)  
PNEC 1 mg/kg dwt (Bod)

(Contd. on page 7)



BE SURE. BUILD SURE.

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 25.12.2022

Version number 18 (replaces version 17)

Revision: 25.12.2022

**Trade name MC-Flex 2099 - Komponente B**

(Contd. of page 6)

**101-68-8 diphenylmethane-4,4'-di-isocyanate**

PNEC 1 mg/l (Sewage Treatment Plant)  
0.1 mg/l (Mew)  
1 mg/l (Suw)  
PNEC 1 mg/kg dwt (Bod)

**5873-54-1 diphenylmethane-2,4'-diisocyanate**

PNEC 1 mg/l (Sewage Treatment Plant)  
0.1 mg/l (Mew)  
1 mg/l (Suw)  
PNEC 1 mg/kg dwt (Bod)

**9016-87-9 diphenylmethanediisocyanate, isomeres and homologues**

PNEC 1 mg/l (Sewage Treatment Plant)  
0.1 mg/l (Mew)  
1 mg/l (Suw)  
PNEC 1 mg/kg dwt (Bod)

**Ingredients with biological limit values:**

**101-68-8 diphenylmethane-4,4'-di-isocyanate**

BMGV 1 µmol creatinine/mol  
Medium: urine  
Sampling time: At the end of the period od exposure  
Parameter: isocyanate-derived diamine

**5873-54-1 diphenylmethane-2,4'-diisocyanate**

BMGV 1 µmol creatinine/mol  
Medium: urine  
Sampling time: At the end of the period od exposure  
Parameter: isocyanate-derived diamine

**2536-05-2 diphenylmethane-2,2'-diisocyanate**

BMGV 1 µmol creatinine/mol  
Medium: urine  
Sampling time: At the end of the period od exposure  
Parameter: isocyanate-derived diamine

· **Additional information:** The lists that were valid during the compilation were used as basis.

· **8.2 Exposure controls**

· **Appropriate engineering controls**

No further data; see item 7.

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures**

Keep away from foodstuffs, beverages and food.  
Instantly remove any soiled and impregnated garments.  
Wash hands during breaks and at the end of the work.  
Avoid contact with the eyes and skin.  
Do not eat, drink or smoke while working.

(Contd. on page 8)





BE SURE. BUILD SURE.

### Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.12.2022

Version number 18 (replaces version 17)

Revision: 25.12.2022

**Trade name MC-Flex 2099 - Komponente B**

(Contd. of page 7)

- **Breathing equipment:** Short term filter device:  
*In case of brief exposure or low pollution use breathing filter apparatus. In case of intensive or longer exposure use breathing apparatus that is independent of circulating air.*
- **Hand protection** Conditionally suitable materials for protective gloves; EN 374-3:  
Nitrile rubber - NBR: Thickness  $\geq 0.35\text{mm}$ .  
Only suitable for splash protection. Only suitable for short-term exposure. In case of contamination, the protective gloves must be changed immediately.  
Protective gloves.  
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation  
After use of gloves apply skin-cleaning agents and skin cosmetics.
- **Material of gloves** Butyl rubber, BR  
Nitrile rubber, NBR  
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material** The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye/face protection** Safety glasses  
Tightly sealed safety glasses.
- **Body protection:** Protective work clothing.

## SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**
- **General Information**
- **Colour:** Dark brown
- **Smell:** Characteristic
- **Melting point/freezing point:** Not determined
- **Boiling point or initial boiling point and boiling range** 190 °C (9016-87-9 diphenylmethanediisocyanate, isomeres and homologues)
- **Flash point:** >200 °C
- **Ignition temperature:** 400 °C
- **pH** Not applicable.
- **Solubility**
- **Water:** Hydrolized
- **Density and/or relative density**
- **Density at 20 °C** 1.19 g/cm<sup>3</sup>

(Contd. on page 9)





BE SURE. BUILD SURE.

Page 9/13

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.12.2022

Version number 18 (replaces version 17)

Revision: 25.12.2022

Trade name MC-Flex 2099 - Komponente B

(Contd. of page 8)

### · 9.2 Other information

#### · Appearance:

#### · Form:

Fluid

#### · Important information on protection of health and environment, and on safety.

#### · Self-inflammability:

Product is not selfigniting.

#### · Explosive properties:

Product is not explosive.

#### · Information with regard to physical hazard classes

· Explosives Void

· Flammable gases Void

· Aerosols Void

· Oxidising gases Void

· Gases under pressure Void

· Flammable liquids Void

· Flammable solids Void

#### · Self-reactive substances and mixtures

Void

· Pyrophoric liquids Void

· Pyrophoric solids Void

#### · Self-heating substances and mixtures

Void

#### · Substances and mixtures, which emit flammable gases in contact with water

Void

· Oxidising liquids Void

· Oxidising solids Void

· Organic peroxides Void

· Corrosive to metals Void

· Desensitised explosives Void

## SECTION 10: Stability and reactivity

### · 10.1 Reactivity

No further relevant information available.

### · 10.2 Chemical stability

#### · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

### · 10.3 Possibility of hazardous reactions

Reacts with amines

### · 10.4 Conditions to avoid

No further relevant information available.

### · 10.5 Incompatible materials:

No further relevant information available.

### · 10.6 Hazardous

#### decomposition products:

No dangerous decomposition products known

GB

(Contd. on page 10)



BE SURE. BUILD SURE.

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 25.12.2022

Version number 18 (replaces version 17)

Revision: 25.12.2022

**Trade name MC-Flex 2099 - Komponente B**

(Contd. of page 9)

**SECTION 11: Toxicological information**

**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

**Acute toxicity** Harmful if inhaled.

**LD/LC50 values that are relevant for classification:**

**9016-87-9 diphenylmethanediisocyanate, isomeres and homologues**

Oral LD50 >10000 mg/kg (Rat)

Dermal LD50 >5000 mg/kg (Rab)

Inhalative LC50/4 h ~450 mg/l (Rat)

**101-68-8 diphenylmethane-4,4'-di-isocyanante**

Oral LD50 >10000 mg/kg (rat)

Dermal LD50 >9400 mg/kg (rabbit)

**9016-87-9 diphenylmethanediisocyanate, isomeres and homologues**

Oral LD50 >10000 mg/kg (Rat)

Dermal LD50 >5000 mg/kg (Rab)

Inhalative LC50/4 h ~450 mg/l (Rat)

**Skin corrosion/irritation** Causes skin irritation.

**Serious eye damage/irritation** Causes serious eye irritation.

**Respiratory or skin sensitisation** May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

**Germ cell mutagenicity** Based on available data, the classification criteria are not met.

**Carcinogenicity** Suspected of causing cancer.

**Reproductive toxicity** Based on available data, the classification criteria are not met.

**STOT-single exposure** May cause respiratory irritation.

**STOT-repeated exposure** May cause damage to organs through prolonged or repeated exposure.

**Aspiration hazard** Based on available data, the classification criteria are not met.

**11.2 Information on other hazards**

**Endocrine disrupting properties**

None of the ingredients is listed.

**SECTION 12: Ecological information**

**12.1 Toxicity**

**Aquatic toxicity:**

**101-68-8 diphenylmethane-4,4'-di-isocyanante**

EC50/24h >1000 mg/l (Daphnia magna)

LC50/96h >1000 mg/l (Brachydanio rerio)

NOEC >1000 mg/l (Eisenia foetida)

>10 mg/l (Daphnia magna)

(Contd. on page 11)



BE SURE. BUILD SURE.

### Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.12.2022

Version number 18 (replaces version 17)

Revision: 25.12.2022

**Trade name MC-Flex 2099 - Komponente B**

(Contd. of page 10)

- **12.2 Persistence and degradability** *No further relevant information available.*
- **12.3 Bioaccumulative potential** *No further relevant information available.*
- **12.4 Mobility in soil** *No further relevant information available.*
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** *Not applicable.*
- **vPvB:** *Not applicable.*
- **12.6 Endocrine disrupting properties** *The product does not contain substances with endocrine disrupting properties.*
- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:** *Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.*

#### **SECTION 13: Disposal considerations**

- **13.1 Waste treatment methods**
- **Recommendation** *Must not be disposed of together with household garbage. Do not allow product to reach sewage system.*
- **Uncleaned packagings:**
- **Recommendation:** *Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.*

#### **SECTION 14: Transport information**

- |   |                        |
|---|------------------------|
| · <b>14.1 UN number or ID number</b><br>· <b>ADR, ADN, IMDG, IATA</b>                       | <i>Void</i>            |
| · <b>14.2 UN proper shipping name</b><br>· <b>ADR, ADN, IMDG, IATA</b>                      | <i>Void</i>            |
| · <b>14.3 Transport hazard class(es)</b><br>· <b>ADR, ADN, IMDG, IATA</b><br>· <b>Class</b> | <i>Void</i>            |
| · <b>14.4 Packing group</b><br>· <b>ADR, IMDG, IATA</b>                                     | <i>Void</i>            |
| · <b>14.5 Environmental hazards:</b><br>· <b>Marine pollutant:</b>                          | <i>No</i>              |
| · <b>14.6 Special precautions for user</b>  | <i>Not applicable.</i> |
| · <b>14.7 Maritime transport in bulk according to IMO instruments</b>                       | <i>Not applicable.</i> |

(Contd. on page 12)



BE SURE. BUILD SURE.

### Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.12.2022

Version number 18 (replaces version 17)

Revision: 25.12.2022

Trade name MC-Flex 2099 - Komponente B

(Contd. of page 11)

· UN "Model Regulation": Void

#### SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- 15.2 Chemical safety assessment:

No further relevant information available.

A Chemical Safety Assessment has not been carried out.

#### SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
  - H315 Causes skin irritation.
  - H317 May cause an allergic skin reaction.
  - H319 Causes serious eye irritation.
  - H332 Harmful if inhaled.
  - H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
  - H335 May cause respiratory irritation.
  - H351 Suspected of causing cancer.
  - H373 May cause damage to organs through prolonged or repeated exposure.
  - EUH204 Contains isocyanates. May produce an allergic reaction.

- **Department issuing data specification sheet:**

Environment protection department.

- **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)  
 ICAO: International Civil Aviation Organisation  
 ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)  
 IMDG: International Maritime Code for Dangerous Goods  
 IATA: International Air Transport Association  
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service (division of the American Chemical Society)  
 DNEL: Derived No-Effect Level (UK REACH)  
 PNEC: Predicted No-Effect Concentration (UK REACH)  
 LC50: Lethal concentration, 50 percent  
 LD50: Lethal dose, 50 percent  
 PBT: Persistent, Bioaccumulative and Toxic  
 vPvB: very Persistent and very Bioaccumulative  
 Acute Tox. 4: Acute toxicity – Category 4  
 Skin Irrit. 2: Skin corrosion/irritation – Category 2

(Contd. on page 13)



BE SURE. BUILD SURE.

Page 13/13

**Safety data sheet**  
**according to 1907/2006/EC, Article 31**

Printing date 25.12.2022

Version number 18 (replaces version 17)

Revision: 25.12.2022

**Trade name MC-Flex 2099 - Komponente B**

(Contd. of page 12)

*Eye Irrit. 2: Serious eye damage/eye irritation – Category 2*

*Resp. Sens. 1: Respiratory sensitisation – Category 1*

*Skin Sens. 1: Skin sensitisation – Category 1*

*Carc. 2: Carcinogenicity – Category 2*

*STOT SE 3: Specific target organ toxicity (single exposure) – Category 3*

*STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2*

**\* Data compared to the  
previous version altered.**

GB