



BE SURE. BUILD SURE.

Page 1/9

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 05.03.2020

Version number 5

Revision: 05.03.2020

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name **MC-Floor TopSpeed Flex Plus - Komponente A**

Article number: 69

UFI: Y3NE-E06A-R00M-NGAA

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Sector of Use SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Product category PC9a Coatings and paints, thinners, paint removers

Process category PROC10 Roller application or brushing

Environmental release category

ERC8f Widespread use leading to inclusion into/onto article (outdoor)

ERC11a Widespread use of articles with low release (indoor)

Article category AC13 Plastic articles

Application of the substance / the mixture

Polyurethane lacquer

#### 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: MC-Bauchemie Müller GmbH & Co. KG  
Am Kruppwald 1-8  
D-46238 Bottrop  
Tel.: +49(0)2041-101-0  
Fax.: +49(0)2041-101-400  
E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG  
Hagackerstr. 10  
CH-8953 Dietikon  
Tel.: +44-7400510  
Fax : +44-7400533

Informing department: msds@mc-bauchemie.de

1.4 Emergency telephone number:

Tel.: +49 / (0)700 24112112 (MCR)  
Tel.: +48612864565

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

#### 2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

GB



BE SURE. BUILD SURE.

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 05.03.2020

Version number 5

Revision: 05.03.2020

**Trade name MC-Floor TopSpeed Flex Plus - Komponente A**

(Contd. of page 1)

· **Hazard pictograms**



GHS07

· **Signal word**

Warning

· **Hazard-determining components of labelling:**

tetraethyl-N,N'-(methylenedicyclohexane-4,1-diyl)bis-DL-aspartate poly(oxy(methyl-1,2-ethanediyl))  
4-morpholinecarbaldehyde

· **Hazard statements**

H317 May cause an allergic skin reaction.  
H412 Harmful to aquatic life with long lasting effects.

· **Precautionary statements**

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
P273 Avoid release to the environment.  
P280 Wear protective gloves.  
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.  
P321 Specific treatment (see on this label).  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

**SECTION 3: Composition/information on ingredients**

· **3.2 Chemical characterisation: Mixtures**

· **Description:** Resin mixture.  
Mixture consisting of the following components.

· **Dangerous components:**

CAS: 136210-30-5 ELINCS: 429-270-1 Reg.nr.: 01-0000017556-64-xxxx	tetraethyl-N,N'-(methylenedicyclohexane-4,1-diyl)bis-DL-aspartate Skin Sens. 1, H317; Aquatic Chronic 3, H412	25-50%
CAS: 152637-10-0	poly(oxy(methyl-1,2-ethanediyl)) Skin Sens. 1, H317; Aquatic Chronic 3, H412	≥2.5-<25%
CAS: 222417-26-7	Polyacrylate Eye Dam. 1, H318; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Irrit. 2, H315	≥0.25-<0.5%
CAS: 4394-85-8 EINECS: 224-518-3 Reg.nr.: 01-2119987993-12	4-morpholinecarbaldehyde Skin Sens. 1, H317	≥0.1-<0.5%

GB

(Contd. on page 3)



BE SURE. BUILD SURE.

Page 3/9

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 05.03.2020

Version number 5

Revision: 05.03.2020

Trade name MC-Floor TopSpeed Flex Plus - Komponente A

(Contd. of page 2)

### SECTION 4: First aid measures

#### · 4.1 Description of first aid measures

- **General information** No special measures required.
- **After inhalation** Void
- **After skin contact** The product is not skin irritating.
- **After eye contact** Rinse opened eye for several minutes under running water.
- **After swallowing** Rinse out mouth and then drink plenty of water.  
Seek medical treatment.

#### · 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

#### · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

### SECTION 5: Firefighting measures

#### · 5.1 Extinguishing media

- **Suitable extinguishing agents** Use fire fighting measures that suit the environment.

#### · 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

#### · 5.3 Advice for firefighters

- **Protective equipment:** No special measures required.

### SECTION 6: Accidental release measures

#### · 6.1 Personal precautions, protective equipment and emergency procedures

Not required.

#### · 6.2 Environmental precautions:

No special measures required.

#### · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

#### · 6.4 Reference to other sections

No dangerous materials are released.

GB

(Contd. on page 4)



BE SURE. BUILD SURE.

### Safety data sheet according to 1907/2006/EC, Article 31

Printing date 05.03.2020

Version number 5

Revision: 05.03.2020

Trade name MC-Floor TopSpeed Flex Plus - Komponente A

(Contd. of page 3)

#### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** *Open and handle container with care.*
- **Information about protection against explosions and fires:** *No special measures required.*
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and containers:** *No special requirements.*
- **Information about storage in one common storage facility:** *Not required.*
- **Further information about storage conditions:** *None.*
- **7.3 Specific end use(s)** *No further relevant information available.*

#### SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical systems:** *No further data; see item 7.*
- **8.1 Control parameters**
- **Components with critical values that require monitoring at the workplace:** *The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.*

##### · DNELs

##### 136210-30-5 tetraethyl-N,N'-(methylenedicyclohexane-4,1-diyl)bis-DL-aspartate

Dermal	DNEL	4 mg/kg bw/day (ArL)
Inhalative	DNEL	28 mg/m <sup>3</sup> (ArL)
		112 mg/m <sup>3</sup> (Ark)

##### · PNECs

##### 136210-30-5 tetraethyl-N,N'-(methylenedicyclohexane-4,1-diyl)bis-DL-aspartate

PNEC	31.1 mg/l (Kla)
	0.000013 mg/l (Mew)
	0.00013 mg/l (Suw)
PNEC	0.1 mg/kg dwt (Bod)
	0.02 mg/kg dwt (Marine water sediment)
	0.21 mg/kg dwt (Fresh water sediment)

- **Additional information:** *The lists that were valid during the compilation were used as basis.*

(Contd. on page 5)



BE SURE. BUILD SURE.

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 05.03.2020

Version number 5

Revision: 05.03.2020

**Trade name MC-Floor TopSpeed Flex Plus - Komponente A**

(Contd. of page 4)

- **8.2 Exposure controls**
- **Personal protective equipment**
- **General protective and hygienic measures**
  - The usual precautionary measures should be adhered to in handling the chemicals.
- **Protection of hands:**
  - Protective gloves.
- **Material of gloves**
  - Butyl rubber, BR
  - Recommended thickness of the material:  $\geq 0.5$  mm
- **Penetration time of glove material**
  - Breakthrough time:  $> = 480$  min
  - The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**
  - Safety glasses
  - Tightly sealed safety glasses.
- **Body protection:**
  - Protective work clothing.

**SECTION 9: Physical and chemical properties**

- **9.1 Information on basic physical and chemical properties**
- **General Information**
- **Appearance:**
  - Form:** Fluid
  - Colour:** Grey
  - Smell:** Characteristic
- **Change in condition**
  - Melting point/freezing point:** Not determined
  - Initial boiling point and boiling range:** Not determined
- **Flash point:**  $> 200$  °C
- **Self-inflammability:** Product is not selfigniting.
- **Explosive properties:** Product is not explosive.
- **Density at 20 °C** 1.42 g/cm<sup>3</sup>
- **Solubility in / Miscibility with Water:** Not miscible or difficult to mix
- **9.2 Other information** No further relevant information available.

**SECTION 10: Stability and reactivity**

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.

(Contd. on page 6)



BE SURE. BUILD SURE.

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 05.03.2020

Version number 5

Revision: 05.03.2020

**Trade name MC-Floor TopSpeed Flex Plus - Komponente A**

(Contd. of page 5)

- **10.3 Possibility of hazardous reactions** No dangerous reactions known
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known

**SECTION 11: Toxicological information**

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values that are relevant for classification:**

**136210-30-5 tetraethyl-N,N'-(methylenedicyclohexane-4,1-diyl)bis-DL-aspartate**

Oral LD50 >2,000 mg/kg (rat) (67/548/EWG, Annex V, B.1)

Dermal LD50 >2,000 mg/kg (rat) (67/548/EWG, Annex V, B.3)

**152637-10-0 poly(oxy(methyl-1,2-ethanediyl))**

Oral LD50 >2,000 mg/kg (rat)

NOAEL 1,000 mg/kg (rat)

Dermal LD50 >2,000 mg/kg (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

**SECTION 12: Ecological information**

· **12.1 Toxicity**

· **Aquatic toxicity:**

**136210-30-5 tetraethyl-N,N'-(methylenedicyclohexane-4,1-diyl)bis-DL-aspartate**

LC50/96h 66 mg/l (Danio rerio) (OECD 203)

EC50 3,110 mg/l (BEL)

EC50/48h 88.6 mg/l (Daphnia magna)

NOEC 0.01 mg/l (Daphnia magna)

(Contd. on page 7)



BE SURE. BUILD SURE.

### Safety data sheet according to 1907/2006/EC, Article 31

Printing date 05.03.2020

Version number 5

Revision: 05.03.2020

**Trade name MC-Floor TopSpeed Flex Plus - Komponente A**

(Contd. of page 6)

ErC50/72h	113 mg/l (Scenedesmus subspicatus)
<b>152637-10-0 poly(oxy(methyl-1,2-ethanediyl))</b>	
LC50/96h	66 mg/l (Danio rerio)
EC50	3,110 mg/l (BEL)
EC50/48h	88.6 mg/l (Daphnia magna)
ErC50/72h	113 mg/l (Scenedesmus subspicatus)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:** Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

#### SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· <b>European waste catalogue</b>	
08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 01 00	wastes from MFSU and removal of paint and varnish
08 01 12	waste paint and varnish other than those mentioned in 08 01 11

- **Uncleaned packagings:**
- **Recommendation:** Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.

#### SECTION 14: Transport information

· <b>14.1 UN-Number</b>	
· <b>ADR, ADN, IMDG, IATA</b>	Void
· <b>14.2 UN proper shipping name</b>	
· <b>ADR, ADN, IMDG, IATA</b>	Void

(Contd. on page 8)



BE SURE. BUILD SURE.

### Safety data sheet according to 1907/2006/EC, Article 31

Printing date 05.03.2020

Version number 5

Revision: 05.03.2020

**Trade name MC-Floor TopSpeed Flex Plus - Komponente A**

(Contd. of page 7)

· <b>14.3 Transport hazard class(es)</b>	
· <b>ADR, ADN, IMDG, IATA</b>	
· <b>Class</b>	Void
· <b>14.4 Packing group</b>	
· <b>ADR, IMDG, IATA</b>	Void
· <b>14.5 Environmental hazards:</b>	
· <b>Marine pollutant:</b>	No
· <b>14.6 Special precautions for user</b>	Not applicable.
· <b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code</b>	Not applicable.
· <b>UN "Model Regulation":</b>	Void

#### SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

#### SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
  - H315 Causes skin irritation.
  - H317 May cause an allergic skin reaction.
  - H318 Causes serious eye damage.
  - H400 Very toxic to aquatic life.
  - H410 Very toxic to aquatic life with long lasting effects.
  - H412 Harmful to aquatic life with long lasting effects.
- **Department issuing data specification sheet:** Environment protection department.
- **Abbreviations and acronyms:**
  - RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
  - ICAO: International Civil Aviation Organisation
  - ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
  - IMDG: International Maritime Code for Dangerous Goods
  - IATA: International Air Transport Association
  - GHS: Globally Harmonised System of Classification and Labelling of Chemicals

(Contd. on page 9)





BE SURE. BUILD SURE.

Page 9/9

**Safety data sheet**  
**according to 1907/2006/EC, Article 31**

Printing date 05.03.2020

Version number 5

Revision: 05.03.2020

**Trade name MC-Floor TopSpeed Flex Plus - Komponente A**

(Contd. of page 8)

*EINECS: European Inventory of Existing Commercial Chemical Substances*

*ELINCS: European List of Notified Chemical Substances*

*CAS: Chemical Abstracts Service (division of the American Chemical Society)*

*DNEL: Derived No-Effect Level (REACH)*

*PNEC: Predicted No-Effect Concentration (REACH)*

*LC50: Lethal concentration, 50 percent*

*LD50: Lethal dose, 50 percent*

*PBT: Persistent, Bioaccumulative and Toxic*

*vPvB: very Persistent and very Bioaccumulative*

*Skin Irrit. 2: Skin corrosion/irritation – Category 2*

*Eye Dam. 1: Serious eye damage/eye irritation – Category 1*

*Skin Sens. 1: Skin sensitisation – Category 1*

*Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1*

*Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1*

*Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3*

**\* Data compared to the  
previous version altered.**

GB