



BE SURE. BUILD SURE.

Page 1/14

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.12.2023

Version number 25 (replaces version 24)

Revision: 02.12.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name **MC-Floor Connect Adhesive - Komponente B**

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

1.3 Application of the substance / the mixture

Epoxy coating

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: MC-Bauchemie Müller GmbH & Co. KG
Am Kruppwald 1-8
D-46238 Bottrop
Tel.: +49(0)2041-101-0
Fax.: +49(0)2041-101-400
E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG
Hagackerstr. 10
CH-8953 Dietikon
Tel.: +44-7400510
Fax : +44-7400533

Informing department: msds@mc-bauchemie.de

1.4 Emergency telephone number:

Tel.: +49 / (0)700 24112112 (MCR)
Tel.: +48612864565

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Acute Tox. 4 H302 Harmful if swallowed.
Acute Tox. 4 H312 Harmful in contact with skin.
Skin Corr. 1A H314 Causes severe skin burns and eye damage.
Eye Dam. 1 H318 Causes serious eye damage.
Skin Sens. 1 H317 May cause an allergic skin reaction.
Repr. 2 H361fd Suspected of damaging fertility. Suspected of damaging the unborn child.
STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.
Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to

Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)

GB



BE SURE. BUILD SURE.

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.12.2023

Version number 25 (replaces version 24)

Revision: 02.12.2023

Trade name MC-Floor Connect Adhesive - Komponente B

(Contd. of page 1)

Hazard pictograms



GHS05 GHS07 GHS08

Signal word

Danger

Hazard-determining components of labelling:

polymer amine terminated
Isophorone diamine
2-piperazin-1-ylethylamine
Benzyl alcohol
2,4,6-Tris-(1-Phenyl-Ethyl) carboic acid
Orange juice oil
Aminoethylpiperazine

Hazard statements

H302 Harmful if swallowed.
H312 Harmful in contact with skin.
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H361fd Suspected of damaging fertility. Suspected of damaging the unborn child.
H373 May cause damage to organs through prolonged or repeated exposure.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P260 Do not breathe dusts or mists.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER/doctor.
P321 Specific treatment (see on this label).
P362+P364 Take off contaminated clothing and wash it before reuse.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.
vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture consisting of the following components.

Dangerous components:

	polymer amine terminated Eye Dam. 1, H318; Skin Irrit. 2, H315; Skin Sens. 1B, H317	10-30%
--	--	--------

(Contd. on page 3)



BE SURE. BUILD SURE.

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 02.12.2023

Version number 25 (replaces version 24)

Revision: 02.12.2023

Trade name MC-Floor Connect Adhesive - Komponente B

(Contd. of page 2)

CAS: 100-51-6	Benzyl alcohol Acute Tox. 4, H302; Acute Tox. 4, H332; Eye Irrit. 2, H319	10-30%
CAS: 61788-44-1 EINECS: 262-975-0	2,4,6-Tris-(1-Phenyl-Ethyl) carboic acid Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Skin Sens. 1, H317	≥10-<25%
CAS: 2855-13-2 EINECS: 220-666-8 Reg.nr.: 01-2119514687-32	Isophorone diamine Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317; Aquatic Chronic 3, H412	≥10-<25%
CAS: 15520-10-2 EINECS: 239-556-6	2-methylpentane-1,5-diamine Skin Corr. 1A, H314; Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; STOT SE 3, H335	≥10-<20%
CAS: 140-31-8 EINECS: 205-411-0 Reg.nr.: 01-2119471486-30	2-piperazin-1-ylethylamine Acute Tox. 3, H311; Repr. 2, H361fd; STOT RE 1, H372; Skin Corr. 1B, H314; Acute Tox. 4, H302; Skin Sens. 1, H317; Aquatic Chronic 3, H412	≥5-<10%
CAS: 9046-10-0 Reg.nr.: 01-2119557899-12	Polyoxypropylenediamine Skin Corr. 1B, H314; Aquatic Chronic 3, H412	≥2.5-<5%
CAS: 8028-48-6 EINECS: 232-433-8 Reg.nr.: 01-2119493353-35-XXXX	Orange juice oil Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Skin Sens. 1, H317	≥0.25-<1%
CAS: 140-31-8 EINECS: 205-411-0	Aminoethylpiperazine Acute Tox. 3, H311; Repr. 2, H361; STOT RE 1, H372; Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Sens. 1, H317; Aquatic Chronic 3, H412	≥0.1-<1%

· **Additional information**

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· **4.1 Description of first aid measures**

· **General information**

Instantly remove any clothing soiled by the product.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· **After inhalation**

Supply fresh air and call for doctor for safety reasons.
In case of unconsciousness bring patient into stable side position for transport.

· **After skin contact**

Instantly wash with water and soap and rinse thoroughly.

· **After eye contact**

Rinse opened eye for several minutes under running water. Then consult a doctor.

· **After swallowing**

Instantly call for doctor.

(Contd. on page 4)



BE SURE. BUILD SURE.

Page 4/14

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.12.2023

Version number 25 (replaces version 24)

Revision: 02.12.2023

Trade name MC-Floor Connect Adhesive - Komponente B

(Contd. of page 3)

Drink copious amounts of water and provide fresh air. Instantly call for doctor.

· **4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

· **4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

SECTION 5: Firefighting measures

· **5.1 Extinguishing media**

· **Suitable extinguishing agents** *Use fire fighting measures that suit the environment.*

· **5.2 Special hazards arising from the substance or mixture**

No further relevant information available.

· **5.3 Advice for firefighters**

· **Protective equipment:**

Put on breathing apparatus.

SECTION 6: Accidental release measures

· **6.1 Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

· **6.2 Environmental precautions:**

Inform respective authorities in case product reaches water or sewage system.

· **6.3 Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralising agent.

Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

· **6.4 Reference to other sections**

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage

· **7.1 Precautions for safe handling**

Store in cool, dry place in tightly closed containers.

Open and handle container with care.

· **Information about protection against explosions and fires:**

No special measures required.

(Contd. on page 5)

GB



BE SURE. BUILD SURE.

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 02.12.2023

Version number 25 (replaces version 24)

Revision: 02.12.2023

Trade name MC-Floor Connect Adhesive - Komponente B

(Contd. of page 4)

- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and containers:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Storage class** 8A
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**
- **Components with critical values that require monitoring at the workplace:** The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· **DNELs**

CAS: 100-51-6 Benzyl alcohol

Oral	DNEL	4 mg/kg bw/Tag (ArL) 20 mg/kg bw/Tag (Ark)
Dermal	DNEL	8 mg/kg bw/day (ArL) 40 mg/kg bw/day (Ark)
Inhalative	DNEL	22 mg/m ³ (ArL) 110 mg/m ³ (Ark)

CAS: 2855-13-2 Isophorone diamine

Oral	DNEL	0.526 mg/kg bw/Tag (ArL)
Inhalative	DNEL	20.1 mg/m ³ (ArL)

CAS: 15520-10-2 2-methylpentane-1,5-diamine

Dermal	DNEL	1.5 mg/kg bw/day (ArL)
Inhalative	DNEL	0.25 mg/m ³ (ArL) 0.5 mg/m ³ (Ark)

CAS: 140-31-8 2-piperazin-1-ylethylamine

Dermal	DNEL	3.33 mg/kg bw/day (ArL)
Inhalative	DNEL	10.6 mg/m ³ (ArL)

CAS: 9046-10-0 Polyoxypropylenediamine

Oral	DNEL	0.04 mg/kg bw/Tag (ArL)
Dermal	DNEL	2.5 mg/kg bw/day (ArL)

CAS: 8028-48-6 Orange juice oil

Oral	DNEL	4.44 mg/kg bw/Tag (ArL)
------	------	-------------------------

(Contd. on page 6)



BE SURE. BUILD SURE.

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 02.12.2023

Version number 25 (replaces version 24)

Revision: 02.12.2023

Trade name MC-Floor Connect Adhesive - Komponente B

(Contd. of page 5)

Dermal	DNEL	8.89 mg/kg bw/day (ArL)
Inhalative	DNEL	31.1 mg/m ³ (ArL)
CAS: 140-31-8 Aminoethylpiperazine		
Dermal	DNEL	3.33 mg/kg bw/day (ArL)
Inhalative	DNEL	10.6 mg/m ³ (ArL)
PNECs		
CAS: 100-51-6 Benzyl alcohol		
PNEC	0.527 mg/l (Marine water sediment)	
	0.1 mg/l (Mew)	
	1 mg/l (Fresh water sediment)	
PNEC	0.456 mg/kg dwt (Bod)	
	5.27 mg/kg dwt (Fresh water sediment)	
CAS: 2855-13-2 Isophorone diamine		
PNEC	0.006 mg/l (Mew)	
	0.06 mg/l (Freshwater)	
PNEC	0.578 mg/kg dwt (Sediment)	
	5.784 mg/kg dwt (Fresh water sediment)	
CAS: 15520-10-2 2-methylpentane-1,5-diamine		
PNEC	0.042 mg/l (Mew)	
	0.42 mg/l (Freshwater)	
CAS: 140-31-8 2-piperazin-1-ylethylamine		
PNEC	250 mg/l (Kla)	
	0.0058 mg/l (Mew)	
	0.058 mg/l (Freshwater)	
PNEC	1 mg/kg dwt (Bod)	
	21.5 mg/kg dwt (Sediment)	
	215 mg/kg dwt (Fresh water sediment)	
CAS: 9046-10-0 Polyoxypropylenediamine		
PNEC	7.5 mg/l (Sewage Treatment Plant)	
	0.015 mg/l (Fresh water)	
PNEC	0.0176 mg/kg dwt (Bod)	
	0.125 mg/kg dwt (Sediment)	
	0.132 mg/kg dwt (Fresh water sediment)	
CAS: 140-31-8 Aminoethylpiperazine		
PNEC	250 mg/l (Kla)	
	0.0058 mg/l (Mew)	
	0.058 mg/l (Freshwater)	
PNEC	1 mg/kg dwt (Bod)	
	21.5 mg/kg dwt (Sediment)	
	215 mg/kg dwt (Fresh water sediment)	

(Contd. on page 7)



BE SURE. BUILD SURE.

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.12.2023

Version number 25 (replaces version 24)

Revision: 02.12.2023

Trade name MC-Floor Connect Adhesive - Komponente B

(Contd. of page 6)

- **Additional information:** *The lists that were valid during the compilation were used as basis.*
- **8.2 Exposure controls**
- **Appropriate engineering controls** *No further data; see section 7.*
- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures** *Keep away from foodstuffs, beverages and food.
Instantly remove any soiled and impregnated garments.
Wash hands during breaks and at the end of the work.
Do not inhale gases / fumes / aerosols.
Avoid contact with the eyes and skin.*
- **Hand protection** *Protective gloves.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
After use of gloves apply skin-cleaning agents and skin cosmetics.*
- **Material of gloves** *The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.*
- **Penetration time of glove material** *The exact breakthrough time must be obtained from the protective glove manufacturer and must be observed.*
- **Eye/face protection** *Safety glasses
Tightly sealed safety glasses.*
- **Body protection:** *Protective work clothing.*

SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**
- **General Information**
- **Colour:** *Whitish*
- **Smell:** *Characteristic*
- **Melting point/freezing point:** *Not determined*
- **Boiling point or initial boiling point and boiling range** *193 °C (CAS: 15520-10-2 2-methylpentane-1,5-diamine)*
- **Lower and upper explosion limit**
- **Lower:** *1.3 Vol % (CAS: 100-51-6 Benzyl alcohol)*
- **Upper:** *13 Vol % (CAS: 100-51-6 Benzyl alcohol)*
- **Flash point:** *83 °C*
- **pH at 20 °C** *12.5*
- **Viscosity:**
- **Kinematic viscosity** *Not determined.*
- **dynamic at 20 °C:** *100 mPas*

(Contd. on page 8)



BE SURE. BUILD SURE.

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.12.2023

Version number 25 (replaces version 24)

Revision: 02.12.2023

Trade name MC-Floor Connect Adhesive - Komponente B

(Contd. of page 7)

- **Solubility**
- **Water:** Not miscible or difficult to mix
- **Steam pressure at 20 °C:** 0.1 hPa (CAS: 100-51-6 Benzyl alcohol)
- **Vapour pressure at 50 °C:** 0.7 hPa
- **Density and/or relative density**
- **Density at 20 °C** 1.02 g/cm³

- **9.2 Other information**
- **Appearance:**
- **Form:** Fluid
- **Important information on protection of health and environment, and on safety.**
- **Self-inflammability:** Product is not selfigniting.
- **Explosive properties:** Product is not explosive.

- **Information with regard to physical hazard classes**
- **Explosives** Void
- **Flammable gases** Void
- **Aerosols** Void
- **Oxidising gases** Void
- **Gases under pressure** Void
- **Flammable liquids** Void
- **Flammable solids** Void
- **Self-reactive substances and mixtures** Void
- **Pyrophoric liquids** Void
- **Pyrophoric solids** Void
- **Self-heating substances and mixtures** Void
- **Substances and mixtures, which emit flammable gases in contact with water** Void
- **Oxidising liquids** Void
- **Oxidising solids** Void
- **Organic peroxides** Void
- **Corrosive to metals** Void
- **Desensitised explosives** Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.

(Contd. on page 9)



BE SURE. BUILD SURE.

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 02.12.2023

Version number 25 (replaces version 24)

Revision: 02.12.2023

Trade name MC-Floor Connect Adhesive - Komponente B

(Contd. of page 8)

- **10.6 Hazardous decomposition products:** No dangerous decomposition products known

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Harmful if swallowed.
Harmful in contact with skin.

- **LD/LC50 values that are relevant for classification:**

CAS: 100-51-6 Benzyl alcohol

Oral	LD50	1230 mg/kg (rat)
	NOAEL 2nd year study	200 mg/kg (mouse)
Dermal	LD50	200 mg/kg (rat)
	LD50	2000 mg/kg (rabbit)
Inhalative	LC50/4 h	>4178 mg/l (rat)

CAS: 2855-13-2 Isophorone diamine

Oral	LD50	1030 mg/kg (ATE)
	LD50	1030 mg/kg (rat)
Dermal	NOAEL	250 mg/kg (rat)
	LD50	1840 mg/kg (rabbit)
		>2000 mg/kg (rat)

CAS: 15520-10-2 2-methylpentane-1,5-diamine

Oral	LD50	1170 mg/kg (rat)
Dermal	LD50	1870 mg/kg (rabbit)
Inhalative	LC50/4 h	19.6 mg/l (rat)

CAS: 140-31-8 2-piperazin-1-ylethylamine

Oral	LD50	2000-5000 mg/kg (rat)
		500 mg/kg (rabbit)
Dermal	LD50	200-1000 mg/kg (rabbit)

CAS: 9046-10-0 Polyoxypropylenediamine

Oral	LD50	2855 mg/kg (Rat)
Dermal	LD50	2980 mg/kg (Kan)

CAS: 8028-48-6 Orange juice oil

Oral	LD50	>4400 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rabbit)

CAS: 140-31-8 Aminoethylpiperazine

Oral	LD50	2000-5000 mg/kg (rat)
		500 mg/kg (rabbit)
Dermal	LD50	200-1000 mg/kg (rabbit)

- **Skin corrosion/irritation** Causes severe skin burns and eye damage.

(Contd. on page 10)



BE SURE. BUILD SURE.

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 02.12.2023

Version number 25 (replaces version 24)

Revision: 02.12.2023

Trade name MC-Floor Connect Adhesive - Komponente B

(Contd. of page 9)

- **Serious eye damage/irritation** Causes serious eye damage.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Suspected of damaging fertility. Suspected of damaging the unborn child.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** May cause damage to organs through prolonged or repeated exposure.
- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **11.2 Information on other hazards**

· **Endocrine disrupting properties**

CAS: 61788-44-1 2,4,6-Tris-(1-Phenyl-Ethyl) carboic acid

List II

SECTION 12: Ecological information

· **12.1 Toxicity**

· **Aquatic toxicity:**

CAS: 100-51-6 Benzyl alcohol

IC50/72h	700 mg/l (algae)
LC50/96h	460 mg/l (Pimephales promelas)
	10 mg/l (Lepomis macrochirus)

CAS: 2855-13-2 Isophorone diamine

LC50/96h	110 mg/l (Leucidus idus)
EC50	1120 mg/l (Pseudomonas putida)
EC50/48h	23 mg/l (Daphnia magna)
NOEC	1.5 mg/l (Desmodesmus subspicatus)
	3 mg/l (Daphnia magna)
ErC50/72h	>50 mg/l (Desmodesmus subspicatus)

CAS: 15520-10-2 2-methylpentane-1,5-diamine

EC50/72h	>100 mg/l (algae)
EC50	1825 mg/l (fish)
EC50/48h	19.8 mg/l (Daphnia magna)

CAS: 140-31-8 2-piperazin-1-ylethylamine

EC50/72h	>1000 mg/l (algae)
LC50/96h	2190 mg/l (fish)

CAS: 140-31-8 Aminoethylpiperazine

EC50/72h	>1000 mg/l (algae)
LC50/96h	2190 mg/l (fish)

· **12.2 Persistence and degradability**

No further relevant information available.

(Contd. on page 11)



BE SURE. BUILD SURE.

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.12.2023

Version number 25 (replaces version 24)

Revision: 02.12.2023

Trade name MC-Floor Connect Adhesive - Komponente B

(Contd. of page 10)

- **12.3 Bioaccumulative potential** *No further relevant information available.*
- **12.4 Mobility in soil** *No further relevant information available.*
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** *Not applicable.*
- **vPvB:** *Not applicable.*
- **12.6 Endocrine disrupting properties** *For information on endocrine disrupting properties see section 11.*
- **12.7 Other adverse effects**
- **Remark:** *Harmful to fish*
- **Additional ecological information:**
- **General notes:** *Harmful to aquatic organisms
Must not reach sewage water or drainage ditch undiluted or unneutralised.
Do not allow product to reach ground water, water bodies or sewage system.
Danger to drinking water if even small quantities leak into soil.*

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation** *Must not be disposed of together with household garbage. Do not allow product to reach sewage system.*
- **Uncleaned packagings:**
- **Recommendation:** *Disposal must be made according to official regulations.*

SECTION 14: Transport information

- **14.1 UN number or ID number**
- **ADR, IMDG, IATA** *UN2735*
- **14.2 UN proper shipping name**
- **ADR, IMDG, IATA** *AMINES, LIQUID, CORROSIVE, N.O.S. (Isophorone diamine, 2-methylpentane-1,5-diamine)*
- **14.3 Transport hazard class(es)**
- **ADR**
- **Class** *8 (C7) Corrosive substances.*
- **Label** *8*
- **IMDG, IATA**
- **Class** *8 Corrosive substances.*
- **Label** *8*
- **14.4 Packing group**
- **ADR, IMDG, IATA** *II*

(Contd. on page 12)



BE SURE. BUILD SURE.

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.12.2023

Version number 25 (replaces version 24)

Revision: 02.12.2023

Trade name MC-Floor Connect Adhesive - Komponente B

(Contd. of page 11)

· 14.5 Environmental hazards:	
· Marine pollutant:	No
· 14.6 Special precautions for user	
· Kemler Number:	Warning: Corrosive substances. 80
· EMS Number:	F-A, S-B
· Segregation groups	(SGG18) Alkalis
· Stowage Category	A
· Segregation Code	SG35 Stow "separated from" SGG1-acids
· 14.7 Maritime transport in bulk according to IMO instruments	
Not applicable.	
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· Transport category	2
· Tunnel restriction code	E
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S. (ISOPHORONE DIAMINE, 2-METHYLPENTANE-1,5-DIAMINE), 8, II

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture** No further relevant information available.
- Poisons Act**

· Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

(Contd. on page 13)



BE SURE. BUILD SURE.

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.12.2023

Version number 25 (replaces version 24)

Revision: 02.12.2023

Trade name MC-Floor Connect Adhesive - Komponente B

(Contd. of page 12)

· **Reportable poisons**

None of the ingredients is listed.

· **15.2 Chemical safety assessment:**

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H311 Toxic in contact with skin.
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H361 Suspected of damaging fertility or the unborn child.
- H361fd Suspected of damaging fertility. Suspected of damaging the unborn child.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.

· **Department issuing data specification sheet:**

Environment protection department.

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
 ICAO: International Civil Aviation Organisation
 ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 DNEL: Derived No-Effect Level (UK REACH)
 PNEC: Predicted No-Effect Concentration (UK REACH)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 Flam. Liq. 3: Flammable liquids – Category 3
 Acute Tox. 4: Acute toxicity – Category 4

(Contd. on page 14)



BE SURE. BUILD SURE.

Page 14/14

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 02.12.2023

Version number 25 (replaces version 24)

Revision: 02.12.2023

Trade name MC-Floor Connect Adhesive - Komponente B

(Contd. of page 13)

Acute Tox. 3: Acute toxicity – Category 3
Skin Corr. 1A: Skin corrosion/irritation – Category 1A
Skin Corr. 1B: Skin corrosion/irritation – Category 1B
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Skin Sens. 1: Skin sensitisation – Category 1
Skin Sens. 1B: Skin sensitisation – Category 1B
Repr. 2: Reproductive toxicity – Category 2
Repr. 2: Reproductive toxicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

*** Data compared to the previous version altered.**

GB