



BE SURE. BUILD SURE.

Page 1/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.11.2018

Revision: 06.11.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name **MC-Injekt GL-95 TR - Komponente B**

· 1.2 Relevant identified uses of the substance or mixture and uses advised against *No further relevant information available.*

· Application of the substance / the mixture
*Construction chemicals
Injektion*

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier: *MC-Bauchemie Müller GmbH & Co. KG
Am Kruppwald 1-8
D-46238 Bottrop
Tel.: +49(0)2041-101-0
Fax.: +49(0)2041-101-400
E-Mail: info@mc-bauchemie.de*

*MC-Bauchemie AG
Hagackerstr. 10
CH-8953 Dietikon
Tel.: +44-7400510
Fax : +44-7400533*

· Informing department: *Technische Abteilung
msds@mc-bauchemie.de*

· 1.4 Emergency telephone number: *Tel.: +49 / (0)700 24112112 (MCR)
Tel.: +48612864565*

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Ox. Sol. 2 *H272 May intensify fire; oxidiser.*

Acute Tox. 4 *H302 Harmful if swallowed.*

Skin Irrit. 2 *H315 Causes skin irritation.*

Eye Irrit. 2 *H319 Causes serious eye irritation.*

Resp. Sens. 1 *H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.*

Skin Sens. 1 *H317 May cause an allergic skin reaction.*

STOT SE 3 *H335 May cause respiratory irritation.*

· 2.2 Label elements

· Labelling according to

Regulation (EC) No 1272/2008 *The product is classified and labelled according to the CLP regulation.*

(Contd. on page 2)

GB



BE SURE. BUILD SURE.

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.11.2018

Revision: 06.11.2018

Trade name MC-Injekt GL-95 TR - Komponente B

(Contd. of page 1)

· Hazard pictograms



GHS03 GHS07 GHS08

· Signal word

Danger

· Hazard-determining components of labelling:

· Hazard statements

disodium peroxodisulphate
H272 May intensify fire; oxidiser.
H302 Harmful if swallowed.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317 May cause an allergic skin reaction.
H335 May cause respiratory irritation.

· Precautionary statements

P210 Keep away from heat. - No smoking.
P220 Keep/Store away from clothing/combustible materials.
P221 Take any precaution to avoid mixing with combustibles.
P284 [In case of inadequate ventilation] wear respiratory protection.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· Description: Mixture consisting of the following components.

· Dangerous components:

| | | |
|-------------------|---|---------|
| CAS: 7775-27-1 | disodium peroxodisulphate | 70-100% |
| EINECS: 231-892-1 | Ox. Sol. 2, H272; Resp. Sens. 1, H334; Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335 | |

GB

(Contd. on page 3)



BE SURE. BUILD SURE.

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.11.2018

Revision: 06.11.2018

Trade name MC-Injekt GL-95 TR - Komponente B

(Contd. of page 2)

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Instantly remove any clothing soiled by the product.

Do not leave affected persons unsupervised.

Take affected persons out of danger area and instruct to lie down.

Personal protection for the First Aider.

· After inhalation

Supply fresh air and call for doctor for safety reasons.

In case of unconsciousness bring patient into stable side position for transport.

· After skin contact

Do not use mouth to mouth or mouth to nose resuscitation.

Instantly wash with water and soap and rinse thoroughly.

· After eye contact

Rinse opened eye for several minutes under running water. Then consult a doctor.

· After swallowing

Do not induce vomiting; instantly call for medical help.

Rinse out mouth and then drink plenty of water.

· 4.2 Most important symptoms and effects, both acute and delayed

Allergic reactions

· 4.3 Indication of any immediate medical attention and special treatment needed

Medical supervision for at least 48 hours

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· Suitable extinguishing agents

Water haze

Water spray jet

· For safety reasons unsuitable extinguishing agents

Water with a full water jet.

· 5.2 Special hazards arising from the substance or mixture

Can be released in case of fire

Sulphur dioxide (SO₂)

· 5.3 Advice for firefighters

· Protective equipment:

Wear self-contained breathing apparatus.

· Additional information

Cool endangered containers with water spray jet.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

GB

(Contd. on page 4)



BE SURE. BUILD SURE.

Page 4/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.11.2018

Revision: 06.11.2018

Trade name **MC-Injekt GL-95 TR - Komponente B**

(Contd. of page 3)

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
 - Ensure adequate ventilation*
 - Avoid causing dust.*
 - Use breathing protection against the effects of fumes/dust/aerosol.*
 - Keep away from ignition sources*
 - Wear protective equipment. Keep unprotected persons away.*
- **6.2 Environmental precautions:**
 - Damp down dust with water spray jet.*
 - Do not allow to enter drainage system, surface or ground water.*
- **6.3 Methods and material for containment and cleaning up:**
 - Collect mechanically.*
 - Dispose of the material collected according to regulations.*
 - Ensure adequate ventilation.*
- **6.4 Reference to other sections**
 - See Section 7 for information on safe handling*
 - See Section 8 for information on personal protection equipment.*
 - See Section 13 for information on disposal.*

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
 - Any deposit of dust which cannot be avoided must be removed regularly.*
 - Ensure good ventilation/exhaustion at the workplace.*
 - Prevent formation of dust.*
- **Information about protection against explosions and fires:**
 - Substance/product is oxidising when dry.*
 - Substance/product can reduce the ignition temperature of flammable substances.*
 - Keep ignition sources away - Do not smoke.*
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and containers:**
 - Store only in the original container.*
- **Information about storage in one common storage facility:**
 - Do not store together with reducing agents, heavy-metal compounds, acids and alkalis.*
 - Store away from flammable substances.*
- **Further information about storage conditions:**
 - Store in cool, dry conditions in well sealed containers.*
 - Protect from humidity and keep away from water.*
 - This product is hygroscopic.*

(Contd. on page 5)

GB



BE SURE. BUILD SURE.

Page 5/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.11.2018

Revision: 06.11.2018

Trade name **MC-Injekt GL-95 TR - Komponente B**

· **7.3 Specific end use(s)** No further relevant information available.

(Contd. of page 4)

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **8.1 Control parameters** Allgemeine Staubgrenzwert:
Einatembare Fraktion (E-Staub): 10 mg/m³ (Schichtmittelwert)
Alveolengängige Fraktion (A-Staub): 3 mg/m³ (Schichtmittelwert)
- **Components with critical values that require monitoring at the workplace:** The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- **Additional information:** The lists that were valid during the compilation were used as basis.
- **8.2 Exposure controls**
- **Personal protective equipment**
- **General protective and hygienic measures** Do not inhale dust / smoke / mist.
Keep away from foodstuffs, beverages and food.
Instantly remove any soiled and impregnated garments.
Wash hands during breaks and at the end of the work.
- **Protection of hands:** Protective gloves.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
After use of gloves apply skin-cleaning agents and skin cosmetics.
- **Material of gloves** Butyl rubber, BR
Recommended thickness of the material: ≥ 0.5 mm
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material** Penetration: ≥ 480 min
The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:** Safety glasses
Tightly sealed safety glasses.
- **Body protection:** Impervious protective clothing
Protective work clothing.

GB

(Contd. on page 6)



BE SURE. BUILD SURE.

Page 6/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.11.2018

Revision: 06.11.2018

Trade name MC-Injekt GL-95 TR - Komponente B

(Contd. of page 5)

SECTION 9: Physical and chemical properties

| | |
|--|---|
| · 9.1 Information on basic physical and chemical properties | |
| · General Information | |
| · Appearance: | |
| Form: | Powder |
| Colour: | White |
| · Smell: | Odourless |
| · Odour threshold: | Not determined. |
| · pH-value (250 g/l) at 25 °C: | 4.3 |
| · Change in condition | |
| Melting point/freezing point: | ontleding 200 °C Not applicable |
| Initial boiling point and boiling range: | Not applicable |
| · Flash point: | Not applicable |
| · Inflammability (solid, gaseous) | Contact with combustible material may cause fire. |
| · Decomposition temperature: | ~180 °C °C (SADT (UN-Test H.4)) |
| · Self-inflammability: | Not determined. |
| · Explosive properties: | Explosive when mixed with combustible material. |
| · Critical values for explosion: | |
| Lower: | Not determined. |
| Upper: | Not determined. |
| · Steam pressure: | Not applicable. |
| · Density at 20 °C | 1.20 ~ 2.59 g/cm ³ |
| · Settled apparent density at 20 °C | 1150 ~ 1350 kg/m ³ |
| · Relative density | Not determined. |
| · Vapour density | Not applicable. |
| · Evaporation rate | Not applicable. |
| · Solubility in / Miscibility with Water at 20 °C: | 545 ~ 556 g/l |
| · Partition coefficient: n-octanol/water: | Not determined. |
| · Viscosity: | |
| dynamic: | Not applicable. |
| kinematic: | Not applicable. |
| · 9.2 Other information | No further relevant information available. |

SECTION 10: Stability and reactivity

| | |
|--------------------------|--|
| · 10.1 Reactivity | No further relevant information available. |
|--------------------------|--|

(Contd. on page 7)

GB



BE SURE. BUILD SURE.

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.11.2018

Revision: 06.11.2018

Trade name MC-Injekt GL-95 TR - Komponente B

(Contd. of page 6)

- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
 - To avoid thermal decomposition do not overheat.
 - Zündquellen fernhalten
 - Maßnahmen gegen elektrostatische Aufladungen treffen.
 - Vor Feuchtigkeit schützen.
 - In feuchtem Zustand schon bei Raumtemperatur langsame Zersetzung.
- **10.3 Possibility of hazardous reactions**
 - Reacts with fats and oils
 - Reacts with alkali (lyes)
 - Danger of bursting
 - Acts as an oxidizing agent on organic materials such as wood, paper and fats
 - Korrosionswirkung auf Gebrauchsmetalle. Feuergefahr bei Berührung mit brennbaren Stoffen.
 - Reacts with acids
 - Reacts with fabric soaked in the product (e.g. cleaning wool)
 - Reacts with reducing agents
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:**
 - Sulphur oxides (SOx)
 - Oxygen
 - Danger of toxic pyrolysis products

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
 - **Acute toxicity** Harmful if swallowed.
 - **LD/LC50 values that are relevant for classification:**
- | | | |
|--|----------|---------------------------|
| 7775-27-1 disodium peroxodisulphate | | |
| Oral | LD50 | 920 mg/kg (Ratte) |
| Dermal | LD50 | >10,000 mg/kg (Kaninchen) |
| Inhalative | LC50/4 h | >5.1 mg/l (Ratte) |
- **Primary irritant effect:**
 - **Skin corrosion/irritation** Causes skin irritation.
 - **Serious eye damage/irritation** Causes serious eye irritation.
 - **Respiratory or skin sensitisation**
 - May cause allergy or asthma symptoms or breathing difficulties if inhaled.
 - May cause an allergic skin reaction.
 - **CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)**
 - **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
 - **Carcinogenicity** Based on available data, the classification criteria are not met.
 - **Reproductive toxicity** Based on available data, the classification criteria are not met.
 - **STOT-single exposure** May cause respiratory irritation.
 - **STOT-repeated exposure** Based on available data, the classification criteria are not met.

(Contd. on page 8)



BE SURE. BUILD SURE.

Page 8/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.11.2018

Revision: 06.11.2018

Trade name **MC-Injekt GL-95 TR - Komponente B**

· **Aspiration hazard**

Based on available data, the classification criteria are not met.

(Contd. of page 7)

SECTION 12: Ecological information

· **12.1 Toxicity**

· **Aquatic toxicity:**

7775-27-1 disodium peroxodisulphate

EC50/72h 116 mg/l (Bak)

LC50/96h 771 mg/l (*Oncorhynchus mykiss*)

EC50/48h 133 mg/l (*Daphnia magna*)

· **12.2 Persistence and degradability**

Anorganic product, is not eliminable from water by means of biological cleaning processes.

· **12.3 Bioaccumulative potential**

No further relevant information available.

· **12.4 Mobility in soil**

No further relevant information available.

· **Additional ecological information:**

· **General notes:**

Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

· **12.5 Results of PBT and vPvB assessment**

· **PBT:**

Not applicable.

· **vPvB:**

Not applicable.

· **12.6 Other adverse effects**

No further relevant information available.

SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**

· **Recommendation**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· **Waste disposal key number:**

Die Abfallschlüsselnummer nach der Abfallverzeichnis-Verordnung (AVV) ist abhängig vom Abfallerzeuger und kann dadurch für ein Produkt unterschiedlich sein. Die Abfallschlüsselnummer ist daher von jedem Abfallerzeuger gesondert zu ermitteln.

· **Uncleaned packagings:**

· **Recommendation:**

Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.

SECTION 14: Transport information

· **14.1 UN-Number**

· **ADR, IMDG, IATA**

UN1505

(Contd. on page 9)

GB



BE SURE. BUILD SURE.

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.11.2018

Revision: 06.11.2018

Trade name MC-Injekt GL-95 TR - Komponente B

(Contd. of page 8)

| | |
|--|---|
| <ul style="list-style-type: none"> · 14.2 UN proper shipping name · ADR · IMDG, IATA | <p>1505 SODIUM PERSULPHATE SODIUM PERSULPHATE</p> |
| <ul style="list-style-type: none"> · 14.3 Transport hazard class(es) · ADR · Class · Label | <p>5.1 (O2) Oxidising substances. 5.1</p> |
| <ul style="list-style-type: none"> · IMDG, IATA · Class · Label | <p>5.1 Oxidising substances. 5.1</p> |
| <ul style="list-style-type: none"> · 14.4 Packing group · ADR, IMDG, IATA | <p>III</p> |
| <ul style="list-style-type: none"> · 14.5 Environmental hazards: · Marine pollutant: | <p>No</p> |
| <ul style="list-style-type: none"> · 14.6 Special precautions for user · Kemler Number: · EMS Number: · Stowage Category · Segregation Code | <p>Warning: Oxidising substances. 50 F-A,S-Q A SG39 Stow "separated from" ammonium compounds other than AMMONIUM PERSULPHATE (UN 1444). SG49 Stow "separated from" cyanides</p> |
| <ul style="list-style-type: none"> · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code | <p>Not applicable.</p> |
| <ul style="list-style-type: none"> · Transport/Additional information: · ADR · Limited quantities (LQ) · Excepted quantities (EQ) · Transport category · Tunnel restriction code | <p>5 kg Code: E1 Maximum net quantity per inner packaging: 30 g Maximum net quantity per outer packaging: 1000 g 3 E</p> |
| <ul style="list-style-type: none"> · IMDG · Limited quantities (LQ) · Excepted quantities (EQ) | <p>5 kg Code: E1 Maximum net quantity per inner packaging: 30 g Maximum net quantity per outer packaging: 1000 g</p> |
| <ul style="list-style-type: none"> · UN "Model Regulation": | <p>UN 1505 SODIUM PERSULPHATE, 5.1, III</p> |

GB

(Contd. on page 10)



BE SURE. BUILD SURE.

Page 10/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.11.2018

Revision: 06.11.2018

Trade name MC-Injekt GL-95 TR - Komponente B

(Contd. of page 9)

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
 - Directive 2012/18/EU
 - Named dangerous substances - ANNEX I *None of the ingredients is listed.*
 - Seveso category *P8 OXIDISING LIQUIDS AND SOLIDS*
 - Qualifying quantity (tonnes) for the application of lower-tier requirements *50 t*
 - Qualifying quantity (tonnes) for the application of upper-tier requirements *200 t*
 - National regulations
 - Other regulations, limitations and prohibitive regulations *Die Vorschriften der Chemikalien-Verbotsverordnung sowie Anhang XVII der Verordnung (EG) Nr. 1907/2006 sind zu beachten.*
- **15.2 Chemical safety assessment:** *A Chemical Safety Assessment has not been carried out.*

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
 - H272 May intensify fire; oxidiser.*
 - H302 Harmful if swallowed.*
 - H315 Causes skin irritation.*
 - H317 May cause an allergic skin reaction.*
 - H319 Causes serious eye irritation.*
 - H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.*
 - H335 May cause respiratory irritation.*
- **Department issuing data specification sheet:** *Environment protection department.*
- **Abbreviations and acronyms:**
 - RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)*
 - ICAO: International Civil Aviation Organisation*
 - ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)*
 - IMDG: International Maritime Code for Dangerous Goods*
 - IATA: International Air Transport Association*
 - GHS: Globally Harmonised System of Classification and Labelling of Chemicals*
 - EINECS: European Inventory of Existing Commercial Chemical Substances*
 - ELINCS: European List of Notified Chemical Substances*

(Contd. on page 11)

GB



BE SURE. BUILD SURE.

Page 11/11

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 06.11.2018

Revision: 06.11.2018

Trade name MC-Injekt GL-95 TR - Komponente B

(Contd. of page 10)

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Ox. Sol. 2: Oxidizing solids – Category 2

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Resp. Sens. 1: Respiratory sensitisation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

· * **Data compared to the
previous version altered.**

GB