

Page 1/11

Safety data sheet according to UK REACH

Printing date 30.03.2025 Version number 27 (replaces version 26) Revision: 30.03.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

• Trade name MC-PowerFlow 5103

· Article number: 3636

· 1.2 Relevant identified uses of the substance or mixture

and uses advised against No further relevant information available.

· Application of the substance

/ the mixture Concrete/Mortar admixtures

· 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: MC-Bauchemie Müller GmbH & Co. KG

Am Kruppwald 1-8 D-46238 Bottrop Tel.: +49(0)2041-101-0 Fax.: +49(0)2041-101-400 E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG Hagackerstr. 10 CH-8953 Dietikon Tel.: +44-7400510 Fax: +44-7400533

Informing department:

1.4 Emergency telephone

number:

Tel.: +49 / (0)700 24112112 (MCR)

Tel.: +1 872 5888271 (MCR)

msds@mc-bauchemie.de

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Skin Sens. 1 H317 May cause an allergic skin reaction.

- · 2.2 Label elements
- Labelling according to

Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms



Warning

· Hazard-determining

· Signal word

components of labelling: 2-Octyl-2H-isothiazol-3-on 1,2-benzisothiazol-3(2H)-one

Mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-

isothiazol-3-one (3:1)

(Contd. on page 2)



Page 2/11

Safety data sheet according to UK REACH

Revision: 30.03.2025 Printing date 30.03.2025 Version number 27 (replaces version 26)

Trade name MC-PowerFlow 5103

(Contd. of page 1)

· Hazard statements H317 May cause an allergic skin reaction.

Precautionary statements Avoid breathing dust/fume/gas/mist/vapours/spray. P261

> P280 Wear protective gloves.

P362+P364 Take off contaminated clothing and wash it before

P333+P313 If skin irritation or rash occurs: Get medical advice/

attention.

P321 Specific treatment (see on this label).

P501 Dispose of contents/container in accordance with

local/regional/national/international regulations.

· Additional information: Contains biocidal products: 1,2-benzisothiazol-3(2H)-one, 2-Octyl-

2H-isothiazol-3-on, Mixture of: 5-chloro-2-methyl-2H-isothiazol-3-

one and 2-methyl-2H-isothiazol-3-one (3:1)

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable. · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.1 Substances

CAS No. Designation: void Void · Identification number(s):

· 3.2 Mixtures

Description: Mixture consisting of the following components.

· Dangerous components:

CAS: 2634-33-5 1,2-benzisothiazol-3(2H)-one <0.025%

EINECS: 220-120-9 Acute Tox. 2, H330; Eye Dam. 1, H318; Aquatic Acute

1, H400; Aquatic Chronic 1, H410; Acute Tox. 4, H302;

Skin Irrit. 2, H315; Skin Sens. 1, H317

Specific concentration limit:

Skin Sens. 1; H317: C ≥0.05 %

(Contd. on page 3)



Page 3/11

Safety data sheet according to UK REACH

Printing date 30.03.2025 Version number 27 (replaces version 26) Revision: 30.03.2025

Trade name MC-PowerFlow 5103

040 00500 00 1		(Contd. of page
CAS: 26530-20-1	2-Octyl-2H-isothiazol-3-on	<i>≥</i> 0.0015-<0.0025%
EINECS: 247-761-7	Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 2,	
	H330; Skin Corr. 1, H314; Aquatic Acute 1, H400	
	(M=100); Aquatic Chronic 1, H410 (M=100); Skin Sens.	
	1A, H317, EUH071	
	ATE: LD50 oral: 125 mg/kg	
	LD50 dermal: 311 mg/kg	
	LC50/4 h inhalative: 0.27 mg/l	
	Specific concentration limit:	
	Skin Sens. 1A; H317: C ≥0.0015 %	
CAS: 55965-84-9	Mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one and	≥0.00025-<0.00155
	2-methyl-2H-isothiazol-3-one (3:1)	
	Acute Tox. 3, H301; Acute Tox. 2, H310; Acute Tox. 2,	
	H330; Skin Corr. 1C, H314; Eye Dam. 1, H318; Aquatic	
	Acute 1, H400 (M=100); Aquatic Chronic 1, H410	
	(M=100); Skin Sens. 1A, H317, EUH071	
	Specific concentration limits:	
	Skin Corr. 1C; H314: C ≥0.6 %	
	Skin Irrit. 2; H315: 0.06 % ≤ C < 0.6 %	
	Eye Dam. 1; H318: C ≥ 0.6 %	
	Eye Irrit. 2; H319: 0.06 % ≤ C < 0.6 %	
	Skin Sens. 1A; H317: C ≥ 0.0015 %	

· Additional information

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

• General information For all first aid measures: observe self-protection and consult a

doctor!

After inhalation
 After skin contact
 Take the person out into the fresh air.
 Remove contaminated clothing immediately.

Hold affected areas under cold running water for at least 15

minutes.

· After eye contact Rinse for 10 minutes under running water with the eyelids open or

use eye rinsing solution. Always consult an ophthalmologist!

• After swallowing Drink plenty of water in small sips.

Do not induce vomiting.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· Suitable extinguishing agents Void

5.2 Special hazards arising from the substance or

mixture No further relevant information available.

(Contd. on page 4)



Page 4/11

Safety data sheet according to UK REACH

Printing date 30.03.2025 Version number 27 (replaces version 26) Revision: 30.03.2025

Trade name MC-PowerFlow 5103

(Contd. of page 3)

· 5.3 Advice for firefighters

· Protective equipment: No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and

emergency procedures Not required.

· 6.2 Environmental

precautions: No special measures required.

· 6.3 Methods and material for

containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders,

universal binders, sawdust).

· 6.4 Reference to other

sections No dangerous materials are released.

SECTION 7: Handling and storage

· 7.1 Precautions for safe

handling Avoid splashing.

Avoid dust development with powder products.

Limit the storage quantity at the workplace to one shift

requirement.

Do not leave containers open.

Provide washing facilities in the work area. Provide an eye shower or eyewash bottle.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage

· Requirements to be met by

storerooms and containers: Avoid splashing.

Avoid dust development with powder products.

Limit the storage quantity at the workplace to one shift

requirement.

Do not leave containers open.

Provide washing facilities in the work area. Provide an eye shower or eyewash bottle.

· Information about storage in

one common storage facility: Combined storage bans apply from a total storage quantity of 200

кg.

Do not store together with substances of the following LGK: 1;

5.1A; 5.2; 6.2; 7

Storage with substances of the following LGK is only possible under the conditions specified in TRGS 510: 4.1A; 4.2; 4.3; 5.1C

· Further information about

storage conditions: None.

(Contd. on page 5)



Page 5/11

Safety data sheet according to UK REACH

Printing date 30.03.2025 Version number 27 (replaces version 26) Revision: 30.03.2025

Trade name MC-PowerFlow 5103

(Contd. of page 4)

· Storage class

SECTION 8: Exposure controls/personal protection

12

· 8.1 Control parameters · Components with critical

values that require

monitoring at the workplace: The product does not contain any relevant quantities of materials

with critical values that have to be monitored at the workplace.

• Additional information: The lists that were valid during the compilation were used as basis.

· 8.2 Exposure controls · Appropriate engineering

controls No further data; see section 7.

· Individual protection measures, such as personal protective equipment

· General protective and

hygienic measures Do not store any foodstuffs or eat, drink, snuff or smoke in the

work area!

Avoid contact with eyes, skin and clothing!

Clean hands thoroughly after work and before cleaning! Use skin care products after work (moisturising cream).

Change wet/uncleaned clothing immediately, place in water and

only use again after cleaning!

• Breathing equipment: If the limit value is exceeded:

Combination filter A-P2 (brown/white).

· Hand protection Gloves made of: Natural latex, polychloroprene, nitrile rubber.

(Category 3 chemical protective gloves, recognisable by the CE

mark with four-digit test number).

When wearing protective gloves, cotton undergloves are

recommended.

see "Hand protection"

· Material of gloves

Penetration time of glove

material

The exact breakthrough time must be obtained from the protective

glove manufacturer and must be observed.

• Eye/face protection Gauze goggles

Body protection: Alkali-resistant protective clothing

Skin protection Use greasy skin protection ointment for all uncovered parts of the

body!

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Colour: Dark brown Characteristic

· Melting point/freezing point: <0 °C

(Contd. on page 6)



Page 6/11

Safety data sheet according to UK REACH

Printing date 30.03.2025 Version number 27 (replaces version 26) Revision: 30.03.2025

Trade name MC-PowerFlow 5103

(Contd. of page 5)

Boiling point or initial boiling point and

boiling range 100 °C (CAS: 7732-18-5 Water)

· Flash point: Not applicable

· pH at 20 °C 5.5

· Viscosity:

Kinematic viscositydynamic:Not determined.Not determined.

·Solubility

· Water: Fully miscible

· Steam pressure at 20 °C: 23 hPa (CAS: 7732-18-5 Water)

Density and/or relative density

Density at 20 °C 1.04 g/cm³

· 9.2 Other information

· Appearance:

· Form: Fluid

· Important information on protection of health

and environment, and on safety.

• Self-inflammability: Product is not selfigniting. • Explosive properties: Product is not explosive.

· Information with regard to physical hazard

classes

Explosives

Flammable gases

Oxidising gases

Gases under pressure

Flammable liquids

Flammable solids

Void

Void

Void

Void

Void

Void

Void

Void

Void

Self-reactive substances and mixtures
 Pyrophoric liquids
 Pyrophoric solids
 Self-heating substances and mixtures

· Substances and mixtures, which emit

flammable gases in contact with water

Oxidising liquids
Oxidising solids
Organic peroxides
Corrosive to metals
Desensitised explosives
Void

SECTION 10: Stability and reactivity

• 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

· Thermal decomposition /

conditions to be avoided: No decomposition if used according to specifications.

(Contd. on page 7)



Page 7/11

Safety data sheet according to UK REACH

Printing date 30.03.2025 Version number 27 (replaces version 26) Revision: 30.03.2025

Trade name MC-PowerFlow 5103

(Contd. of page 6)

· 10.3 Possibility of hazardous

reactions No dangerous reactions known

• 10.4 Conditions to avoid No further relevant information available. • 10.5 Incompatible materials: No further relevant information available.

· 10.6 Hazardous

decomposition products: No dangerous decomposition products known

SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

· Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values that are relevant for classification:					
CAS: 2634-33-5 1,2-benzisothiazol-3(2H)-one					
LD50	1020 mg/kg (rat)				
LD50	>2000 mg/kg (rat)				
CAS: 26530-20-1 2-Octyl-2H-isothiazol-3-on					
LD50	125 mg/kg (ATE)				
	500 mg/kg (rat)				
LD50	311 mg/kg (ATE)				
	>2000 mg/kg (rat)				
LC50/4 h	0.27 mg/l (ATE)				
	0.6 mg/l (rat)				
	1-33-5 1,2- LD50 LD50 30-20-1 2- LD50				

CAS: 55965-84-9 Mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

		` /
Oral	LD50	49.6-75 mg/kg (rat)
Dermal	LD50	87.12 mg/kg (rabbit)
Inhalative	LC50/4 h	0.171 mg/l (rat)

Primary irritant effect:

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Respiratory or skin

sensitisation
May cause an allergic skin reaction.
Based on available data, the classification criteria are not met.
Based on available data, the classification criteria are not met.
Based on available data, the classification criteria are not met.
Based on available data, the classification criteria are not met.
Based on available data, the classification criteria are not met.
Based on available data, the classification criteria are not met.
Based on available data, the classification criteria are not met.
Based on available data, the classification criteria are not met.
Based on available data, the classification criteria are not met.
Based on available data, the classification criteria are not met.

11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

GB



Page 8/11

Safety data sheet according to UK REACH

Printing date 30.03.2025 Version number 27 (replaces version 26) Revision: 30.03.2025

Trade name MC-PowerFlow 5103

(Contd. of page 7)

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

CAS: 2634-33-5 1,2-benzisothiazol-3(2H)-one

EC50/72h | 0.067 mg/l (Pseudokirchneriella subcapitata)

0.11 mg/l (Selenastrum capricornutum)

LC50/96h | 1.6 mg/l (Oncorhynchus mykiss)

EC50/48h | 1.1 mg/l (Daphnia magna)

CAS: 26530-20-1 2-Octyl-2H-isothiazol-3-on

EC50/48h | 0.42 mg/l (Daphnien)

CAS: 55965-84-9 Mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

LC50/24h | 0.19 mg/l (fish)

EC50/72h 0.027 mg/l (Pseudokirchneriella subcapitata)

LC50/96h | 0.19 mg/l (Oncorhynchus mykiss)

LC50/48h | 0.28 mg/l (fish)

EC50/48h 0.16 mg/l (Daphnia magna)

NOEC 0.02 mg/l (Oncorhynchus mykiss)

0.00049 mg/l (Ske)

0.1 mg/l (Daphnia magna)

· 12.2 Persistence and

degradability No further relevant information available.

· 12.3 Bioaccumulative

potential
 12.4 Mobility in soil
 No further relevant information available.
 No further relevant information available.

· 12.5 Results of PBT and vPvB assessment · PBT: Not applicable. · vPvB: Not applicable.

· 12.6 Endocrine disrupting

properties The product does not contain substances with endocrine disrupting

properties.

· 12.7 Other adverse effects

Additional ecological information:

General notes: Do not allow undiluted product or large quantities of it to reach

ground water, water bodies or sewage system.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

• Recommendation Must not be disposed of together with household garbage. Do not

allow product to reach sewage system.

(Contd. on page 9)



Page 9/11

Safety data sheet according to UK REACH

Printing date 30.03.2025 Version number 27 (replaces version 26) Revision: 30.03.2025

Trade name MC-PowerFlow 5103

(Contd. of page 8)

· Uncleaned packagings:

• Recommendation: Disposal must be made according to official regulations.

14.1 UN number or ID number ADR, ADN, IMDG, IATA	Void
14.2 UN proper shipping name ADR, ADN, IMDG, IATA	Void
14.3 Transport hazard class(es)	
ADR, ADN, IMDG, IATA Class	Void
14.4 Packing group ADR, IMDG, IATA	Void
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user	Not applicable.
14.7 Maritime transport in bulk accordir IMO instruments	ng to Not applicable.
Transport/Additional information:	Not dangerous according to the above specifications.
UN "Model Regulation":	Void

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/ legislation specific for the

substance or mixture No further relevant information available.

· Poisons Act

· Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

(Contd. on page 10)



Page 10/11

Safety data sheet according to UK REACH

Printing date 30.03.2025 Version number 27 (replaces version 26) Revision: 30.03.2025

Trade name MC-PowerFlow 5103

(Contd. of page 9)

· 15.2 Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

		,	-
Relevant phrases	H301	Toxic if swallowed.	
•	H302	Harmful if swallowed.	
	H310	Fatal in contact with skin.	

H311

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.

Toxic in contact with skin.

H330 Fatal if inhaled.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

EUH071 Corrosive to the respiratory tract.

Department issuing data specification sheet:

Environment protection department.

· Abbreviations and acronyms: R

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

ATE: Acute toxicity estimate values Acute Tox. 3: Acute toxicity – Category 3 Acute Tox. 4: Acute toxicity – Category 4

Acute Tox. 2: Acute toxicity – Category 2 Skin Corr. 1: Skin corrosion/irritation – Category 1 Skin Corr. 1C: Skin corrosion/irritation – Category 1C Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Skin Sens. 1: Skin sensitisation – Category 1 Skin Sens. 1A: Skin sensitisation – Category 1A

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard -

Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

(Contd. on page 11)



Page 11/11

Safety data sheet according to UK REACH

Printing date 30.03.2025 Version number 27 (replaces version 26) Revision: 30.03.2025

Trade name MC-PowerFlow 5103

(Contd. of page 10)

* * Data compared to the previous version altered.

GB