

Page 1/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 07.07.2023 Version number 24 (replaces version 23) Revision: 07.07.2023

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

· 1.1 Product identifier

· Trade name MC-Quicksolid - Komponente B

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance

/ the mixture

Polyurethane resin Adhesives

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier: MC-Bauchemie Müller GmbH & Co. KG

> Am Kruppwald 1-8 D-46238 Bottrop Tel.: +49(0)2041-101-0 Fax.: +49(0)2041-101-400 E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG Hagackerstr. 10 CH-8953 Dietikon Tel.: +44-7400510 Fax: +44-7400533

Informing department:

msds@mc-bauchemie.de

1.4 Emergency telephone

number: Tel.: +49 / (0)700 24112112 (MCR)

Tel:: +48612864565

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Skin Sens. 1 H317 May cause an allergic skin reaction. Carc. 2 H351 Suspected of causing cancer. STOT SE 3 H335 May cause respiratory irritation.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

· 2.2 Label elements

Labelling according to

Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)



Page 2/11

(Contd. of page 1)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 07.07.2023 Version number 24 (replaces version 23) Revision: 07.07.2023

Trade name MC-Quicksolid - Komponente B

· Hazard pictograms

SHS07 GHS08

· Signal word Danger

Hazard-determining

components of labelling: diphenylmethanediisocyanate,isomeres and homologues

3-Isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate,

oligomers

diphenylmethane-4,4'-di-isocyanante p-toluenesulphonyl isocyanate

· Hazard statements H315 Causes skin irritation.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing

difficulties if inhaled.

H317 May cause an allergic skin reaction. H351 Suspected of causing cancer. H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated

exposure.

• Precautionary statements P260 Do not breathe dust/fume/gas/mist/vapours/

spray.

P280 Wear protective gloves/protective clothing/eye

protection/face protection/hearing protection.

P284 [In case of inadequate ventilation] wear

respiratory protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for

several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P342+P311 If experiencing respiratory symptoms: Call a

POISON CENTER/doctor.

P403+P233 Store in a well-ventilated place. Keep container

tightly closed.

• Additional information: Contains isocyanates. May produce an allergic reaction.

As from 24 August 2023 adequate training is required before

industrial or professional use.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable. · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

• **Description:** Mixture consisting of the following components.

(Contd. on page 3)



Page 3/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 07.07.2023 Version number 24 (replaces version 23) Revision: 07.07.2023

Trade name MC-Quicksolid - Komponente B

Dangerous components:	(C	Contd. of page 2
CAS: 9016-87-9	diphenylmethanediisocyanate,isomeres and homologues Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335, EUH204 Specific concentration limits: Eye Irrit. 2; H319: $C \ge 5$ % Skin Irrit. 2; H315: $C \ge 5$ % Resp. Sens. 1; H334: $C \ge 0.1$ % STOT SE 3; H335: $C \ge 5$ %	50-70%
CAS: 53880-05-0	3-Isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate, oligomers Skin Sens. 1, H317, EUH204	≥1-<10%
CAS: 67762-90-7	Siloxane und Silicone, di-Me, Reaktionsprodukte mit Siliciumdioxid Acute Tox. 4, H302	<5%
CAS: 101-68-8 EINECS: 202-966-0 Reg.nr.: 01-2119457014-47	diphenylmethane-4,4'-di-isocyanante Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335, EUH204 Specific concentration limits: Eye Irrit. 2; H319: $C \ge 5$ % Skin Irrit. 2; H315: $C \ge 5$ % Resp. Sens. 1; H334: $C \ge 0.1$ % STOT SE 3; H335: $C \ge 5$ %	≥1-<2.5%
CAS: 4083-64-1 EINECS: 223-810-8	p-toluenesulphonyl isocyanate Resp. Sens. 1, H334; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335, EUH014, EUH204 Specific concentration limits: Eye Irrit. 2; H319: $C \ge 5$ % STOT SE 3; H335: $C \ge 5$ % Skin Irrit. 2; H315: $C \ge 5$ %	<i>≥</i> 0.1-<0.5%

SECTION 4: First aid measures

· 4.1 Description of first aid measures

• General information Instantly remove any clothing soiled by the product.

Take affected persons into the open air.

Seek medical treatment.

After inhalation
 After skin contact
 After eye contact
 Supply fresh air; consult doctor in case of symptoms.
 Instantly wash with water and soap and rinse thoroughly.
 Rinse opened eye for several minutes under running water.

Call a doctor immediately.

· After swallowing Call a doctor immediately.

(Contd. on page 4)



Page 4/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 07.07.2023 Version number 24 (replaces version 23) Revision: 07.07.2023

Trade name MC-Quicksolid - Komponente B

(Contd. of page 3)

· 4.2 Most important symptoms and effects, both acute and

delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention

and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

· Suitable extinguishing agents Use fire fighting measures that suit the environment.

5.2 Special hazards arising from the substance or

mixture

No further relevant information available.

· 5.3 Advice for firefighters

· Protective equipment: Put on breathing apparatus.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and

emergency procedures

Not required.

6.2 Environmental

precautions:

Prevent material from reaching sewage system, holes and cellars.

· 6.3 Methods and material for

containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders,

universal binders, sawdust).

Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other

sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage

· 7.1 Precautions for safe

handling Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about protection

against explosions and fires: No special measures required.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage

· Requirements to be met by

storerooms and containers: No special requirements.

(Contd. on page 5)



Page 5/11

Safety data sheet according to 1907/2006/EC, Article 31

Revision: 07.07.2023 Printing date 07.07.2023 Version number 24 (replaces version 23)

Trade name MC-Quicksolid - Komponente B

(Contd. of page 4)

· Information about storage in

one common storage facility: Not required.

· Further information about

storage conditions: Keep container tightly sealed.

· Storage class

No further relevant information available. · 7.3 Specific end use(s)

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Components with critical values that require monitoring at the workplace:

9016-87-9 diphenylmethanediisocyanate, isomeres and homologues

WEL Short-term value: 0.07 mg/m³ Long-term value: 0.02 mg/m3

Sen; as -NCO

101-68-8 diphenylmethane-4,4'-di-isocyanante

WEL Short-term value: 0.07 mg/m³

Long-term value: 0.02 mg/m3

Sen; as -NCO

4083-64-1 p-toluenesulphonyl isocyanate

WEL | Short-term value: 0.07 mg/m3

Long-term value: 0.02 mg/m3

Sen; as -NCO

· DNELs

9016-87-9 diphenylmethanediisocyanate, isomeres and homologues

Inhalative DNEL 0.05 mg/m³ (ArL)

101-68-8 diphenylmethane-4,4'-di-isocyanante

DNEL 50 mg/kg bw/day (Ark) Dermal Inhalative DNEL 0.05 mg/m³ (ArL)

PNECs

9016-87-9 diphenylmethanediisocyanate, isomeres and homologues

PNEC 1 mg/l (Sewage Treatment Plant)

0.1 mg/l (Mew)

1 mg/l (Suw)

PNEC 1 mg/kg dwt (Bod)

101-68-8 diphenylmethane-4,4'-di-isocyanante

PNEC 1 mg/l (Sewage Treatment Plant)

0.1 mg/l (Mew) 1 mg/l (Suw)

PNEC 1 mg/kg dwt (Bod)

(Contd. on page 6)



Page 6/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 07.07.2023 Version number 24 (replaces version 23) Revision: 07.07.2023

Trade name MC-Quicksolid - Komponente B

(Contd. of page 5)

· Ingredients with biological limit values:

101-68-8 diphenylmethane-4,4'-di-isocyanante

BMGV 1 µmol creatinine/mol

Medium: urine

Sampling time: At the end of the period od exposure

Parameter: isocyanate-derived diamine

• Additional information: The lists that were valid during the compilation were used as basis.

· 8.2 Exposure controls · Appropriate engineering

controls No further data; see section 7.

· Individual protection measures, such as personal protective equipment

General protective and

hygienic measures Keep away from foodstuffs, beverages and food.

Instantly remove any soiled and impregnated garments. Wash hands during breaks and at the end of the work.

Avoid contact with the eyes and skin.

· Breathing equipment: Respiratory protection is required at inadequately ventilated

workplaces and during spray processing. Fresh air masks or combination filters A2-P2 are recommended for short-term work.

· Hand protection Conditionally suitable materials for protective gloves; EN 374-3:

Nitrile rubber - NBR: Thickness ≥ 0.35mm.

Only suitable for splash protection. Only suitable for short-term exposure. In case of contamination, the protective gloves must be

changed immediately.

Nitrile rubber, NBR

· Material of gloves

· Penetration time of glove

material

The exact break trough time has to be found out by the

manufacturer of the protective gloves and has to be observed.

• Eye/face protection Safety glasses

Tightly sealed safety glasses.

· Body protection: Protective work clothing.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

Colour: Dark brown
 Smell: Characteristic
 Melting point/freezing point: Not determined

· Boiling point or initial boiling point and

boiling range 1 9 0 ° C (9 0 1 6 - 8 7 - 9

diphenylmethanediisocyanate, isomeres and

homologues)

· Flash point: >200 °C · Auto-ignition temperature: 400 °C

· **pH** Not determined.

(Contd. on page 7)



Page 7/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 07.07.2023 Version number 24 (replaces version 23) Revision: 07.07.2023

Trade name MC-Quicksolid - Komponente B

(Contd. of page 6)

· Viscosity:

Kinematic viscositydynamic at 20 °C:Not determined.5200-7800 mPas

·Solubility

· Water: Not miscible or difficult to mix

· Steam pressure at 25 °C: 0 hPa

· Density and/or relative density

Density at 20 °C 1.45 g/cm³

· 9.2 Other information

· Appearance:

Form: Viscous

· Important information on protection of health

and environment, and on safety.

• Self-inflammability: Product is not selfigniting. • Explosive properties: Product is not explosive.

· Information with regard to physical hazard

classes

· Explosives Void · Flammable gases Void Aerosols Void · Oxidising gases Void · Gases under pressure Void · Flammable liquids Void Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void Self-heating substances and mixtures Void · Substances and mixtures, which emit Void flammable gases in contact with water Void

flammable gases in contact with water

· Oxidising liquids

· Oxidising solids

· Organic peroxides

· Corrosive to metals

· Desensitised explosives

Void

SECTION 10: Stability and reactivity

• 10.1 Reactivity No further relevant information available.

10.2 Chemical stability

Thermal decomposition /

conditions to be avoided: No decomposition if used according to specifications.

· 10.3 Possibility of hazardous

reactions Reacts with amines

• 10.4 Conditions to avoid No further relevant information available. • 10.5 Incompatible materials: No further relevant information available.

(Contd. on page 8)



Page 8/11

Safety data sheet according to 1907/2006/EC, Article 31

Revision: 07.07.2023 Printing date 07.07.2023 Version number 24 (replaces version 23)

Trade name MC-Quicksolid - Komponente B

(Contd. of page 7)

· 10.6 Hazardous

decomposition products: No dangerous decomposition products known

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

· Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50	values tha	t are relevant for classification:	
9016-87-9	diphenyl	methanediisocyanate,isomeres and homologues	
Oral	LD50	>10000 mg/kg (Rat)	
Dermal	LD50	>5000 mg/kg (Rab)	
Inhalative	LC50/4 h	~450 mg/l (Rat)	
67762-90-	67762-90-7 Siloxane und Silicone, di-Me, Reaktionsprodukte mit		
	Silicium	ndioxid	
Oral	LD50	>5000 mg/kg (rat)	
Dermal	LD50	>2000 mg/kg (rabbit)	
101-68-8	diphenylm	nethane-4,4'-di-isocyanante	
Oral	LD50	>10000 mg/kg (rat)	
Dermal	LD50	>9400 mg/kg (rabbit)	
4083-64-1 p-toluenesulphonyl isocyanate			
Oral	LD50	2600 mg/kg (rat)	
01:	:/::4	ction Coupon okin irritation	

Causes skin irritation. · Skin corrosion/irritation · Serious eye damage/irritation Causes serious eye irritation.

· Respiratory or skin

sensitisation May cause allergy or asthma symptoms or breathing difficulties if

inhaled.

May cause an allergic skin reaction.

· Germ cell mutagenicity Based on available data, the classification criteria are not met.

· Carcinogenicity Suspected of causing cancer.

· Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure May cause respiratory irritation.

May cause damage to organs through prolonged or repeated STOT-repeated exposure

exposure.

· Aspiration hazard Based on available data, the classification criteria are not met.

11.2 Information on other hazards

· Endocrine disrupting properties				
541-02-6	2,2,4,4,6,6,8,8,10,10-decamethylcyclopentasiloxane	List II		
556-67-2	octamethylcyclotetrasiloxane	List II; III		



Page 9/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 07.07.2023 Version number 24 (replaces version 23) Revision: 07.07.2023

Trade name MC-Quicksolid - Komponente B

(Contd. of page 8)

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

67762-90-7 Siloxane und Silicone, di-Me, Reaktionsprodukte mit

Siliciumdioxid

Sensitisation EL50 10000 mg/l (Daphnien)

LC50/96h >10000 mg/l (Brachydanio rerio)

101-68-8 diphenylmethane-4,4'-di-isocyanante

EC50/24h >1000 mg/l (Daphnia magna) LC50/96h >1000 mg/l (Brachydanio rerio) NOEC >1000 mg/l (Eisenia foetida)

>10 mg/l (Daphnia magna)

· 12.2 Persistence and

degradability No further relevant information available.

· 12.3 Bioaccumulative

potential
No further relevant information available.

12.4 Mobility in soil
No further relevant information available.

• 12.5 Results of PBT and vPvB assessment
• PBT:
• vPvB:
Not applicable.
Not applicable.

· 12.6 Endocrine disrupting

properties For information on endocrine disrupting properties see section 11.

· 12.7 Other adverse effects

· Additional ecological information:

General notes: Do not allow undiluted product or large quantities of it to reach

ground water, water bodies or sewage system.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

• Recommendation Must not be disposed of together with household garbage. Do not

allow product to reach sewage system.

· Uncleaned packagings:

Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN number or ID number

· ADR, ADN, IMDG, IATA Void

· 14.2 UN proper shipping name

· ADR, ADN, IMDG, IATA Void

(Contd. on page 10)



Page 10/11

Safety data sheet according to 1907/2006/EC, Article 31

Revision: 07.07.2023 Printing date 07.07.2023 Version number 24 (replaces version 23)

Trade name MC-Quicksolid - Komponente B

		(Contd. of page
14.3 Transport hazard class(es)		
ADR, ADN, IMDG, IATA		
Class	Void	
14.4 Packing group		
ADR, IMDG, IATA	Void	
14.5 Environmental hazards:		
Marine pollutant:	No	
14.6 Special precautions for user	Not applicable.	
14.7 Maritime transport in bulk accord	ing to	
IMO instruments	Not applicable.	
UN "Model Regulation":	Void	

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/ legislation specific for the substance or mixture

· 15.2 Chemical safety

assessment:

No further relevant information available.

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases	H302	Harmful if swallowed.
-	H315	Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

H332 Harmful if inhaled.

May cause allergy or asthma symptoms or breathing H334

difficulties if inhaled.

H335 May cause respiratory irritation. H351 Suspected of causing cancer.

May cause damage to organs through prolonged or H373

repeated exposure.

EUH014 Reacts violently with water.

EUH204 Contains isocyanates. May produce an allergic reaction.

· Department issuing data

specification sheet: Environment protection department.

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises

dangereuses par chemin de fer (Regulations Concerning the International

Transport of Dangerous Goods by Rail)

(Contd. on page 11)



Page 11/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 07.07.2023

Version number 24 (replaces version 23)

(Contd. of page 10)

Revision: 07.07.2023

Trade name MC-Quicksolid - Komponente B

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (ÚK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Resp. Sens. 1: Respiratory sensitisation - Category 1

Skin Sens. 1: Skin sensitisation - Category 1

Carc. 2: Carcinogenicity - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

* * Data compared to the previous version altered.

- GF