



BE SURE. BUILD SURE.

Page 1/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.11.2018

Revision: 06.11.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name Mycoflex 4100 TS - Komponente A

Article number: 966

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture

Primer/ Subcoating

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: MC-Bauchemie Müller GmbH & Co. KG
Am Kruppwald 1-8
D-46238 Bottrop
Tel.: +49(0)2041-101-0
Fax.: +49(0)2041-101-400
E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG
Hagackerstr. 10
CH-8953 Dietikon
Tel.: +44-7400510
Fax : +44-7400533

Informing department: Technische Abteilung
msds@mc-bauchemie.de

1.4 Emergency telephone number:

Tel.: +49 / (0)700 24112112 (MCR)
Tel.: +48612864565

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3	H226	Flammable liquid and vapour.
Skin Irrit. 2	H315	Causes skin irritation.
Eye Irrit. 2	H319	Causes serious eye irritation.
Skin Sens. 1	H317	May cause an allergic skin reaction.
STOT SE 3	H335-H336	May cause respiratory irritation. May cause drowsiness or dizziness.
STOT RE 2	H373	May cause damage to organs through prolonged or repeated exposure.
Asp. Tox. 1	H304	May be fatal if swallowed and enters airways.
Aquatic Chronic 3	H412	Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to

Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)



BE SURE. BUILD SURE.

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.11.2018

Revision: 06.11.2018

Trade name Mycoflex 4100 TS - Komponente A

(Contd. of page 1)

Hazard pictograms



GHS02 GHS07 GHS08

Signal word

Danger

Hazard-determining components of labelling:

xylene
Propyl -2,2-diphenyl-4,4'dipropylloxirane polymers and homologues
1-methoxypropan-2-ol

Hazard statements

H226 Flammable liquid and vapour.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.
H373 May cause damage to organs through prolonged or repeated exposure.
H304 May be fatal if swallowed and enters airways.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P321 Specific treatment (see on this label).
P331 Do NOT induce vomiting.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P362+P364 Take off contaminated clothing and wash it before reuse.

Additional information:

Contains epoxy constituents. May produce an allergic reaction.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Chemical characterisation: Mixtures

Description: Mixture consisting of the following components.

Dangerous components:

CAS: 1330-20-7 EINECS: 215-535-7	xylene STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	25-50%
-------------------------------------	--	--------

(Contd. on page 3)



BE SURE. BUILD SURE.

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 06.11.2018

Revision: 06.11.2018

Trade name Mycoflex 4100 TS - Komponente A

(Contd. of page 2)

CAS: 107-98-2 EINECS: 203-539-1 Reg.nr.: 01-2119457435-35-xxxx	1-methoxypropan-2-ol Flam. Liq. 3, H226; STOT SE 3, H336	25-50%
CAS: 25068-38-6 NLP: 500-033-5 Reg.nr.: 01-2119456619-26-0002	Propyl -2,2-diphenyl-4,4'dipropyloxirane polymers and homologues Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	≥5-<25%
CAS: 2530-83-8 EINECS: 219-784-2	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	<1.5%

· **Additional information** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· **4.1 Description of first aid measures**

- **General information** Instantly remove any clothing soiled by the product.
Take affected persons into the open air.
- **After inhalation** Supply fresh air and call for doctor for safety reasons.
- **After skin contact** Instantly wash with water and soap and rinse thoroughly.
- **After eye contact** Rinse opened eye for several minutes under running water.
Seek medical treatment.
- **After swallowing** Do not induce vomiting; instantly call for medical help.

· **4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

· **4.3 Indication of any immediate medical attention**

and special treatment needed If swallowed or in case of vomiting, danger of entering the lungs

SECTION 5: Firefighting measures

· **5.1 Extinguishing media**

· **Suitable extinguishing agents** CO₂, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.

· **For safety reasons unsuitable extinguishing agents**

Water with a full water jet.

· **5.2 Special hazards arising from the substance or mixture**

No further relevant information available.

· **5.3 Advice for firefighters**

· **Protective equipment:**

Put on breathing apparatus.

GB

(Contd. on page 4)



BE SURE. BUILD SURE.

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.11.2018

Revision: 06.11.2018

Trade name Mycoflex 4100 TS - Komponente A

(Contd. of page 3)

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** *Wear protective equipment. Keep unprotected persons away.*
- **6.2 Environmental precautions:** *Prevent material from reaching sewage system, holes and cellars.*
- **6.3 Methods and material for containment and cleaning up:** *Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose of contaminated material as waste according to item 13.
Ensure adequate ventilation.*
- **6.4 Reference to other sections** *See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.
See Section 13 for information on disposal.*

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** *Store in cool, dry place in tightly closed containers.
Open and handle container with care.*
- **Information about protection against explosions and fires:** *Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.*
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and containers:** *No special requirements.*
- **Information about storage in one common storage facility:** *Not required.*
- **Further information about storage conditions:** *Keep container tightly sealed.*
- **7.3 Specific end use(s)** *No further relevant information available.*

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical systems:** *No further data; see item 7.*

8.1 Control parameters

· **Components with critical values that require monitoring at the workplace:**

107-98-2 1-methoxypropan-2-ol

WEL	Short-term value: 560 mg/m ³ , 150 ppm Long-term value: 375 mg/m ³ , 100 ppm
Sk	

(Contd. on page 5)



BE SURE. BUILD SURE.

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.11.2018

Revision: 06.11.2018

Trade name Mycoflex 4100 TS - Komponente A

(Contd. of page 4)

· DNELs

25068-38-6 Propyl -2,2-diphenyl-4,4'dipropyloxirane polymers and homologues

Oral	DNEL	0.75 mg/kg bw/Tag (General) (Kurzfristig und Langfristig Systemisch)
Dermal	DNEL	3.6 mg/kg bw/day (General) (Kurzfristig und Langfristig Systemisch)
		8.3 mg/kg bw/day (Workers) (Kurzfristig und Langfristig Systemisch)
Inhalative	DNEL	0.75 mg/m ³ (General) (Kurzfristig und Langfristig Systemisch)
		12.3 mg/m ³ (Workers) (Kurzfristig und Langfristig Systemisch)

· PNECs

25068-38-6 Propyl -2,2-diphenyl-4,4'dipropyloxirane polymers and homologues

PNEC	3 µg/l (Fresh water)
	0.3 µg/l (Marine)
PNEC	10 mg/l (Sewage Treatment Plant)
PNEC	0.5 mg/kg dwt (Marine water sediment)
	0.05 mg/kg dwt (Sediment)
	0.5 mg/kg dwt (Fresh water sediment)

· Additional information: The lists that were valid during the compilation were used as basis.

· 8.2 Exposure controls

· Personal protective equipment

· General protective and hygienic measures

Keep away from foodstuffs, beverages and food.
Instantly remove any soiled and impregnated garments.
Wash hands during breaks and at the end of the work.
Avoid contact with the eyes and skin.

· Protection of hands:

Protective gloves.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
After use of gloves apply skin-cleaning agents and skin cosmetics.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:

Safety glasses
Tightly sealed safety glasses.

· Body protection:

Protective work clothing.

GB

(Contd. on page 6)



BE SURE. BUILD SURE.

Page 6/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.11.2018

Revision: 06.11.2018

Trade name Mycoflex 4100 TS - Komponente A

(Contd. of page 5)

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

· Form:	Fluid
· Colour:	Yellow
· Smell:	Characteristic

· Change in condition

· Melting point/freezing point:	Not determined
· Initial boiling point and boiling range:	120 °C

· Flash point:	30 °C
----------------	-------

· Ignition temperature:	184 °C
-------------------------	--------

· Self-inflammability:	Product is not selfigniting.
------------------------	------------------------------

· Explosive properties:	Product is not explosive. However, formation of explosive air/steam mixtures is possible.
-------------------------	---

· Critical values for explosion:

· Lower:	1.1 Vol %
· Upper:	13.7 Vol %

· Steam pressure at 20 °C:	13 hPa
----------------------------	--------

· Density at 20 °C	0.95 g/cm ³
--------------------	------------------------

· Solubility in / Miscibility with

· Water:	Not miscible or difficult to mix
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

· 10.1 Reactivity	No further relevant information available.
-------------------	--

· 10.2 Chemical stability

· Thermal decomposition /

· conditions to be avoided:	No decomposition if used according to specifications.
-----------------------------	---

· 10.3 Possibility of hazardous reactions

No dangerous reactions known

· 10.4 Conditions to avoid

No further relevant information available.

· 10.5 Incompatible materials:

No further relevant information available.

· 10.6 Hazardous

decomposition products: No dangerous decomposition products known

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

· Acute toxicity	Based on available data, the classification criteria are not met.
------------------	---

(Contd. on page 7)



BE SURE. BUILD SURE.

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.11.2018

Revision: 06.11.2018

Trade name Mycoflex 4100 TS - Komponente A

(Contd. of page 6)

· **LD/LC50 values that are relevant for classification:**

25068-38-6 Propyl -2,2-diphenyl-4,4'dipropoxyirane polymers and homologues

Oral LD50 30,000 mg/kg (Ratte)

Dermal LD50 >2,000 mg/kg (kan)

· **Primary irritant effect:**

· **Skin corrosion/irritation** Causes skin irritation.

· **Serious eye damage/irritation** Causes serious eye irritation.

· **Respiratory or skin**

sensitisation

May cause an allergic skin reaction.

· **CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)**

· **Germ cell mutagenicity**

Based on available data, the classification criteria are not met.

· **Carcinogenicity**

Based on available data, the classification criteria are not met.

· **Reproductive toxicity**

Based on available data, the classification criteria are not met.

· **STOT-single exposure**

May cause respiratory irritation. May cause drowsiness or dizziness.

· **STOT-repeated exposure**

May cause damage to organs through prolonged or repeated exposure.

· **Aspiration hazard**

May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

· **12.1 Toxicity**

· **Aquatic toxicity:**

No further relevant information available.

· **12.2 Persistence and**

degradability

No further relevant information available.

· **12.3 Bioaccumulative**

potential

No further relevant information available.

· **12.4 Mobility in soil**

No further relevant information available.

· **Additional ecological information:**

· **General notes:**

Do not allow product to reach ground water, water bodies or sewage system.

Danger to drinking water if even small quantities leak into soil.

· **12.5 Results of PBT and vPvB assessment**

· **PBT:**

Not applicable.

· **vPvB:**

Not applicable.

· **12.6 Other adverse effects**

No further relevant information available.

SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**

· **Recommendation**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· **European waste catalogue**

08 00 00

WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS

(Contd. on page 8)



BE SURE. BUILD SURE.

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.11.2018

Revision: 06.11.2018

Trade name Mycoflex 4100 TS - Komponente A

(Contd. of page 7)

08 01 00	wastes from MFSU and removal of paint and varnish
08 01 11	waste paint and varnish containing organic solvents or other dangerous substances

· **Uncleaned packagings:**

· **Recommendation:**

Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.

SECTION 14: Transport information

· 14.1 UN-Number · ADR, IMDG, IATA	UN1866
· 14.2 UN proper shipping name · ADR · IMDG, IATA	1866 RESIN SOLUTION RESIN SOLUTION
· 14.3 Transport hazard class(es) · ADR · Class · Label	3 (F1) Flammable liquids. 3
· IMDG, IATA · Class · Label	3 Flammable liquids. 3
· 14.4 Packing group · ADR, IMDG, IATA	III
· 14.5 Environmental hazards: · Marine pollutant:	No
· 14.6 Special precautions for user · Kemler Number: · EMS Number: · Stowage Category	Warning: Flammable liquids. 30 F-E, S-E A
· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information: · ADR · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· Transport category · Tunnel restriction code · Remarks:	3 D/E Beförderung nach RN 2301a

(Contd. on page 9)



BE SURE. BUILD SURE.

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.11.2018

Revision: 06.11.2018

Trade name Mycoflex 4100 TS - Komponente A

(Contd. of page 8)

· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1866 RESIN SOLUTION, 3, III

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5.000 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50.000 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
 - H226 Flammable liquid and vapour.
 - H304 May be fatal if swallowed and enters airways.
 - H312 Harmful in contact with skin.
 - H315 Causes skin irritation.
 - H317 May cause an allergic skin reaction.
 - H319 Causes serious eye irritation.
 - H332 Harmful if inhaled.
 - H335 May cause respiratory irritation.
 - H336 May cause drowsiness or dizziness.
 - H373 May cause damage to organs through prolonged or repeated exposure.
 - H411 Toxic to aquatic life with long lasting effects.
- **Department issuing data specification sheet:** Environment protection department.
- **Abbreviations and acronyms:** RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

(Contd. on page 10)



BE SURE. BUILD SURE.

Page 10/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.11.2018

Revision: 06.11.2018

Trade name Mycoflex 4100 TS - Komponente A

(Contd. of page 9)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods
by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic
hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic
hazard – Category 3

*** Data compared to the
previous version altered.**

GB