

Page 1/11

# Safety data sheet according to UK REACH

Printing date 29.03.2025 Version number 27 (replaces version 26) Revision: 29.03.2025

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

• Trade name Mycoflex Resyst Adhesive - Komponente A

· Article number: 3366

· 1.2 Relevant identified uses of the substance or mixture

and uses advised against No further relevant information available.

· Application of the substance

/ the mixture Epoxy impregnation

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: MC-Bauchemie Müller GmbH & Co. KG

Am Kruppwald 1-8 D-46238 Bottrop Tel.: +49(0)2041-101-0 Fax.: +49(0)2041-101-400 E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG Hagackerstr. 10 CH-8953 Dietikon Tel.: +44-7400510 Fax: +44-7400533

Informing department:

1.4 Emergency telephone

number:

Tel.: +49 / (0)700 24112112 (MCR)

Tel.: +1 872 5888271 (MCR)

msds@mc-bauchemie.de

### **SECTION 2: Hazards identification**

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

· 2.2 Label elements

Labelling according to

Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP

regulation.

· Hazard pictograms





GHS07 GHS09

· Signal word

Warning

(Contd. on page 2)



Page 2/11

# Safety data sheet according to UK REACH

Printing date 29.03.2025 Version number 27 (replaces version 26) Revision: 29.03.2025

#### Trade name Mycoflex Resyst Adhesive - Komponente A

(Contd. of page 1)

· Hazard-determining

components of labelling: Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]

bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)] bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}

methyl)oxirane

4.4'-Methylenediphenyldiglycidyl ether

Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane

(1:2)

· **Hazard statements** H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

• Precautionary statements P261 Avoid breathing dust/fume/gas/mist/vapours/

sprav.

P273 Avoid release to the environment.

P280 Wear protective gloves / eye protection / face

protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for

several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P332+P313 If skin irritation occurs: Get medical advice/

attention.

P333+P313 If skin irritation or rash occurs: Get medical

advice/attention.

· Additional information: EUH205 Contains epoxy constituents. May produce an allergic

reaction.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

## SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

Description: Mixture consisting of the following components.

· Dangerous components:

CAS: 9003-36-5 Reaction mass of 2,2'-[methylenebis(2,1-

phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane

Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Skin Sens. 1, H317

(Contd. on page 3)

80-100%



Page 3/11

## Safety data sheet according to UK REACH

Revision: 29.03.2025 Printing date 29.03.2025 Version number 27 (replaces version 26)

#### Trade name Mycoflex Resyst Adhesive - Komponente A

	(C	ontd. of page 2)
CAS: 1675-54-3	4,4'-Methylenediphenyldiglycidyl ether	≥2.5-<10%
	Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	
CAS: 933999-84-9	Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2)	≥2.5-<5%
	Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; Aquatic Chronic 3, H412	

· Additional information For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information Remove contaminated clothing immediately. Consult a doctor if

symptoms occur. Move affected person to fresh air.

· After inhalation Supply fresh air; seek medical advice if symptoms occur.

If unconscious, place in recovery position and seek medical advice.

· After skin contact In case of contact with skin, wash carefully with plenty of soap and

water. Consult a doctor in case of skin reactions.

· After eye contact Rinse opened eye for several minutes under running water.

Call a doctor immediately

Rinse mouth with water. Never give anything by mouth to an · After swallowing

unconscious person. DO NOT induce vomiting. If symptoms

persist, consult a doctor.

· 4.2 Most important symptoms and effects, both acute and

delayed Advice for the doctor: Elementary aid, decontamination,

symptomatic treatment.

## SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· Suitable extinguishing agents CO2, extinguishing powder or water jet. Fight larger fires with

water jet or alcohol-resistant foam.

5.2 Special hazards arising from the substance or

mixture

No further relevant information available.

5.3 Advice for firefighters

· Protective equipment: No special measures required.

#### SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and

emergency procedures Not required.

(Contd. on page 4)



Page 4/11

# Safety data sheet according to UK REACH

Printing date 29.03.2025 Version number 27 (replaces version 26) Revision: 29.03.2025

### Trade name Mycoflex Resyst Adhesive - Komponente A

(Contd. of page 3)

6.2 Environmental

precautions: Inform respective authorities in case product reaches water or

sewage system.

· 6.3 Methods and material for

containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders,

universal binders, sawdust).

· 6.4 Reference to other

sections See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

### SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Open and handle containers with care.

Ventilation measures are required in rooms without sufficient air

exchange (e.g. closed rooms),

because the occupational exposure limit values (see chapter 8)

could be exceeded. This must be avoided.

Wear suitable personal protective equipment (see section 8). Avoid contact with eyes, skin and clothing. Change contaminated or damaged gloves and contaminated clothing immediately and wash skin immediately. Mix slowly, partially covering the mixing container. Pour carefully and slowly when repotting. Observe the BGBau technical data sheet and practical guide for handling epoxy

resins.

Information about protection

against explosions and fires: Ensure sufficient air exchange and/or extraction in the working

areas. Take precautionary measures to avoid electrostatic

discharges.

· 7.2 Conditions for safe storage, including any incompatibilities

Storage

· Requirements to be met by

storerooms and containers: No special requirements.

· Further information about

storage conditions: None. Storage class 10

### SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Components with critical

values that require

monitoring at the workplace: The product does not contain any relevant quantities of materials

with critical values that have to be monitored at the workplace.

· Additional information: The lists that were valid during the compilation were used as basis.

(Contd. on page 5)



Page 5/11

# Safety data sheet according to UK REACH

Printing date 29.03.2025 Version number 27 (replaces version 26) Revision: 29.03.2025

#### Trade name Mycoflex Resyst Adhesive - Komponente A

(Contd. of page 4)

· 8.2 Exposure controls · Appropriate engineering

controls No further data; see section 7.

· Individual protection measures, such as personal protective equipment

· General protective and

hygienic measures Keep away from food, drink and animal feed.

Remove soiled, soaked clothing immediately.

Wash hands before breaks and at the end of work.

Avoid contact with eyes and skin.

Breathing equipment: If workplace limit values cannot be complied with by ventilation

measures or if rooms cannot be technically ventilated, respiratory protection must be worn: Use combination filter A1-P2 (brown/white) in rooms that cannot be ventilated. If oxygen deficiency is expected, use self-contained breathing apparatus. Observe wearing time limits according to §9 (3) GefStoffV in conjunction

with BGR 190.

· Hand protection Selection of the glove material on consideration of the penetration

times, rates of diffusion and the degradation

• Material of gloves You can find help with choosing gloves on the website https://

www.bgbau.de/fileadmin/Gisbau/Projekte.pdf

For example, we recommend the Sol-vex 37-900 protective gloves from Ansell GmbH. The breakthrough time of the protective gloves can be found under point 8 "Penetration time of the glove material". The selection of a suitable glove depends not only on the material, but also on other quality features and varies from manufacturer to

manufacturer. As the product

is a preparation of several substances, the resistance of glove materials cannot be calculated in advance and must therefore be checked before use.

Nitrile rubber

Recommended material thickness:≥ 0.4 mm

· Penetration time of glove material

The breakthrough times of the Sol-vex 37-900 protective gloves

are around 8 hours.

The following applies to all other gloves:

The exact breakthrough time must be obtained from the protective

glove manufacturer and adhered to.

Nitrile rubber

Material thickness: ≥ 0.40 mm Penetration time: ≥ 480 min

Butyl rubber:

Material thickness: ≥ 0.5 mm Penetration time: ≥ 480 min Tight-fitting safety goggles.

Eye/face protection Tight-fitting safety safety goggles.
 Body protection: Protective clothing

Suitable protective clothing should be worn when working with epoxy resins. In addition to normal work clothing (long trousers, long-sleeved shirt or T-shirt), disposable overalls, aprons, overshoes, sleeve protectors etc. may be necessary depending on

(Contd. on page 6)



Page 6/11

## Safety data sheet according to UK REACH

Version number 27 (replaces version 26) Revision: 29.03.2025 Printing date 29.03.2025

Trade name Mycoflex Resyst Adhesive - Komponente A

(Contd. of page 5)

the activity. Uncovered areas of skin should be avoided as far as possible, even in hot weather. If the work involves kneeling, the lower leg area should be protected by protective trousers.

### SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Colour: According to product specification

· Smell: Characteristic Not determined

Melting point/freezing point:

Boiling point or initial boiling point and

boiling range >200 °C (CAS: 9003-36-5 Reaction mass of 2,2'-

[methylenebis(2,1-phenyleneoxymethylene)] bis(oxirane) and 2,2'-[methylenebis(4,1phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)

oxirane)

· Flash point: 151 °C

Auto-ignition temperature: 460 °C (CAS: 9003-36-5 Reaction mass of 2,2'-

[methylenebis(2,1-phenyleneoxymethylene)] bis(oxirane) and 2,2'-[methylenebis(4,1phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)

oxirane)

· pH Not determined.

· Viscosity:

· Kinematic viscosity Not determined. · dynamic at 20 °C: 1350 mPas

Solubility

· Water: Not miscible or difficult to mix

· Steam pressure: Not determined.

· Density and/or relative density

· Density at 20 °C 1.37 g/cm<sup>3</sup>

· 9.2 Other information

· Appearance:

Fluid

· Important information on protection of health

and environment, and on safety.

· Self-inflammability: Product is not selfigniting. · Explosive properties: Product is not explosive.

· Information with regard to physical hazard

classes

· Explosives Void · Flammable gases Void · Aerosols Void

(Contd. on page 7)



Page 7/11

# Safety data sheet according to UK REACH

Printing date 29.03.2025 Version number 27 (replaces version 26) Revision: 29.03.2025

#### Trade name Mycoflex Resyst Adhesive - Komponente A

(Contd. of page 6)

· Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit	
flammable gases in contact with water	Void
· Oxidising liquids	Void
Oxidising solids	Void
· Organic peroxides	Void
Corrosive to metals	Void
· Desensitised explosives	Void

### SECTION 10: Stability and reactivity

• 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability · Thermal decomposition /

conditions to be avoided: No decomposition if used according to specifications.

· 10.3 Possibility of hazardous

reactions No dangerous reactions known

10.4 Conditions to avoid
 10.5 Incompatible materials:
 No further relevant information available.

· 10.6 Hazardous

decomposition products: No dangerous decomposition products known

### **SECTION 11: Toxicological information**

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

· Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values that are relevant for classification:

CAS: 9003-36-5 Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]
bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]
bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)
oxirane

Oral LD50 >2000 mg/kg (rat)

Dermal LD50 >2000 mg/kg (rabbit)

CAS: 1675-54-3 4,4'-Methylenediphenyldiglycidyl ether

 Oral
 LD50
 11400 mg/kg (rat)

 Dermal
 LD50
 23000 mg/kg (rabbit)

 >2000 mg/kg (rat)
 >2000 mg/kg (rat)

(Contd. on page 8)



Page 8/11

# Safety data sheet according to UK REACH

Printing date 29.03.2025 Version number 27 (replaces version 26) Revision: 29.03.2025

#### Trade name Mycoflex Resyst Adhesive - Komponente A

(Contd. of page 7)

· Primary irritant effect:

Skin corrosion/irritation
 Serious eye damage/irritation
 Causes skin irritation.
 Causes serious eye irritation.

· Respiratory or skin

**sensitisation** May cause an allergic skin reaction.

Germ cell mutagenicity
 Carcinogenicity
 Reproductive toxicity
 STOT-single exposure
 STOT-repeated exposure
 Aspiration hazard
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.

· 11.2 Information on other hazards

· Endocrine disrupting properties

CAS: 128-37-0 | 2,6-Di-tert-butyl-p-cresol | List II

### **SECTION 12: Ecological information**

· 12.1 Toxicity

· Aquatic toxicity:

CAS: 9003-36-5 Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]
bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]
bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)
oxirane

LC50/96h >100 mg/l (Daphnia magna) EC50/96h >100 mg/l (Leucidus idus)

CAS: 1675-54-3 4,4'-Methylenediphenyldiglycidyl ether

LC50/72h >11 mg/l (algae) IC50 >42.6 mg/l (Bak)

LC50/96h 2 mg/l (Oncorhynchus mykiss)

1.3 mg/l (fish)

EC50/48h | 2.1 mg/l (daphnia)

1.8 mg/l (Daphnia magna)

ErC50/72h 11 mg/l (Selenastrum capricornutum)

· 12.2 Persistence and

degradability No further relevant information available.

· 12.3 Bioaccumulative

potential
No further relevant information available.

12.4 Mobility in soil
No further relevant information available.

12.5 Results of PBT and vPvB assessment
 PBT: Not applicable.
 vPvB: Not applicable.

· 12.6 Endocrine disrupting

**properties** For information on endocrine disrupting properties see section 11.

(Contd. on page 9)



Page 9/11

# Safety data sheet according to UK REACH

Printing date 29.03.2025 Version number 27 (replaces version 26) Revision: 29.03.2025

#### Trade name Mycoflex Resyst Adhesive - Komponente A

(Contd. of page 8)

· 12.7 Other adverse effects

· Additional ecological information:

• General notes: Do not allow product to reach ground water, water bodies or

sewage system.

Danger to drinking water if even small quantities leak into soil.

## **SECTION 13: Disposal considerations**

· 13.1 Waste treatment methods

· Recommendation Must not be disposed of together with household garbage. Do not

allow product to reach sewage system.

· Uncleaned packagings:

• Recommendation: Non contaminated packagings can be used for recycling.

14.1 UN number or ID number	
ADR, IMDG, IATA	UN3082
14.2 UN proper shipping name	
ADR, IATA	ENVIRONMENTALLY HAZARDOU
IMDC	SUBSTANCE, LIQUID, N.O.S. (Epoxide resin) ENVIRONMENTALLY HAZARDOU
IMDG	SUBSTANCE, LIQUID, N.O.S. (Epoxide resin
	MARINE POLLUTANT
14.3 Transport hazard class(es)	
ADR	
Class	<ol> <li>9 (M6) Miscellaneous dangerous substances an articles.</li> </ol>
Label	9
· IMDG, IATA	
Class	9 Miscellaneous dangerous substances ar
	articles.
Label	9
· 14.4 Packing group	
ADR, IMDG, IATA	III
14.5 Environmental hazards:	
Marine pollutant:	Yes
	Symbol (fish and tree)
Special marking (ADR):	Symbol (fish and tree)
Special marking (IATA):	Symbol (fish and tree)
14.6 Special precautions for user	Warning: Miscellaneous dangerous substances ar articles.



Page 10/11

# Safety data sheet according to UK REACH

Printing date 29.03.2025 Version number 27 (replaces version 26) Revision: 29.03.2025

### Trade name Mycoflex Resyst Adhesive - Komponente A

	(Contd. of page
Kemler Number:	90
EMS Number:	F-A,S-F
Stowage Category	Α
14.7 Maritime transport in bulk accord	ling to
IMO instruments	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities (ÉQ)	Code: E1
,	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 100
	ml
Transport category	3
Tunnel restriction code	(-)
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (ÉQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 100
	ml
UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOU
	SUBSTANCE, LIQUID, N.O.S. (EPOXIDE RESIN
	9, III

## **SECTION 15: Regulatory information**

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Poisons Act
- · Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

- · Directive 2012/18/EU
- · Qualifying quantity (tonnes) for the application of lower-

tier requirements 200 t

(Contd. on page 11)



Page 11/11

# Safety data sheet according to UK REACH

Printing date 29.03.2025 Version number 27 (replaces version 26) Revision: 29.03.2025

#### Trade name Mycoflex Resyst Adhesive - Komponente A

(Contd. of page 10)

Qualifying quantity (tonnes) for the application of uppertier requirements

· 15.2 Chemical safety

assessment:

500 t

A Chemical Safety Assessment has not been carried out.

### **SECTION 16: Other information**

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.

Department issuing data

**specification sheet:** Environment protection department.

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises

dangereuses par chemin de fer (Regulations Concerning the International

Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous

Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Skin Sens. 1: Skin sensitisation - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic

hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic

hazard – Category 3

\* Data compared to the previous version altered.