



Donnitol BGR 81

Cleaning agent for construction equipment

Product Properties

- Ready to use
- Short reaction time
- Dilutable up to 1:12 with water
- Metal is not attacked during cleaning

Areas of Application

Cleaning of

- construction machines
- construction equipment

Remove

- hydraulic residues
- lime
- any other soiling

Application Notes

Preparation

Depending on the degree of soiling Donnitol BGR 81 can be applied as concentrate or diluted with water at a mixing ratio of 1:12.

Application

Apply Donnitol BGR 81 by spraying or with a hard brush. Allow it to take effect for a while. For stubborn soiling apply Donnitol BGR 81 more than once.

A fine-pored foam results shortly after application of Donnitol BGR 81.

The treated area must be thoroughly washed with water after each cleaning process, to remove unused residues of Donnitol BGR 81.

Further Information

Contact with eyes must be avoided. Use protective goggles and gloves! Immediately wash any splashes from skin with clear water.

Causes burns! Please refer to the safety data sheet.



Technical Data for Donnitol BGR 81

Characteristic	Unit	Value	Comments
Density	kg/dm ³	1.20	

Product Characteristics for Donnitol BGR 81

Colour	red
Consistency	liquid
Storage	Can be stored in closed packs under frost free and dry conditions.
Form of Delivery	30 kg canister 200 kg barrel 1000 kg container
Disposal	To protect our environment please empty the packs completely!

Property specifications are based on laboratory tests and may vary in practical application. To determine the individual technical suitability, preliminary suitability tests should be carried out under the application conditions.

Note: The information on this data sheet is based on our experiences and correct to the best of our knowledge. It is, however, not binding. It has to be adjusted to the individual structure, application purpose and especially to local conditions. Our data refers to the accepted engineering rules, which have to be observed during application. This provided we are liable for the correctness of this data within the scope of our terms and conditions of sale-delivery-and-service. Recommendations of our employees which differ from the data contained in our information sheets are only binding if given in written form. The accepted engineering rules must be observed at all times.

Edition 11/13. Some technical changes have been made to this print medium. Older editions are invalid and may not be used anymore. If a technically revised new edition is issued, this edition becomes invalid.