

PRODUCT PROPERTIES

- Highly tear-proof
- Water tight
- Quick and easy installation
- Excellent ageing stability
- High chemical resistance
- Applicable in damp locations, such as balconies, terraces and wet rooms
- Component of the Expert Proof and Nafuflex waterproofing systems

AREAS OF APPLICATION

- Sealing of coving areas
- Sealing of connecting joints
- Sealing of internal and external corners

APPLICATION ADVICE

Substrate preparation: Loose particles, old coatings, demoulding agents, grease etc. have to be removed. The substrate must be frost-free, clean and dry.

Application: MC-FastTape is embedded into the first waterproofing layer. Afterwards the second layer is applied. For the application in coving areas we recommend the application with Expert Proof eco. Connections can be made by using Mycoflex 488 MS or Expert Proof eco. Both sides should overlap at least 100 mm.

Further information: MC-FastTape is certified as a system in connection with Expert Proof, Expert Proof eco and Expert Proof one.

For further application details see our MC-FastTape Fyler.

TECHNICAL VALUES & PRODUCT CHARACTERISTICS

Characteristic	Unit	Value	Comments
Thickness	mm	0.7	
Width	mm	120	
Weight	g/m	44	
Thermal resistance	°C	> -30 < 90	
Water impermeability	bar	> 1.5	EN 1928
Fire behaviour		B2 E	DIN 4102-1 DIN 13501-1
Elongation at fracture (lengthways)	%	50	EN ISO 527-3
Elongation at fracture (transverse)	%	200	EN ISO 527-3

All technical values are laboratory results determined at 21°C ±2°C and 50% relative humidity.

delivery form	MC-FastTape - 50 m roll MC-FastTape IE - 10 internal corners / package MC-FastTape AE - 10 external corners / package
Storage	
colour shade	blue

Safety instructions

Please note the safety information and advice given on the packaging labels and safety data sheets.

Note: The information contained in this data sheet is based on our experience and is correct to the best of our knowledge. It is, however, not binding. It will need to be adapted to the requirements of the individual structure, to the specific application and to non-standard local conditions. Application-specific conditions must be checked in advance by the planning engineer/specifier and, where different from the standard conditions indicated, will require individual approval. Technical advice provided by MC's specialist consultants does not replace the need for a planning review by the client or its agents in respect of the history of the building or structure. Subject to this prerequisite, we are liable for the correctness of this information within the framework of our terms and conditions of sale and delivery. Recommendations of our employees deviating from the information given in our data sheets are only binding for us if they are confirmed in writing. In all cases, the generally accepted rules and practices reflecting the current state of the art must be observed. The information given in this technical data sheet is valid for the product supplied by the country company listed in the footer. It should be noted that data in other countries may differ. The product data sheets valid for the relevant foreign country must be observed. The latest technical data sheet shall apply to the exclusion of previous, duly superseded versions; the date of issue in the footer must be observed. The latest version is available from us on request or may be downloaded from our website. [2100004642]