

MC-Montan Grout 02

Additive for two-component grouting mortar (A/B annular gap mortar)



PRODUCT PROPERTIES

- Improved stabilization
- Reduction of viscosity
- Dispersing effect
- Optimizes pumpability
- Long slump retention

AREAS OF APPLICATION

- Backfill grout for tunnel boring machines with a shield
- (A/B Backfill Grout) for sensitive areas / urban areas
- Additive for Component A

APPLICATION ADVICE

MC-Montan Grout 02 is an additive for improving the properties of the hydraulic binders.

MC-Montan Grout 02 has a stabilizing and dispersing effect on the composition of the component A and improves the pumpability.

At the same time, MC-Montan Grout 02 can be set to extend the processing time up to 96 hours.

The dosage is dependent on the composition of component A and the desired processing time. A customary dosage is 5 kg to 12 kg per m³.

MC-Montan Grout 02 can be used with all common dosing devices.

"MC-Business Unit Tunnelling" is available for individual recommendation and optimization of the application on site.

TECHNICAL VALUES & PRODUCT CHARACTERISTICS

Characteristic	Unit	Value	Comments
Density	kg/dm ³	1.05 - 1.07	
Designation of admixture		MC-Montan Grout 02	
Colour		yellowish	
Form		liquid	
In-company production control		EN ISO 9001	
Storage		Can be stored in cool and dry conditions for at least 12 months in original unopened packs. Protect from frost. Protect from direct sun radiation.	
Delivery form		200 kg drums 1.000 kg IBC	

Safety instructions

Please note the safety information and advice given on the packaging labels and safety data sheets.

Note: The information contained in this data sheet is based on our experience and is correct to the best of our knowledge. It is, however, not binding. It will need to be adapted to the requirements of the individual structure, to the specific application and to non-standard local conditions. Application-specific conditions must be checked in advance by the planning engineer/specifier and, where different from the standard conditions indicated, will require individual approval. Technical advice provided by MC's specialist consultants does not replace the need for a planning review by the client or its agents in respect of the history of the building or structure. Subject to this prerequisite, we are liable for the correctness of this information within the framework of our terms and conditions of sale and delivery. Recommendations of our employees deviating from the information given in our data sheets are only binding for us if they are confirmed in writing. In all cases, the generally accepted rules and practices reflecting the current state of the art must be observed. The information given in this technical data sheet is valid for the product supplied by the country company listed in the footer. It should be noted that data in other countries may differ. The product data sheets valid for the relevant foreign country must be observed. The latest technical data sheet shall apply to the exclusion of previous, duly superseded versions; the date of issue in the footer must be observed. The latest version is available from us on request or may be downloaded from our website. [2300018447]