

MC-Tool Rubber

Rubber rubbing board for concrete cosmetic purposes



PRODUCT PROPERTIES

- Tool for fine and super fine Concrete Cosmetics
- Ergonomic wooden handle
- Made of abrasion resistant rubber

AREAS OF APPLICATION

- For floating of Concrete Cosmetics
 - Especially for fine and super fine Concrete Cosmetics
 - For small and large area fillings
 - For pore and cavity fillings
- For economical floating of fillers without loss of excess material
- For floating of Concrete Cosmetics for exposed concrete quality

APPLICATION ADVICE

MC-Tool Rubber is a special developed tool for the application of fine and super fine Concrete Cosmetic fillers of MC.

Substrate preparation for Concrete Cosmetics: The substrate must be clean, solid, able to bear loads and free from anti adhesive substances.

The substrate has to be pre-wetted so that it is semidry yet still absorbent. When repairing deep damage, honey combs etc. the moist substrate should be treated previously with a primer and after with a coarse filler.

Application: The fine and super fine filler is poured into the measured water and stirred with a slow rotating agitator until it has a lump free, workable consistency. The mixture is then to be applied evenly with the rubber float MC-Tool Rubber.

After the filler has almost set, the surface can be smoothed with MC-Tool Sponge. First of all the sponge should be pre-wetted so that the surface can be easily emulsified.

Further Information: MC-Tool Rubber is especially for pore and cavity fillings. The soft and abrasion resistant rubber float has been developed especially for individual processing so that light pressure can be applied partial where necessary.

Colour changes may appear during processing!

MC-Tool Rubber should only be washed with clean water.

After treatment: Surfaces treated with MC-Tool Rubber have to receive after treatment as quickly as possible to protect them from fast drying from sun and wind exposure.

TECHNICAL VALUES & PRODUCT CHARACTERISTICS

Characteristic	Unit	Value	Comments
Application conditions	°C	≥ 5	air, substrate and material temperatures
Equipment cleaning agent		clean water	
Delivery form		Box of 2 pieces	
Storage		Can be stored in cool and dry conditions for at least 12 months in original unopened packs.	
Colour		grey	

Safety instructions

Please note the safety information and advice given on the packaging labels and safety data sheets.

Note: The information contained in this data sheet is based on our experience and is correct to the best of our knowledge. It is, however, not binding. It will need to be adapted to the requirements of the individual structure, to the specific application and to non-standard local conditions. Application-specific conditions must be checked in advance by the planning engineer/specifier and, where different from the standard conditions indicated, will require individual approval. Technical advice provided by MC's specialist consultants does not replace the need for a planning review by the client or its agents in respect of the history of the building or structure. Subject to this prerequisite, we are liable for the correctness of this information within the framework of our terms and conditions of sale and delivery. Recommendations of our employees deviating from the information given in our data sheets are only binding for us if they are confirmed in writing. In all cases, the generally accepted rules and practices reflecting the current state of the art must be observed. The information given in this technical data sheet is valid for the product supplied by the country company listed in the footer. It should be noted that data in other countries may differ. The product data sheets valid for the relevant foreign country must be observed. The latest technical data sheet shall apply to the exclusion of previous, duly superseded versions; the date of issue in the footer must be observed. The latest version is available from us on request or may be downloaded from our website. [2300018364]