



Mycoflex BI-Band Primer

Primer

Product Properties

- Ready-to-use
- Solvent-containing acrylate resin
- Sealing effect
- Application with roller and brush

Areas of Application

- Special primer on Mycoflex BI-Band for subsequent colour design with MC-Color Flex pure, MC-Color Flex pro, MC-Color Flex vision und Zentrifix CR finish

Application

Substrate Preparation

The Mycoflex BI-Band must be clean, dry and free from loose particles, dust, oil and any other contaminants.

Application

Mycoflex BI-Band Primer must be mixed thorough-

ly prior to application. Application may be carried out using rollers or brushes.

Application must not be carried out in case of rain, high humidity, frost or risk of frost. Freshly applied layers must be protected against dew, rain and frost.



Product Characteristics for Mycoflex BI-Band Primer

Characteristic	Unit	Value*	Comment
Density	g/cm ³	1.26	
Min. waiting time until overcoating	hours	4 - 6	
Touch-dry	hours	approx. 4	
Coverage	g/m	approx. 80 - 100	
Rain-proof	hours	approx. 4 - 8	
Application conditions	°C %	≥ 8 - ≤ 30 ≤ 85	air-, material- and substrate temperature relative humidity

Product Characteristics for Mycoflex BI-Band Primer

Delivery	1 kg packs (4 x 1 kg per box)
Storage	Can be stored in cool (below 20 °C) and dry conditions for at least 24 months in original unopened packs. Protect from frost!
Disposal	Packs must be emptied completely.
EU-regulation 2004/42 (Decopaint standard)	Mycoflex BI-Band Primer: RL2004/42/EG All/i (500 g/l) < 500 g/l VOC

* All technical data are lab values and relate to + 23 °C and 50 % relative humidity.

Note: The information on this data sheet is based on our experiences and correct to the best of our knowledge. It is, however, not binding. It has to be adjusted to the individual structure, application purpose and especially to local conditions. Our data refers to the accepted engineering rules, which have to be observed during application. This provided we are liable for the correctness of this data within the scope of our terms and conditions of sale-delivery-and-service. Recommendations of our employees which differ from the data contained in our information sheets are only binding if given in written form. The accepted engineering rules must be observed at all times.

Edition 07/16. Some technical changes have been made to this print medium. Older editions are invalid and may not be used anymore. If a technically revised new edition is issued, this edition becomes invalid.