

Nafuflex GRID 25 NF

Reinforcing insert made of glass fibre fabric



PRODUCT PROPERTIES

- Water and weather-proof
- Can be used outside and inside
- For the reinforcement of Nafuflex bituminous coating systems

AREAS OF APPLICATION

- Used to proof constructions - between two layers of the bituminous coating system
- Applicable to proof existing construction joints, cracks and penetrations

APPLICATION ADVICE

Handling: The reinforcing inlay Nafuflex GRID 25 NF has to be incorporated directly into the first layer of the bituminous coating system.

The reinforcing inlay has to be cut to the required length, incorporated in the moist layer and flattened by hand or with an adequate tool.

Overlapping of inlays of at least from 10 cm is coercive at inlays ends.

Further Information: For further information please consult the Technical Data-Sheets of the respective Nafuflex-products.

TECHNICAL VALUES & PRODUCT CHARACTERISTICS

Characteristic	Unit	Value	Comments
Density	g/m ²	70	
Width	m	1	
Length	m	50	
Mesh size	mm	5	squared
Consumption	m/m ²	approx. 1.1	

All technical values are laboratory results determined at 21°C ±2°C and 50% relative humidity.

colour shade	white
area	50 m ²
delivery form	50 m strip, width 1 m
Storage	

Safety instructions

Please note the safety information and advice given on the packaging labels and safety data sheets. GISCODE : BBP10

Note: The information contained in this data sheet is based on our experience and is correct to the best of our knowledge. It is, however, not binding. It will need to be adapted to the requirements of the individual structure, to the specific application and to non-standard local conditions. Application-specific conditions must be checked in advance by the planning engineer/specifier and, where different from the standard conditions indicated, will require individual approval. Technical advice provided by MC's specialist consultants does not replace the need for a planning review by the client or its agents in respect of the history of the building or structure. Subject to this prerequisite, we are liable for the correctness of this information within the framework of our terms and conditions of sale and delivery. Recommendations of our employees deviating from the information given in our data sheets are only binding for us if they are confirmed in writing. In all cases, the generally accepted rules and practices reflecting the current state of the art must be observed. The information given in this technical data sheet is valid for the product supplied by the country company listed in the footer. It should be noted that data in other countries may differ. The product data sheets valid for the relevant foreign country must be observed. The latest technical data sheet shall apply to the exclusion of previous, duly superseded versions; the date of issue in the footer must be observed. The latest version is available from us on request or may be downloaded from our website. [2100004692]